

184393K250RBA-F

184393K250RBA-F Information



Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



184393K250RBA-F Specifications

Series 184 Capacitance 0.039µF Tolerance ±10% Voltage Rating - AC 160V Voltage Rating - DC 250V Dielectric Material Polyester, Metallized ESR (Equivalent Series Resistance) - Operating Temperature -55°C ~ 125°C Mounting Type Through Hole Size / Dimension 0.413" L x 0.157" W (10.50mm x 4.00mm) Height - Seated (Max) 0.354" (9.00mm) Termination PC Pins		
CategoryCapacitorsPackageRadialSeries184Capacitance0.039µFTolerance±10%Voltage Rating - AC660 VVoltage Rating - BC250VDieteric Material-Operating Temperature-Operating Type55°C ~ 125°CMounting Type541°GPackage / Case641°JSiz / Dimension0.413° L x 0.157° W (10.50mm x 4.00mm)Height - Seated (Max)0.25° (7.50mm)Applications6000000000000000000000000000000000000	Manufacturer Part Number	184393K250RBA-F
Fin CapacitorsPackageRadialSeries184Capacitance0.039µFTolerance±10%Voltage Rating - AC160VVoltage Rating - DC250VDielectric MaterialPolyester, MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 125°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.413° L x 0.157° W (10.50mm x 4.00mm)Height - Seated (Max)0.354″ (9.00mm)Lead Spacing0.295° (7.50mm)ApplicationsGeneral PurposeFeatures-	Manufacturer	Cornell Dubilier Electronics (CDE)
PackageRadialSeries184Capacitance0.039µFTolerance±10%Voltage Rating - AC160VVoltage Rating - DC250VDielectric MaterialPolyester, MetallizedDSR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 125°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.413" L x 0.157" W (10.50mm x 4.00mm)Height - Seated (Max)0.254" (9.00mm)Lead Spacing0.295" (7.50mm)ApplicationsGeneral PurposeFeatures-	Category	Capacitors
Series 184 Capacitance 0.039µF Tolerance ±10% Voltage Rating - AC 160V Voltage Rating - DC 250V Dielectric Material Polyester, Metallized ESR (Equivalent Series Resistance) - Operating Temperature -55°C ~ 125°C Mounting Type Radial Size / Dimension 0.413" L x 0.157" W (10.50mm x 4.00mm) Height - Seated (Max) 0.354" (9.00mm) Lead Spacing 0.295" (7.50mm) Applications General Purpose Features -		Film Capacitors
Capacitance0.039μFTolerance±10%Voltage Rating - AC160VVoltage Rating - DC250VDielectric MaterialPolyester, MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 125°CMounting TypeRatialPackage / CaseRadialSize / Dimension0.413" L x 0.157" W (10.50mm x 4.00mm)Height - Seated (Max)0.255" (7.50mm)Lead Spacing0.295" (7.50mm)ApplicationsGeneral PurposeFeatures-	Package	Radial
Tolerance±10%Voltage Rating - AC160VVoltage Rating - DC250VDielectric MaterialPolyester, MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 125°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.413" L x 0.157" W (10.50mm x 4.00mm)Height - Seated (Max)0.354" (9.00mm)TerminationPC PinsLead Spacing0.295" (7.50mm)ApplicationsGeneral PurposeFeatures-	Series	184
NotifiedDescriptionVoltage Rating - AC160VVoltage Rating - DC250VDielectric MaterialPolyester, MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 125°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.413" L x 0.157" W (10.50mm x 4.00mm)Height - Seated (Max)0.354" (9.00mm)TerminationPC PinsLead Spacing0.295" (7.50mm)ApplicationsGeneral PurposeFeatures-	Capacitance	0.039µF
Voltage Rating - DC250VDielectric MaterialPolyester, MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 125°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.413" L x 0.157" W (10.50mm x 4.00mm)Height - Seated (Max)0.354" (9.00mm)TerminationPC PinsLead Spacing0.295" (7.50mm)ApplicationsGeneral PurposeFeatures-	Tolerance	$\pm 10\%$
Dielectric MaterialPolyester, MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 125°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.413" L x 0.157" W (10.50mm x 4.00mm)Height - Seated (Max)0.354" (9.00mm)TerminationPC PinsLead Spacing0.295" (7.50mm)ApplicationsGeneral PurposeFeatures-	Voltage Rating - AC	160V
ESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 125°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.413" L x 0.157" W (10.50mm x 4.00mm)Height - Seated (Max)0.354" (9.00mm)TerminationPC PinsLead Spacing0.295" (7.50mm)ApplicationsGeneral PurposeFeatures-	Voltage Rating - DC	250V
Operating Temperature-55°C ~ 125°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.413" L x 0.157" W (10.50mm x 4.00mm)Height - Seated (Max)0.354" (9.00mm)TerminationPC PinsLead Spacing0.295" (7.50mm)ApplicationsGeneral PurposeFeatures-	Dielectric Material	Polyester, Metallized
I we be inMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.413" L x 0.157" W (10.50mm x 4.00mm)Height - Seated (Max)0.354" (9.00mm)TerminationPC PinsLead Spacing0.295" (7.50mm)ApplicationsGeneral PurposeFeatures-	ESR (Equivalent Series Resistance)	-
Package / CaseRadialSize / Dimension0.413" L x 0.157" W (10.50mm x 4.00mm)Height - Seated (Max)0.354" (9.00mm)TerminationPC PinsLead Spacing0.295" (7.50mm)ApplicationsGeneral PurposeFeatures-	Operating Temperature	-55°C ~ 125°C
Size / Dimension 0.413" L x 0.157" W (10.50mm x 4.00mm) Height - Seated (Max) 0.354" (9.00mm) Termination PC Pins Lead Spacing 0.295" (7.50mm) Applications General Purpose Features -	Mounting Type	Through Hole
Height - Seated (Max)0.354" (9.00mm)TerminationPC PinsLead Spacing0.295" (7.50mm)ApplicationsGeneral PurposeFeatures-	Package / Case	Radial
TerminationPC PinsLead Spacing0.295" (7.50mm)ApplicationsGeneral PurposeFeatures-	Size / Dimension	0.413" L x 0.157" W (10.50mm x 4.00mm)
Lead Spacing0.295" (7.50mm)ApplicationsGeneral PurposeFeatures-	Height - Seated (Max)	0.354" (9.00mm)
ApplicationsGeneral PurposeFeatures-	Termination	PC Pins
Features -	Lead Spacing	0.295" (7.50mm)
	Applications	General Purpose
Report errors?	Features	-
		Report errors?

184393K250RBA-F Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE ELARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

184393K250RBA-F Payment Methods





If you have any question about 184393K250RBA-F, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com