

1882610000

1882610000 Information

Heisener.com	Part Number Manufacturer Category Description Package	1882610000 Weidmuller Connectors, Interconnects Terminal Blocks - Din Rail, Channel CONN TERM BLK FEED THRU 10-28AWG - For the pricing/inventory/lead time, please contact	
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



1882610000 Specifications

Manufacturer Part Number 188261000 Manufacturer Veidmuller Category Connectors, Interconnects Package - Package - Series P Type Feed Through (2), Isolated Disconnect Type - Number of Positions 5 Number of Levels 3, 1 Grounded Termination Style Seland Current - IEC 32A Voltage - IEC 400V Voltage - IEC 300V Vire Gauge or Range - AWG 0.54 Am2 Vire Gauge or Range - AWG 0.54 Am2		
CategoryConnectors, InterconnectsTerminal Blocks - Din Rail, ChannelPackage-SeriesPTypeFeed Through (2), IsolatedDisconnect Type-Number of Positions5Number of Levels3; 1 GroundedTerminal - Width5Terminal - Width5Current - LEC32AVoltage - IEC400VVoltage - UL17AVoltage - Range - AWG10-28 AWGWire Gauge or Range - AWG0.5-4mm²Features-ColorBeige	Manufacturer Part Number	1882610000
Terminal Blocks - Din Rail, ChannelPackage-SeriesPTypeFeed Through (2), IsolatedDisconnect Type-Number of Positions5Number of Levels3; 1 GroundedTerminal - Width5.1mmTermination StylePush In, SpringCurrent - IEC32AVoltage - IEC400VVoltage - UL300VWire Gauge or Range - AWG10-28 AWGWire Gauge or Range - amount-Features-ColorBeige	Manufacturer	Weidmuller
Package-SeriesPTypeFeed Through (2), IsolatedDisconnect Type-Number of Positions5Number of Levels3, I GroundedTerminal - Width5.1mmTermination StylePush In, SpringCurrent - IEC32AVoltage - IEC400VVoltage - UL30VWire Gauge or Range - AWG0.5-4mm²Vire Gauge or Range - AMG-Features-ColorBeige	Category	Connectors, Interconnects
SeriesPTypeFeed Through (2), IsolatedDisconnect Type-Number of Positions5Number of Levels3; 1 GroundedTerminal - Width5.1mmTermination StylePush In, SpringCurrent - IEC32AVoltage - IEC400VCurrent - UL17AVoltage or Range - AWG0.28 AWGWire Gauge or Range - and Comparison0.54mm²Features-ColorBeige		Terminal Blocks - Din Rail, Channel
TypeFeed Through (2), IsolatedDisconnect Type-Number of Positions5Number of Levels3; 1 GroundedTerminal - Width5.1mmTermination StylePush In, SpringCurrent - IEC32AVoltage - IEC400VCurrent - UL17AVoltage or Range - AWG10-28 AWGWire Gauge or Range - mm²0.5-4mm²Features-ColorBeige	Package	-
Disconnect Type-Number of Positions5Number of Levels3; 1 GroundedTerminal - Width5.1mmTermination StylePush In, SpringCurrent - IEC32AVoltage - IEC400VCurrent - UL17AVoltage - UL300VWire Gauge or Range - AWG10-28 AWGWire Gauge or Range - mar ² 0.5-4mm ² Features-ColorBige	Series	Р
Number of Positions5Number of Levels3; 1 GroundedTerminal - Width5.1mmTermination StylePush In, SpringCurrent - IEC32AVoltage - IEC400VCurrent - UL17AVoltage - UL300VWire Gauge or Range - AWG10-28 AWGWire Gauge or Range - mm²0.5-4mm²Features-ColorBeige	Туре	Feed Through (2), Isolated
Number of Levels3; 1 GroundedTerminal - Width5.1mmTermination StylePush In, SpringCurrent - IEC32AVoltage - IEC400VCurrent - UL17AVoltage - UL300VWire Gauge or Range - AWG10-28 AWGWire Gauge or Range - mm²0.5-4mm²Features-ColorBeige	Disconnect Type	-
Terminal - Width5.1mmTermination StylePush In, SpringCurrent - IEC32AVoltage - IEC400VCurrent - UL17AVoltage - UL300VWire Gauge or Range - AWG10-28 AWGWire Gauge or Range - mm²0.5-4mm²Features-ColorBeige	Number of Positions	5
Termination StylePush In, SpringCurrent - IEC32AVoltage - IEC400VCurrent - UL17AVoltage - UL300VWire Gauge or Range - AWG10-28 AWGWire Gauge or Range - mar ² 0.5-4mm ² Features-ColorBeige	Number of Levels	3; 1 Grounded
Current - IEC32AVoltage - IEC400VCurrent - UL17AVoltage - UL300VWire Gauge or Range - AWG10-28 AWGWire Gauge or Range - mm²0.5-4mm²Features-ColorBeige	Terminal - Width	5.1mm
Voltage - IEC400VCurrent - UL17AVoltage - UL300VWire Gauge or Range - AWG10-28 AWGWire Gauge or Range - mm²0.5-4mm²Features-ColorBeige	Termination Style	Push In, Spring
Current - UL17AVoltage - UL300VWire Gauge or Range - AWG10-28 AWGWire Gauge or Range - mm²0.5-4mm²Features-ColorBeige	Current - IEC	32A
Voltage - UL300VWire Gauge or Range - AWG10-28 AWGWire Gauge or Range - mm²0.5-4mm²Features-ColorBeige	Voltage - IEC	400V
Wire Gauge or Range - AWG10-28 AWGWire Gauge or Range - mm²0.5-4mm²Features-ColorBeige	Current - UL	17A
Wire Gauge or Range - mm²0.5-4mm²Features-ColorBeige	Voltage - UL	300V
Features - Color Beige	Wire Gauge or Range - AWG	10-28 AWG
Color Beige	Wire Gauge or Range - mm ²	0.5-4mm ²
	Features	-
Report errors?	Color	Beige
		Report errors?

1882610000 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE GUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.



If you have any question about 1882610000, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com