



### 19022B2US Information

Heisener.com

19022B2US Part Number

Manufacturer TE Connectivity Potter & Brumfield Relays

Category

Signal Relays, Up to 2 Amps

RELAY GEN PURPOSE DPDT 2A 12V **Description** 

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# 19022B2US Specifications

Manufacturer Part Number  Manufacturer  TE Connectivity Potter & Brumfield Relays  Relays  Signal Relays, Up to 2 Amps  Package  - Series  190  Relay Type  General Purpose  Coil Type  Non Latching  Coil Current  12.5mA  Coil Voltage  12VDC  Contact Form  DPDT (2 Form C)  Contact Rating (Current)  2A  Switching Voltage  125VAC, 125VDC - Max  Turn On Voltage (Max)  Turn Off Voltage (Min)  0.6 VDC  Operate Time  Release Time  3ms  Sealed Falls:	_	
Category         Relays           Signal Relays, Up to 2 Amps           Package         -           Series         190           Relay Type         General Purpose           Coil Type         Non Latching           Coil Current         12.5mA           Coil Voltage         12VDC           Contact Form         DPDT (2 Form C)           Contact Rating (Current)         2A           Switching Voltage         125VAC, 125VDC - Max           Turn On Voltage (Max)         9 VDC           Turn Off Voltage (Min)         0.6 VDC           Operate Time         7ms           Release Time         3ms	Manufacturer Part Number	19022B2US
Package         -           Series         190           Relay Type         General Purpose           Coil Type         Non Latching           Coil Current         12.5mA           Coil Voltage         12VDC           Contact Form         DPDT (2 Form C)           Contact Rating (Current)         2A           Switching Voltage         125VAC, 125VDC - Max           Turn On Voltage (Max)         9 VDC           Turn Off Voltage (Min)         0.6 VDC           Operate Time         7ms           Release Time         3ms	Manufacturer	TE Connectivity Potter & Brumfield Relays
Package - 190  Relay Type General Purpose  Coil Type Non Latching  Coil Current 12.5mA  Coil Voltage 12VDC  Contact Form DPDT (2 Form C)  Contact Rating (Current) 2A  Switching Voltage 125VAC, 125VDC - Max  Turn On Voltage (Max) 9 VDC  Turn Off Voltage (Min) 0.6 VDC  Operate Time 7ms  Release Time 3ms	Category	Relays
Series190Relay TypeGeneral PurposeCoil TypeNon LatchingCoil Current12.5mACoil Voltage12VDCContact FormDPDT (2 Form C)Contact Rating (Current)2ASwitching Voltage125VAC, 125VDC - MaxTurn On Voltage (Max)9 VDCTurn Off Voltage (Min)0.6 VDCOperate Time7msRelease Time3ms		Signal Relays, Up to 2 Amps
Relay TypeGeneral PurposeCoil TypeNon LatchingCoil Current12.5mACoil Voltage12VDCContact FormDPDT (2 Form C)Contact Rating (Current)2ASwitching Voltage125VAC, 125VDC - MaxTurn On Voltage (Max)9 VDCTurn Off Voltage (Min)0.6 VDCOperate Time7msRelease Time3ms	Package	-
Coil TypeNon LatchingCoil Current12.5mACoil Voltage12VDCContact FormDPDT (2 Form C)Contact Rating (Current)2ASwitching Voltage125VAC, 125VDC - MaxTurn On Voltage (Max)9 VDCTurn Off Voltage (Min)0.6 VDCOperate Time7msRelease Time3ms	Series	190
Coil Current12.5mACoil Voltage12VDCContact FormDPDT (2 Form C)Contact Rating (Current)2ASwitching Voltage125VAC, 125VDC - MaxTurn On Voltage (Max)9 VDCTurn Off Voltage (Min)0.6 VDCOperate Time7msRelease Time3ms	Relay Type	General Purpose
Coil Voltage12VDCContact FormDPDT (2 Form C)Contact Rating (Current)2ASwitching Voltage125VAC, 125VDC - MaxTurn On Voltage (Max)9 VDCTurn Off Voltage (Min)0.6 VDCOperate Time7msRelease Time3ms	Coil Type	Non Latching
Contact Form DPDT (2 Form C)  Contact Rating (Current) 2A  Switching Voltage 125VAC, 125VDC - Max  Turn On Voltage (Max) 9 VDC  Turn Off Voltage (Min) 0.6 VDC  Operate Time 7ms  Release Time 3ms	Coil Current	12.5mA
Contact Rating (Current)  Switching Voltage  125VAC, 125VDC - Max  Turn On Voltage (Max)  9 VDC  Turn Off Voltage (Min)  0.6 VDC  Operate Time  7ms  Release Time  3ms	Coil Voltage	12VDC
Switching Voltage 125VAC, 125VDC - Max Turn On Voltage (Max) 9 VDC Turn Off Voltage (Min) 0.6 VDC Operate Time 7ms Release Time 3ms	Contact Form	DPDT (2 Form C)
Turn On Voltage (Max)  9 VDC  Turn Off Voltage (Min)  0.6 VDC  Operate Time  7ms  Release Time  3ms	Contact Rating (Current)	2A
Turn Off Voltage (Min) Operate Time 7ms Release Time 3ms	Switching Voltage	125VAC, 125VDC - Max
Operate Time7msRelease Time3ms	Turn On Voltage (Max)	9 VDC
Release Time 3ms	Turn Off Voltage (Min)	0.6 VDC
	Operate Time	7ms
Factories Carled Fully	Release Time	3ms
reatures Sealed - runy	Features	Sealed - Fully
Mounting Type Through Hole	Mounting Type	Through Hole
Termination Style PC Pin	Termination Style	PC Pin
Report errors?		Report errors?

#### 19022B2US Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

# 19022B2US Payment Methods



















## 19022B2US Shipping Methods













If you have any question about 19022B2US, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com