

19200031250 Information



For Reference Only

Part Number 19200031250 **Manufacturer** HARTING

Category Connectors, Interconnects

Heavy Duty Connectors - Housings, Hoods, Bases

Description CONN BASE SIDE ENTRY SZ3A M20

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









19200031250 Specifications

Manufacturer Part Number 19200031250 Manufacturer HARTING Category Connectors, Interconnects Package - Series Han? A Connector Type Base - Panel Mount 90° Style Side Entry Size 3A Lock Location Locking Clip (1) on Base Bottom Thread Size M20 Size / Dimension 1.102" L x 1.575" W x 1.071" H (28.00mm x 40.00mm x 27.20mm) Housing Color Gray Features - Ingress Protection IP44 Housing Material Zinc, Die Cast Housing Finish Powder Coated Operating Temperature -40°C ~ 125°C	1)200031230 Specifications		
Category Connectors, Interconnects Heavy Duty Connectors - Housings, Hoods, Bases Package - Series Han? A Connector Type Base - Panel Mount 90° Style Side Entry Size 3A Lock Location Locking Clip (1) on Base Bottom Thread Size M20 Size / Dimension 1.102" L x 1.575" W x 1.071" H (28.00mm x 40.00mm x 27.20mm) Housing Color Gray Features Ingress Protection IP44 Housing Material Zinc, Die Cast Housing Finish Powder Coated Operating Temperature -40°C ~ 125°C	Manufacturer Part Number	19200031250	
Heavy Duty Connectors - Housings, Hoods, Bases Package - Series Han? A Connector Type Base - Panel Mount 90° Style Side Entry Size 3A Lock Location Locking Clip (1) on Base Bottom Thread Size M20 Size / Dimension 1.102" L x 1.575" W x 1.071" H (28.00mm x 40.00mm x 27.20mm) Housing Color Gray Features - Ingress Protection IP44 Housing Material Zinc, Die Cast Housing Finish Powder Coated Operating Temperature -40°C ~ 125°C	Manufacturer	HARTING	
Package-SeriesHan? AConnector TypeBase - Panel Mount 90°StyleSide EntrySize3ALock LocationLocking Clip (1) on Base BottomThread SizeM20Size / Dimension1.102" L x 1.575" W x 1.071" H (28.00mm x 40.00mm x 27.20mm)Housing ColorGrayFeatures-Ingress ProtectionIP44Housing MaterialZinc, Die CastHousing FinishPowder CoatedOperating Temperature-40°C ~ 125°C	Category	Connectors, Interconnects	
SeriesHan? AConnector TypeBase - Panel Mount 90°StyleSide EntrySize3ALock LocationLocking Clip (1) on Base BottomThread SizeM20Size / Dimension1.102" L x 1.575" W x 1.071" H (28.00mm x 40.00mm x 27.20mm)Housing ColorGrayFeatures-Ingress ProtectionIP44Housing MaterialZinc, Die CastHousing FinishPowder CoatedOperating Temperature-40°C ~ 125°C		Heavy Duty Connectors - Housings, Hoods, Bases	
Connector Type Base - Panel Mount 90° Style Side Entry 3A Lock Location Locking Clip (1) on Base Bottom Thread Size M20 Size / Dimension 1.102" L x 1.575" W x 1.071" H (28.00mm x 40.00mm x 27.20mm) Housing Color Gray Features Ingress Protection IP44 Housing Material Zinc, Die Cast Housing Finish Powder Coated Operating Temperature - 40°C ~ 125°C	Package	-	
Style Side Entry Size 3A Lock Location Locking Clip (1) on Base Bottom Thread Size M20 Size / Dimension 1.102" L x 1.575" W x 1.071" H (28.00mm x 40.00mm x 27.20mm) Housing Color Gray Features - Ingress Protection IP44 Housing Material Zinc, Die Cast Housing Finish Powder Coated Operating Temperature -40°C ~ 125°C	Series	Han? A	
Size 3A Lock Location Locking Clip (1) on Base Bottom Thread Size M20 Size / Dimension 1.102" L x 1.575" W x 1.071" H (28.00mm x 40.00mm x 27.20mm) Housing Color Gray Features - Ingress Protection IP44 Housing Material Zinc, Die Cast Housing Finish Powder Coated Operating Temperature -40°C ~ 125°C	Connector Type	Base - Panel Mount 90°	
Lock LocationLocking Clip (1) on Base BottomThread SizeM20Size / Dimension1.102" L x 1.575" W x 1.071" H (28.00mm x 40.00mm x 27.20mm)Housing ColorGrayFeatures-Ingress ProtectionIP44Housing MaterialZinc, Die CastHousing FinishPowder CoatedOperating Temperature-40°C ~ 125°C	Style	Side Entry	
Thread Size $M20$ Size / Dimension 1.102 " L x 1.575 " W x 1.071 " H (28.00 mm x 40.00 mm x 27.20 mm) Housing Color Gray Features - Ingress Protection IP44 Housing Material Zinc, Die Cast Housing Finish Powder Coated Operating Temperature $-40^{\circ}\text{C} \sim 125^{\circ}\text{C}$	Size	3A	
Size / Dimension 1.102" L x 1.575" W x 1.071" H (28.00mm x 40.00mm x 27.20mm) Housing Color Gray Features - Ingress Protection IP44 Housing Material Zinc, Die Cast Housing Finish Powder Coated Operating Temperature -40°C ~ 125°C	Lock Location	Locking Clip (1) on Base Bottom	
Housing ColorGrayFeatures-Ingress ProtectionIP44Housing MaterialZinc, Die CastHousing FinishPowder CoatedOperating Temperature $-40^{\circ}\text{C} \sim 125^{\circ}\text{C}$	Thread Size	M20	
Features - Ingress Protection IP44 Housing Material Zinc, Die Cast Housing Finish Powder Coated Operating Temperature -40°C ~ 125°C	Size / Dimension	1.102" L x 1.575" W x 1.071" H (28.00mm x 40.00mm x 27.20mm)	
Ingress ProtectionIP44Housing MaterialZinc, Die CastHousing FinishPowder CoatedOperating Temperature $-40^{\circ}\text{C} \sim 125^{\circ}\text{C}$	Housing Color	Gray	
Housing Material Zinc, Die Cast Housing Finish Powder Coated Operating Temperature $-40^{\circ}\text{C} \sim 125^{\circ}\text{C}$	Features	-	
Housing Finish Powder Coated Operating Temperature $-40^{\circ}\text{C} \sim 125^{\circ}\text{C}$	Ingress Protection	IP44	
Operating Temperature $-40^{\circ}\text{C} \sim 125^{\circ}\text{C}$	Housing Material	Zinc, Die Cast	
	Housing Finish	Powder Coated	
Report errors?	Operating Temperature	-40°C ~ 125°C	
			Report errors?

19200031250 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

19200031250 Payment Methods



















19200031250 Shipping Methods













If you have any question about 19200031250, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com