

# 19461160250

#### 19461160250 Information





Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



### 19461160250 Specifications

Manufacturer Part Number19461160250ManufacturerHARTINGCategoryConnectors. InterconnectsHeavy Duty Connectors - Housings, Hoods, BasesPackage-SeriesHan-Eco?Connector TypeBase - Box MountStyleSide EntrySizeIGALock LocationLocking Clip (1) on Base BottomThread SizeJackForensionSides' x 1.969" X 1.850" H (80.50mm x 47.00mm)Foatures-Foatures-Housing CholorHost Type, Nylon, Glass FilledHousing Material-Housing Finish-Operating Temperature40°C ~ 125°CKentor-Kentor-Kentor-Kentor-Kentor-Kentor-Kentor-Kentor-Kentor-Kentor-Kentor-Kentor-Kentor-Kentor-Kentor-Kentor-Kentor-Kentor-Kentor-Kentor-Kentor-Kentor-Kentor-Kentor-Kentor-Kentor-Kentor-Kentor-Kentor-Kentor-Kentor-Kentor-Kentor-<			
CategoryConnectors, Interconnects Heavy Duty Connectors - Housings, Hoods, BasesPackage-PackageInterco?SeriesHan-Eco?Connector TypeBase - Box MountStyleSide EntrySize16ALock LocationLocking Clip (1) on Base BottomThread SizeM20Size/ Dimension3.169" L x 1.969" W x 1.850" H (80.50mm x 50.00mm x 47.00mm)Housing ColorBackFeatures-Housing MaterialPolyamide (PA), Nylon, Glass FilledHousing Finish-Operating Temperature-40°C ~ 12°C	Manufacturer Part Number	19461160250	
Heavy Duty Connectors - Housings, Hoods, BasesPackage-SeriesHan-Eco?Connector TypeBase - Box MountStyleSide EntrySize16ALock LocationLocking Clip (1) on Base BottomThread SizeM20Size / DimensionSilo9" L x 1.969" W x 1.850" H (80.50mm x 50.00mm x 47.00mm)Housing ColorBlackFeatures-Ingress ProtectionP65 - Dust Tight, Water ResistantHousing Material-Housing Finish-Qperating Temperature40°C ~ 125°C	Manufacturer	HARTING	
Package-SeriesHan-Eco?Connector TypeBase - Box MountStyleSide EntrySize16ALock LocationLocking Clip (1) on Base BottomThread SizeM20Size / Dimension3.169" L x 1.969" W x 1.850" H (80.50mm x 50.00mm x 47.00mm)Housing ColorBlackFeatures-Housing MaterialPolyamide (PA), Nylon, Glass FilledHousing Finish-Qperating Temperature-40°C ~ 125°C	Category	Connectors, Interconnects	
Series Han-Eco?   Connector Type Base - Box Mount   Style Side Entry   Size I6A   Lock Location Locking Clip (1) on Base Bottom   Thread Size M20   Size / Dimension 3.169" L x 1.969" W x 1.850" H (80.50mm x 47.00mm x 47.00mm)   Foatures -   Ingress Protection M26   Housing Material Polyamide Resistant   Housing Finish -   Ausing Finish -   Yoperating Temperature 40°C ~ 125°C		Heavy Duty Connectors - Housings, Hoods, Bases	
Connector TypeBase - Box MountStyleSide EntrySize16ALock LocationLocking Clip (1) on Base BottomThread SizeM20Size / Dimension3.169" L x 1.969" W x 1.850" H (80.50mm x 50.00mm x 47.00mm)Housing ColorBlackFeatures-Ingress ProtectionP65 - Dust Tight, Water ResistantHousing Finish-Operating Temperature-40°C ~ 125°C	Package	-	
StyleSide EntrySize16ALock LocationLocking Clip (1) on Base BottomThread SizeM20Size / Dimension3.169" L x 1.969" W x 1.850" H (80.50mm x 50.00mm x 47.00mm)Housing ColorBlackFeatures-Ingress ProtectionIP65 - Dust Tight, Water ResistantHousing Material-Housing Finish-Operating Temperature-40°C ~ 125°C	Series	Han-Eco?	
Size16ALock LocationLocking Clip (1) on Base BottomThread SizeM20Size / Dimension3.169" L x 1.969" W x 1.850" H (80.50mm x 50.00mm x 47.00mm)Housing ColorBlackFeatures-Ingress ProtectionIP65 - Dust Tight, Water ResistantHousing MaterialPolyamide (PA), Nylon, Glass FilledHousing Finish-Operating Temperature-40°C ~ 125°C	Connector Type	Base - Box Mount	
Lock LocationLocking Clip (1) on Base BottomThread SizeM20Size / Dimension3.169" L x 1.969" W x 1.850" H (80.50mm x 50.00mm x 47.00mm)Housing ColorBlackFeatures-Ingress ProtectionP65 - Dust Tight, Water ResistantHousing MaterialPolyamide (PA), Nylon, Glass FilledHousing Finish-40°C ~ 125°C	Style	Side Entry	
Thread SizeM20Size / Dimension3.169" L x 1.969" W x 1.850" H (80.50mm x 50.00mm x 47.00mm)Housing ColorBlackFeatures-Ingress ProtectionIP65 - Dust Tight, Water ResistantHousing MaterialPolyamide (PA), Nylon, Glass FilledHousing Finish-Operating Temperature-40°C ~ 125°C	Size	16A	
Size / Dimension3.169" L x 1.969" W x 1.850" H (80.50mm x 50.00mm x 47.00mm)Housing ColorBlackFeatures-Ingress ProtectionIP65 - Dust Tight, Water ResistantHousing MaterialPolyamide (PA), Nylon, Glass FilledHousing Finish-Operating Temperature-40°C ~ 125°C	Lock Location	Locking Clip (1) on Base Bottom	
Housing ColorBlackFeatures-Ingress ProtectionIP65 - Dust Tight, Water ResistantHousing MaterialPolyamide (PA), Nylon, Glass FilledHousing Finish-Operating Temperature-40°C ~ 125°C	Thread Size	M20	
Features-Ingress ProtectionIP65 - Dust Tight, Water ResistantHousing MaterialPolyamide (PA), Nylon, Glass FilledHousing Finish-Operating Temperature-40°C ~ 125°C	Size / Dimension	3.169" L x 1.969" W x 1.850" H (80.50mm x 50.00mm x 47.00mm)	
Ingress ProtectionIP65 - Dust Tight, Water ResistantHousing MaterialPolyamide (PA), Nylon, Glass FilledHousing Finish-Operating Temperature-40°C ~ 125°C	Housing Color	Black	
Housing MaterialPolyamide (PA), Nylon, Glass FilledHousing Finish-Operating Temperature-40°C ~ 125°C	Features	-	
Housing Finish-Operating Temperature-40°C ~ 125°C	Ingress Protection	IP65 - Dust Tight, Water Resistant	
Operating Temperature -40°C ~ 125°C	Housing Material	Polyamide (PA), Nylon, Glass Filled	
	Housing Finish	-	
Report errors?	Operating Temperature	-40°C ~ 125°C	
			Report errors?

#### 19461160250 Guarantees



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

# SERVICE BUARANTEE

#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

#### 

If you have any question about 19461160250, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com