

## 195D105X9016C4T

#### 195D105X9016C4T Information

www.helseyer.com	 195D105X9016C4T Vishay Sprague Capacitors Tantalum Capacitors CAP TANT 1UF 16V 10% 0905 0905 (2114 Metric) For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

### **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



#### 195D105X9016C4T Specifications

Manufacturer Part Number195D105X9016C4TManufacturerVishay SpragueCategoryCapacitorsPackage0905 (2114 Metric)SeriesTANTAMOUNT?, 195DCapacitanceµFTolerance±10%Voltage - Rated16VTypeConformal CoatedDeparting Temperature-55°C ~ 125°CLifetime @ Temp.005 (2114 Metric)Mounting TypeSurface MountPackage / Case005 (2114 Metric)Nouting Type-55°C ~ 125°CLifetime @ Temp015 (2114 Metric)Package / Case005 (2114 Metric)Nouting Type005 (2114 Metric)Height - Seated (Max)005°T (1 39mm)Lead Spacing-Height - Seated (Max)0.55° (1 39mm)Lead Spacing-FeaturesGeneral PurposeFaiture Rate-Faiture Rate- <td< th=""><th></th><th></th></td<>		
CategoryCapacitorsCategoryTantalum CapacitorsPackage0905 (2114 Metric)PackageGopo (2114 Metric)SeriesTANTAMOUNT?, 195DCapacitance1µFTolerance±10%Voltage - Rated16VTypeConformal CoatedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 125°CLifetime @ TempMounting TypeSurface MountPackage / Case0905 (2114 Metric)Size / Dimension0.087" L x 0.045" W (2.21mm x 1.14mm)Height - Seated (Max)0.055" (1.39mm)Lead Spacing-FeaturesGeneral Purpose	Manufacturer Part Number	195D105X9016C4T
Autalum CapacitorsPackage0905 (2114 Metric)SeriesTANTAMOUNT?, 195DCapacitance1µFTolerance±10%Voltage - Rated16VTypeConformal CoatedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 125°CLifetime @ TempMounting TypeSurface MountSize / Dimension0,087" L x 0,045" W (2.21mm x 1.14mm)Height - Seated (Max)0,055" (1.39mm)Lead Spacing-FaturesCFeaturesCFeaturesGeneral Purpose	Manufacturer	Vishay Sprague
Package0905 (2114 Metric)SeriesTANTAMOUNT?, 195DCapacitance1µFTolerance±10%Voltage - Rated16VTypeConformal CoatedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 125°CLifetime @ Temp.Surface MountMounting TypeSurface MountSize / Dimension0.087" L x 0.045" W (2.21mm x 1.14mm)Height - Seated (Max)0.055" (1.39mm)Lead SpacingCFaturesGeneral Purpose	Category	Capacitors
SeriesTANTAMOUNT?, 195DCapacitanceIµFTolerance±10%Voltage - Rated16VTypeConformal CoatedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 125°CLifetime @ Temp.Surface MountPackage / Case0905 (2114 Metric)Size / Dimension0.087" L x 0.045" W (2.21mm x 1.14mm)Height - Seated (Max)0.055" (1.39mm)Lead Spacing-FeaturesGeneral Purpose		Tantalum Capacitors
CapacitanceIµFTolerance±10%Voltage - Rated16VTypeConformal CoatedType-ESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 125°CLifetime @ TempMounting TypeSurface MountPackage / Case0905 (2114 Metric)Size / Dimension0.087" L x 0.045" W (2.21mm x 1.14mm)Height - Seated (Max)0.055" (1.39mm)Lead SpacingCManufacturer Size CodeCFeaturesGeneral Purpose	Package	0905 (2114 Metric)
Tolerance±10%Voltage - Rated16VTypeConformal CoatedType-ESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 125°CLifetime @ TempMounting TypeSurface MountPackage / Case0905 (2114 Metric)Size / Dimension0.055" (1.39mm)Height - Seated (Max)-Lead Spacing-FaturesGeneral PurposeFeaturesC	Series	TANTAMOUNT?, 195D
NoticeDescriptionVoltage - Rated16VTypeConformal CoatedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 125°CLifetime @ TempMounting TypeSurface MountPackage / Case0905 (2114 Metric)Size / Dimension0.087" L x 0.045" W (2.21mm x 1.14mm)Height - Seated (Max)0.055" (1.39mm)Lead Spacing-Manufacturer Size CodeCFeaturesGeneral Purpose	Capacitance	1μF
Type Conformal Coated   ESR (Equivalent Series Resistance) -   Operating Temperature -55°C ~ 125°C   Lifetime @ Temp. -   Mounting Type Surface Mount   Package / Case 0905 (2114 Metric)   Size / Dimension 0.087" L x 0.045" W (2.21mm x 1.14mm)   Height - Seated (Max) 0.055" (1.39mm)   Lead Spacing -   Manufacturer Size Code C   Features General Purpose	Tolerance	$\pm 10\%$
FractionFractionESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 125°CLifetime @ TempMounting TypeSurface MountPackage / Case0905 (2114 Metric)Size / Dimension0.087" L x 0.045" W (2.21mm x 1.14mm)Height - Seated (Max)0.055" (1.39mm)Lead Spacing-Manufacturer Size CodeCFeaturesGeneral Purpose	Voltage - Rated	16V
Operating Temperature -55°C ~ 125°C   Lifetime @ Temp. -   Mounting Type Surface Mount   Package / Case 0905 (2114 Metric)   Size / Dimension 0.087" L x 0.045" W (2.21mm x 1.14mm)   Height - Seated (Max) 0.055" (1.39mm)   Lead Spacing -   Manufacturer Size Code C   Features General Purpose	Туре	Conformal Coated
Lifetime @ TempMounting TypeSurface MountPackage / Case0905 (2114 Metric)Size / Dimension0.087" L x 0.045" W (2.21mm x 1.14mm)Height - Seated (Max)0.055" (1.39mm)Lead Spacing-Manufacturer Size CodeCFeaturesGeneral Purpose	ESR (Equivalent Series Resistance)	-
Mounting TypeSurface MountPackage / Case0905 (2114 Metric)Size / Dimension0.087" L x 0.045" W (2.21mm x 1.14mm)Height - Seated (Max)0.055" (1.39mm)Lead Spacing-Manufacturer Size CodeCFeaturesGeneral Purpose	Operating Temperature	-55°C ~ 125°C
Package / Case0905 (2114 Metric)Size / Dimension0.087" L x 0.045" W (2.21mm x 1.14mm)Height - Seated (Max)0.055" (1.39mm)Lead Spacing-Manufacturer Size CodeCFeaturesGeneral Purpose	Lifetime @ Temp.	-
Size / Dimension 0.087" L x 0.045" W (2.21mm x 1.14mm)   Height - Seated (Max) 0.055" (1.39mm)   Lead Spacing -   Manufacturer Size Code C   Features General Purpose	Mounting Type	Surface Mount
Height - Seated (Max)0.055" (1.39mm)Lead Spacing-Manufacturer Size CodeCFeaturesGeneral Purpose	Package / Case	0905 (2114 Metric)
Lead Spacing-Manufacturer Size CodeCFeaturesGeneral Purpose	Size / Dimension	0.087" L x 0.045" W (2.21mm x 1.14mm)
Manufacturer Size CodeCFeaturesGeneral Purpose	Height - Seated (Max)	0.055" (1.39mm)
Features General Purpose	Lead Spacing	-
	Manufacturer Size Code	С
Failure Rate -	Features	General Purpose
	Failure Rate	-
Report errors?		Report errors?

#### 195D105X9016C4T Guarantees



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

# SERVICE BUARANTEE

#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

#### 195D105X9016C4T Payment Methods





If you have any question about 195D105X9016C4T, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com