


199D105X9020AXB1E3

199D105X9020AXB1E3 Information



nber	199D105X9020AXB1E3
turer	Vishay Sprague
Ÿ	Capacitors Tantalum Capacitors
ion	CAP TANT 1UF 20V 10% RADIAL
	Radial
	For the pricing/inventory/lead time, please contact
	us
	Website: https://www.heisener.com
	E-mail: salesdept@heisener.com



Request a Quote

For Reference Only

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



199D105X9020AXB1E3 Specifications

Manufacturer Vishay Sprague Category Capacitors Tantalum Capacitors Tantalum Capacitors Package Radial Series TANTALEX?, 199D Capacitance 1µF Tolerance ±10% Voltage - Rated 20V Type Conformal Coated ESR (Equivalent Series Resistance) - Operating Temperature -55°C ~ 125°C Lifetime @ Temp. - Mounting Type Radial Size / Dimension 0.173° Dia (4.40mm) Height - Seated (Max) 0.340° (8.64mm) Lad Spacing 0.100° (2.54mm) Manufacturer Size Code A Features General Purpose		
CategoryCapacitorsPackageRadialPackageRadialSeriesTANTALEX?, 199DCapacitance1µFTolerance±10%Voltage - Rated20VTypeConformal CoatedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 125°CLifetime @ TempMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.173" Dia (4.40mm)Height - Seated (Max)0.340" (8.64mm)Lad Spacing0.100" (2.54mm)Manufacturer Size CodeAFaituresGeneral PurposeFaiture Rate-	Manufacturer Part Number	199D105X9020AXB1E3
Tantalum CapacitorsPackageRadialSeriesTANTALEX?, 199DCapacitanceμFTolerance±10%Voltage - Rated20VYopeConformal CoatedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 125°CLifetime @ TempMounting TypeRadialPackage / CaseRadialSize / Dimension0.173" Dia (4.40mm)Height - Seated (Max)0.340" (8.64mm)Lead Spacing0.100" (2.54mm)Manufacturer Size CodeAFeaturesGeneral PurposeFailure Rate-	Manufacturer	Vishay Sprague
PackageRadialSeriesTANTALEX?, 199DCapacitance1µFTolerance±10%Voltage - Rated20VTypeConformal CoatedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 125°CLifetime @ TempMounting TypeRadialPackage / CaseRadialSize / Dimension0.173" Dia (4.40mm)Height - Seated (Max)0.340" (8.64mm)Lead Spacing0.100" (2.54mm)FaturesGeneral PurposeFailure Rate-	Category	Capacitors
Series TANTALEX?, 199D Capacitance 1µF Tolerance ±10% Voltage - Rated 20V Type Conformal Coated ESR (Equivalent Series Resistance) - Operating Temperature -55°C ~ 125°C Lifetime @ Temp. - Mounting Type Through Hole Package / Case Radial Size / Dimension 0.173" Dia (4.40mm) Height - Seated (Max) 0.340" (8.64mm) Lad Spacing 0.100" (2.54mm) Features General Purpose Failure Rate -		Tantalum Capacitors
CapacitanceIµFTolerance±10%Voltage - Rated20VTypeConformal CoatedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 125°CLifetime @ TempMounting TypeRadialPackage / CaseRadialSize / Dimension0.1073" Dia (4.40mm)Height - Seated (Max)0.340" (8.64mm)Lad Spacing0.100" (2.54mm)Manufacturer Size CodeAFeaturesGeneral PurposeFailure Rate-	Package	Radial
Tolerance±10%Voltage - Rated20VTypeConformal CoatedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 125°CLifetime @ TempMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.173" Dia (4.40mm)Height - Seated (Max)0.340" (8.64mm)Lead Spacing0.100" (2.54mm)Manufacturer Size CodeAFeaturesGeneral PurposeFailure Rate-	Series	TANTALEX?, 199D
Voltage - Rated20VTypeConformal CoatedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 125°CLifetime @ TempMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.173" Dia (4.40mm)Height - Seated (Max)0.340" (8.64mm)Lead SpacingAManufacturer Size CodeAFeaturesGeneral PurposeFailure Rate-	Capacitance	1µF
TypeConformal CoatedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 125°CLifetime @ TempMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.173" Dia (4.40mm)Height - Seated (Max)0.340" (8.64mm)Lead SpacingAManufacturer Size CodeAFeaturesGeneral PurposeFailure Rate-	Tolerance	±10%
Final-ESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 125°CLifetime @ TempMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.173" Dia (4.40mm)Height - Seated (Max)0.340" (8.64mm)Lead Spacing0.100" (2.54mm)Manufacturer Size CodeAFeaturesGeneral PurposeFailure Rate-	Voltage - Rated	20V
Operating Temperature-55°C ~ 125°CLifetime @ TempMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.173" Dia (4.40mm)Height - Seated (Max)0.340" (8.64mm)Lead Spacing0.100" (2.54mm)Manufacturer Size CodeAFeaturesGeneral PurposeFailure Rate-	Туре	Conformal Coated
Lifetime @ TempMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.173" Dia (4.40mm)Height - Seated (Max)0.340" (8.64mm)Lead Spacing0.100" (2.54mm)Manufacturer Size CodeAFeaturesGeneral PurposeFailure Rate-	ESR (Equivalent Series Resistance)	-
Mounting TypeThrough HolePackage / CaseRadialPackage / Case0.173" Dia (4.40mm)Size / Dimension0.340" (8.64mm)Height - Seated (Max)0.340" (8.64mm)Lead Spacing0.100" (2.54mm)Manufacturer Size CodeAFeaturesGeneral PurposeFailure Rate-	Operating Temperature	-55°C ~ 125°C
Package / CaseRadialSize / Dimension0.173" Dia (4.40mm)Height - Seated (Max)0.340" (8.64mm)Lead Spacing0.100" (2.54mm)Manufacturer Size CodeAFeaturesGeneral PurposeFailure Rate-	Lifetime @ Temp.	-
Size / Dimension0.173" Dia (4.40mm)Height - Seated (Max)0.340" (8.64mm)Lead Spacing0.100" (2.54mm)Manufacturer Size CodeAFeaturesGeneral PurposeFailure Rate-	Mounting Type	Through Hole
Height - Seated (Max)0.340" (8.64mm)Lead Spacing0.100" (2.54mm)Manufacturer Size CodeAFeaturesGeneral PurposeFailure Rate-	Package / Case	Radial
Lead Spacing0.100" (2.54mm)Manufacturer Size CodeAFeaturesGeneral PurposeFailure Rate-	Size / Dimension	0.173" Dia (4.40mm)
Manufacturer Size CodeAFeaturesGeneral PurposeFailure Rate-	Height - Seated (Max)	0.340" (8.64mm)
Features General Purpose Failure Rate -	Lead Spacing	0.100" (2.54mm)
Failure Rate -	Manufacturer Size Code	А
	Features	General Purpose
Report errors?	Failure Rate	-
		Report errors?

199D105X9020AXB1E3 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

199D105X9020AXB1E3 Payment Methods



If you have any question about 199D105X9020AXB1E3, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com