



19C015PV2L Information

Heisener.com

19C015PV2L Part Number

Manufacturer Honeywell Sensing and Productivity Solutions

Category Sensors, Transducers

Pressure Sensors, Transducers

Description SENSOR PRESSURE VAC GAUGE 15PSI

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









19C015PV2L Specifications

Manufacturer Part Number 19C015PV2L Manufacturer Honeywell Sensing and Productivity Solutions Category Sensors, Transducers Package Cylinder Series 19 mm Pressure Type Vacuum Operating Pressure -15 PSI (-103.42 kPa) Output Type Wheatstone Bridge Output 0 mV ~ 100 mV Accuracy ±0.25% Voltage - Supply - Port Size - Port Syle No Port Features Temperature Compensated Termination Style PC Pin, Wire Leads Maximum Pressure -45 PSI (-310.26 kPa) Operating Temperature -40°C ~ 125°C Package / Case Cylinder Supplier Device Package - Report errors?		
Category Sensors, Transducers Package Cylinder Series 19 mm Pressure Type Vacuum Operating Pressure -15 PSI (-103.42 kPa) Output Type Wheatstone Bridge Output 0 mV ~ 100 mV Accuracy ±0.25% Voltage - Supply - Port Size - Port Style No Port Features Temperature Compensated Termination Style PC Pin, Wire Leads Maximum Pressure -45 PSI (-310.26 kPa) Operating Temperature -40°C ~ 125°C Package / Case Cylinder Supplier Device Package -	Manufacturer Part Number	19C015PV2L
Package Cylinder Series 19 mm Pressure Type Vacuum Operating Pressure -15 PSI (-103.42 kPa) Output Type Wheatstone Bridge Output 0 mV ~ 100 mV Accuracy ±0.25% Voltage - Supply - Port Size - Port Style No Port Features Temperature Compensated Termination Style PC Pin, Wire Leads Maximum Pressure -45 PSI (-310.26 kPa) Operating Temperature -40°C ~ 125°C Package / Case Cylinder Supplier Device Package -	Manufacturer	Honeywell Sensing and Productivity Solutions
PackageCylinderSeries19 mmPressure TypeVacuumOperating Pressure-15 PSI (-103.42 kPa)Output TypeWheatstone BridgeOutput0 mV ~ 100 mVAccuracy±0.25%Voltage - Supply-Port Size-Port StyleNo PortFeaturesTemperature CompensatedTermination StylePC Pin, Wire LeadsMaximum Pressure-45 PSI (-310.26 kPa)Operating Temperature-40°C ~ 125°CPackage / CaseCylinderSupplier Device Package-	Category	Sensors, Transducers
Series19 mmPressure TypeVacuumOperating Pressure-15 PSI (-103.42 kPa)Output TypeWheatstone BridgeOutput0 mV ~ 100 mVAccuracy±0.25%Voltage - Supply-Port Size-Port StyleNo PortFeaturesTemperature CompensatedTermination StylePC Pin, Wire LeadsMaximum Pressure-45 PSI (-310.26 kPa)Operating Temperature-40°C ~ 125°CPackage / CaseCylinderSupplier Device Package-		Pressure Sensors, Transducers
Pressure Type Vacuum Operating Pressure -15 PSI (-103.42 kPa) Output Type Wheatstone Bridge Output 0 mV ~ 100 mV Accuracy ±0.25% Voltage - Supply - Port Size - Port Style No Port Features Temperature Compensated Termination Style PC Pin, Wire Leads Maximum Pressure -45 PSI (-310.26 kPa) Operating Temperature -40°C ~ 125°C Package / Case Cylinder Supplier Device Package	Package	Cylinder
Operating Pressure Output Type Wheatstone Bridge Output Output On W ~ 100 mV Accuracy ±0.25% Voltage - Supply - Port Size - Port Style No Port Features Temperature Compensated Termination Style PC Pin, Wire Leads Maximum Pressure -45 PSI (-310.26 kPa) Operating Temperature Package / Case Supplier Device Package - Supplier Device Package -15 PSI (-103.42 kPa) Wheatstone Bridge Wheatstone Bridge Wheatstone Bridge No PV TemVe Automatical Style PC Pin, Wire Leads -45 PSI (-310.26 kPa) -40°C ~ 125°C	Series	19 mm
Output TypeWheatstone BridgeOutput0 mV ~ 100 mVAccuracy±0.25%Voltage - Supply-Port Size-Port StyleNo PortFeaturesTemperature CompensatedTermination StylePC Pin, Wire LeadsMaximum Pressure-45 PSI (-310.26 kPa)Operating Temperature-40°C ~ 125°CPackage / CaseCylinderSupplier Device Package-	Pressure Type	Vacuum
Output0 mV ~ 100 mVAccuracy±0.25%Voltage - Supply-Port Size-Port StyleNo PortFeaturesTemperature CompensatedTermination StylePC Pin, Wire LeadsMaximum Pressure-45 PSI (-310.26 kPa)Operating Temperature-40°C ~ 125°CPackage / CaseCylinderSupplier Device Package-	Operating Pressure	-15 PSI (-103.42 kPa)
Accuracy ±0.25% Voltage - Supply - Port Size - Port Style No Port Features Temperature Compensated Termination Style PC Pin, Wire Leads Maximum Pressure -45 PSI (-310.26 kPa) Operating Temperature -40°C ~ 125°C Package / Case Cylinder Supplier Device Package -	Output Type	Wheatstone Bridge
Voltage - Supply Port Size Port Style No Port Features Temperature Compensated Termination Style PC Pin, Wire Leads Maximum Pressure -45 PSI (-310.26 kPa) Operating Temperature -40°C ~ 125°C Package / Case Cylinder Supplier Device Package	Output	$0 \text{ mV} \sim 100 \text{ mV}$
Port Size - Port Style No Port Features Temperature Compensated Termination Style PC Pin, Wire Leads Maximum Pressure -45 PSI (-310.26 kPa) Operating Temperature -40°C ~ 125°C Package / Case Cylinder Supplier Device Package -	Accuracy	±0.25%
Port Style No Port Features Temperature Compensated Termination Style PC Pin, Wire Leads Maximum Pressure -45 PSI (-310.26 kPa) Operating Temperature -40°C ~ 125°C Package / Case Cylinder Supplier Device Package -	Voltage - Supply	-
Features Temperature Compensated Termination Style PC Pin, Wire Leads Maximum Pressure -45 PSI (-310.26 kPa) Operating Temperature -40°C ~ 125°C Package / Case Cylinder Supplier Device Package -	Port Size	-
Termination Style PC Pin, Wire Leads Maximum Pressure -45 PSI (-310.26 kPa) Operating Temperature -40°C ~ 125°C Package / Case Cylinder Supplier Device Package -	Port Style	No Port
Maximum Pressure -45 PSI (-310.26 kPa) Operating Temperature -40°C ~ 125°C Package / Case Cylinder Supplier Device Package -	Features	Temperature Compensated
Operating Temperature -40°C ~ 125°C Package / Case Cylinder Supplier Device Package -	Termination Style	PC Pin, Wire Leads
Package / Case Cylinder Supplier Device Package -	Maximum Pressure	-45 PSI (-310.26 kPa)
Supplier Device Package -	Operating Temperature	-40°C ~ 125°C
	Package / Case	Cylinder
Report errors?	Supplier Device Package	-
		Report errors?

19C015PV2L Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

19C015PV2L Payment Methods



















19C015PV2L Shipping Methods













If you have any question about 19C015PV2L, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com