

1N5610 Information



For Reference Only

Part Number 1N5610

ManufacturerMicrosemi CorporationCategoryCircuit Protection

TVS - Diodes

Description TVS DIODE 30.5VWM 47.6VC G-PKG

Package G, Axial

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









1N5610 Specifications

Manufacturer Part Number IN5610 Manufacturer Microsemi Corporation Category Circuit Protection TVS - Diodes Package G, Axial Series - Type Zener Unidirectional Channels 1 Bidirectional Channels - Voltage - Reverse Standoff (Typ) 30.5V Voltage - Breakdown (Min) 33V Voltage - Clamping (Max) @ Ipp 47.6V Current - Peak Pulse (10/1000µs) 32A Power - Peak Pulse 1500W (1.5kW) Power Line Protection No Applications General Purpose Capacitance @ Frequency - Operating Temperature -55°C ~ 175°C (TJ) Mounting Type Through Hole Package / Case G, Axial Supplier Device Package G, Axial	•	
Category Circuit Protection TVS - Diodes Package G, Axial Series - Type Zener Unidirectional Channels 1 Bidirectional Channels - Voltage - Reverse Standoff (Typ) 30.5V Voltage - Breakdown (Min) 33V Voltage - Clamping (Max) @ Ipp 47.6V Current - Peak Pulse (10/1000µs) 32A Power - Peak Pulse 1500W (1.5kW) Power Line Protection No Applications General Purpose Capacitance @ Frequency - Operating Temperature -55°C ~ 175°C (TJ) Mounting Type Through Hole Package / Case G, Axial Supplier Device Package G, Axial	Manufacturer Part Number	1N5610
Package G, Axial Series - Type Zener Unidirectional Channels 1 Bidirectional Channels - Voltage - Reverse Standoff (Typ) 30.5V Voltage - Breakdown (Min) 33V Voltage - Clamping (Max) @ Ipp 47.6V Current - Peak Pulse (10/1000μs) 32A Power - Peak Pulse 1500W (1.5kW) Power Line Protection No Applications General Purpose Capacitance @ Frequency - Operating Temperature -55°C ~ 175°C (TJ) Mounting Type Through Hole Package / Case G, Axial Supplier Device Package G, Axial	Manufacturer	Microsemi Corporation
PackageG, AxialSeries-TypeZenerUnidirectional Channels1Bidirectional Channels-Voltage - Reverse Standoff (Typ)30.5VVoltage - Breakdown (Min)33VVoltage - Clamping (Max) @ Ipp47.6VCurrent - Peak Pulse (10/1000μs)32APower - Peak Pulse1500W (1.5kW)Power Line ProtectionNoApplicationsGeneral PurposeCapacitance @ Frequency-Operating Temperature-55°C ~ 175°C (TJ)Mounting TypeThrough HolePackage / CaseG, AxialSupplier Device PackageG, Axial	Category	Circuit Protection
Series-TypeZenerUnidirectional Channels1Bidirectional Channels-Voltage - Reverse Standoff (Typ)30.5VVoltage - Breakdown (Min)33VVoltage - Clamping (Max) @ Ipp47.6VCurrent - Peak Pulse (10/1000μs)32APower - Peak Pulse1500W (1.5kW)Power Line ProtectionNoApplicationsGeneral PurposeCapacitance @ Frequency-Operating Temperature-55°C ~ 175°C (TJ)Mounting TypeThrough HolePackage / CaseG, AxialSupplier Device PackageG, Axial		TVS - Diodes
Type Zener Unidirectional Channels Bidirectional Channels - Voltage - Reverse Standoff (Typ) 30.5V Voltage - Breakdown (Min) Voltage - Clamping (Max) @ Ipp 47.6V Current - Peak Pulse (10/1000µs) Power - Peak Pulse 1500W (1.5kW) Power Line Protection No Applications General Purpose Capacitance @ Frequency Operating Temperature -55°C ~ 175°C (TJ) Mounting Type Through Hole Package / Case G, Axial Supplier Device Package	Package	G, Axial
Unidirectional Channels Bidirectional Channels - Voltage - Reverse Standoff (Typ) 30.5V Voltage - Breakdown (Min) 33V Voltage - Clamping (Max) @ Ipp 47.6V Current - Peak Pulse (10/1000µs) 32A Power - Peak Pulse 1500W (1.5kW) Power Line Protection No Applications General Purpose Capacitance @ Frequency Operating Temperature -55°C ~ 175°C (TJ) Mounting Type Through Hole Package / Case G, Axial Supplier Device Package	Series	-
Bidirectional Channels-Voltage - Reverse Standoff (Typ)30.5VVoltage - Breakdown (Min)33VVoltage - Clamping (Max) @ Ipp47.6VCurrent - Peak Pulse (10/1000μs)32APower - Peak Pulse1500W (1.5kW)Power Line ProtectionNoApplicationsGeneral PurposeCapacitance @ Frequency-Operating Temperature-55°C ~ 175°C (TJ)Mounting TypeThrough HolePackage / CaseG, AxialSupplier Device PackageG, Axial	Туре	Zener
Voltage - Reverse Standoff (Typ) Voltage - Breakdown (Min) 33V Voltage - Clamping (Max) @ Ipp 47.6V Current - Peak Pulse (10/1000µs) Power - Peak Pulse 1500W (1.5kW) Power Line Protection No Applications General Purpose Capacitance @ Frequency Operating Temperature -55°C ~ 175°C (TJ) Mounting Type Through Hole Package / Case G, Axial Supplier Device Package	Unidirectional Channels	1
Voltage - Breakdown (Min)33VVoltage - Clamping (Max) @ Ipp47.6VCurrent - Peak Pulse (10/1000μs)32APower - Peak Pulse1500W (1.5kW)Power Line ProtectionNoApplicationsGeneral PurposeCapacitance @ Frequency-Operating Temperature-55°C ~ 175°C (TJ)Mounting TypeThrough HolePackage / CaseG, AxialSupplier Device PackageG, Axial	Bidirectional Channels	-
Voltage - Clamping (Max) @ Ipp47.6VCurrent - Peak Pulse (10/1000μs)32APower - Peak Pulse1500W (1.5kW)Power Line ProtectionNoApplicationsGeneral PurposeCapacitance @ Frequency-Operating Temperature-55°C ~ 175°C (TJ)Mounting TypeThrough HolePackage / CaseG, AxialSupplier Device PackageG, Axial	Voltage - Reverse Standoff (Typ)	30.5V
Current - Peak Pulse (10/1000µs) Power - Peak Pulse 1500W (1.5kW) Power Line Protection No Applications General Purpose Capacitance @ Frequency Operating Temperature -55°C ~ 175°C (TJ) Mounting Type Through Hole Package / Case G, Axial Supplier Device Package	Voltage - Breakdown (Min)	33V
Power - Peak Pulse 1500W (1.5kW) Power Line Protection No Applications General Purpose Capacitance @ Frequency - Operating Temperature -55°C ~ 175°C (TJ) Mounting Type Through Hole Package / Case G, Axial Supplier Device Package G, Axial	Voltage - Clamping (Max) @ Ipp	47.6V
Power Line Protection Applications General Purpose Capacitance @ Frequency Operating Temperature -55°C ~ 175°C (TJ) Mounting Type Through Hole Package / Case G, Axial Supplier Device Package	Current - Peak Pulse (10/1000µs)	32A
Applications Capacitance @ Frequency Operating Temperature -55°C ~ 175°C (TJ) Mounting Type Through Hole Package / Case G, Axial Supplier Device Package	Power - Peak Pulse	1500W (1.5kW)
Capacitance @ Frequency Operating Temperature -55°C ~ 175°C (TJ) Mounting Type Through Hole Package / Case G, Axial Supplier Device Package G, Axial	Power Line Protection	No
Operating Temperature -55°C ~ 175°C (TJ) Mounting Type Through Hole Package / Case G, Axial Supplier Device Package G, Axial	Applications	General Purpose
Mounting TypeThrough HolePackage / CaseG, AxialSupplier Device PackageG, Axial	Capacitance @ Frequency	-
Package / Case G, Axial Supplier Device Package G, Axial	Operating Temperature	-55°C ~ 175°C (TJ)
Supplier Device Package G, Axial	Mounting Type	Through Hole
	Package / Case	G, Axial
Donort arrows 9	Supplier Device Package	G, Axial
Report errors?		Report errors?

1N5610 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

1N5610 Payment Methods



















1N5610 Shipping Methods













If you have any question about 1N5610, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com