

1N6373-E3/51

Quote

1N6373-E3/51 Information

Heisener.com	Part Number	1N6373-E3/51	
	Manufacturer	Vishay Semiconductor Diodes Division	
	Category	Circuit Protection TVS - Diodes	- 6 233
	Description	TVS DIODE 5VWM 7.5VC 1.5KE	- 22941
	Package	DO-201AA, DO-27, Axial	
		For the pricing/inventory/lead time, please contact	티크크
For Reference Only		us	
		Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



1N6373-E3/51 Specifications

ManufacturerVishay Semiconductor Diodes DivisionCategoryCircuit ProtectionTVS - DiodesTVS - DiodesPackageDO-201AA, DO-27, AxialSeriesTransZorb?TypeZenerUndirectional Channels1Bidirectional Channels-Voltage - Reverse Standoff (Typ)5VVoltage - Breakdown (Min)6VVoltage - Clamping (Max) @ Ipp7.5VCurrent - Peak Pulse (10/1000µs)160APower Line ProtectionNoApplicationsGeneral PurposeCapacitance @ Frequency-Operating Temperature-55°C ~ 175°C (TJ)Mounting TypeThrough HolePackage / CaseDO-201AA, DO-27, AxialSupplier Device Package1.5KE		
CategoryCircuit ProtectionTVS - DiodesPackageDO-201AA, DO-27, AxialPackageDO-201AA, DO-27, AxialSeriesTransZorb?TypeZenerUnidirectional Channels1Bidirectional Channels-Voltage - Reverse Standoff (Typ)5VVoltage - Breakdown (Min)6VVoltage - Clamping (Max) @ Ipp7.5VCurrent - Peak Pulse (10/1000µs)160APower Line ProtectionNoApplicationsGeneral PurposeCapacitance @ Frequency-Operating Temperature55°C ~ 175°C (TJ)Mounting TypeThrough HolePackage / CaseDO-201AA, DO-27, AxialSupplier Device Package1.5KE	Manufacturer Part Number	1N6373-E3/51
TVS - DiodesPackageDO-201AA, DO-27, AxialSeriesTransZorb?TypeZenerUnidirectional Channels1Bidirectional Channels-Voltage - Reverse Standoff (Typ)5VVoltage - Breakdown (Min)6VVoltage - Clamping (Max) @ Ipp7.5VCurrent - Peak Pulse (10/1000µs)160APower Line ProtectionNoApplicationsGeneral PurposeCapacitance @ Frequency-Operating Temperature-55°C ~ 175°C (TJ)Mounting TypeThrough HolePackage / CaseDO-201AA, DO-27, AxialSupplier Device Package1.5KE	Manufacturer	Vishay Semiconductor Diodes Division
PackageDO-201AA, DO-27, AxialSeriesTransZorb?TypeZenerUnidirectional Channels1Bidirectional Channels-Voltage - Reverse Standoff (Typ)5VVoltage - Breakdown (Min)6VVoltage - Clamping (Max) @ Ipp160ACurrent - Peak Pulse (10/1000µs)160APower Line ProtectionNoApplicationsGeneral PurposeCapacitance @ Frequency-Operating Temperature-55°C ~ 175°C (TJ)Mounting TypeDo-201AA, DO-27, AxialSupplier Device Package1.5KE	Category	Circuit Protection
SeriesTransZorb?TypeZenerUnidirectional Channels1Bidirectional Channels-Voltage - Reverse Standoff (Typ)5VVoltage - Breakdown (Min)6VVoltage - Clamping (Max) @ Ipp7.5VCurrent - Peak Pulse (10/1000µs)160APower - Peak Pulse500W (1.5kW)Power Line ProtectionNoApplicationsGeneral PurposeCapacitance @ Frequency-Operating Type55° C ~ 175°C (TJ)Mounting TypeThrough HolePackage / CaseDo-201AA, DO-27, AxialSupplier Device Package1.5KE		TVS - Diodes
TypeZenerUnidirectional Channels1Bidirectional Channels-Voltage - Reverse Standoff (Typ)5VVoltage - Breakdown (Min)6VVoltage - Clamping (Max) @ Ipp7.5VCurrent - Peak Pulse (10/1000µs)160APower - Peak Pulse1500W (1.5kW)Power Line ProtectionNoApplicationsGeneral PurposeCapacitance @ Frequency-Operating Temperature-55°C ~175°C (TJ)Mounting TypeThrough HolePackage / Case1.5KE	Package	DO-201AA, DO-27, Axial
Unidirectional Channels1Bidirectional Channels-Voltage - Reverse Standoff (Typ)5VVoltage - Breakdown (Min)6VVoltage - Clamping (Max) @ Ipp7.5VCurrent - Peak Pulse (10/1000µs)160APower - Peak Pulse (10/1000µs)1500W (1.5kW)Power Line ProtectionNoApplicationsGeneral PurposeCapacitance @ Frequency-Operating Temperature-55°C ~175°C (TJ)Mounting TypeThrough HolePackage / CaseDO-201AA, DO-27, AxialSupplier Device Package1.5KE	Series	TransZorb?
Bidirectional Channels-Bidirectional Channels-Voltage - Reverse Standoff (Typ)5VVoltage - Breakdown (Min)6VVoltage - Clamping (Max) @ Ipp7.5VCurrent - Peak Pulse (10/1000µs)160APower - Peak Pulse (10/1000µs)1500W (1.5kW)Power - Peak Pulse1500W (1.5kW)Power Line ProtectionNoApplicationsGeneral PurposeCapacitance @ Frequency-Operating Temperature-55°C ~ 175°C (TJ)Mounting TypeThrough HolePackage / CaseDO-201AA, DO-27, AxialSupplier Device Package1.5KE	Туре	Zener
Voltage - Reverse Standoff (Typ)5VVoltage - Breakdown (Min)6VVoltage - Clamping (Max) @ Ipp7.5VCurrent - Peak Pulse (10/1000µs)160APower - Peak Pulse1500W (1.5kW)Power Line ProtectionNoApplicationsGeneral PurposeCapacitance @ Frequency-Operating Temperature-55°C ~ 175°C (TJ)Mounting TypeThrough HolePackage / CaseDO-201AA, DO-27, AxialSupplier Device Package1.5KE	Unidirectional Channels	1
Voltage - Breakdown (Min)6VVoltage - Clamping (Max) @ Ipp7.5VCurrent - Peak Pulse (10/1000µs)160APower - Peak Pulse (10/1000µs)1500W (1.5kW)Power Line ProtectionNoApplicationsGeneral PurposeCapacitance @ Frequency-Operating Temperature-55°C ~ 175°C (TJ)Mounting TypeThrough HolePackage / CaseDO-201AA, DO-27, AxialSupplier Device Package1.5KE	Bidirectional Channels	-
Voltage - Clamping (Max) @ Ipp7.5VCurrent - Peak Pulse (10/1000µs)160APower - Peak Pulse1500W (1.5kW)Power Line ProtectionNoApplicationsGeneral PurposeCapacitance @ Frequency-Operating Temperature-55°C ~ 175°C (TJ)Mounting TypeThrough HolePackage / CaseDO-201AA, DO-27, AxialSupplier Device Package1.5KE	Voltage - Reverse Standoff (Typ)	5V
Current - Peak Pulse (10/1000µs)160APower - Peak Pulse1500W (1.5kW)Power Line ProtectionNoApplicationsGeneral PurposeCapacitance @ Frequency-Operating Temperature-55°C ~ 175°C (TJ)Mounting TypeThrough HolePackage / CaseDO-201AA, DO-27, AxialSupplier Device Package1.5KE	Voltage - Breakdown (Min)	6V
Power - Peak Pulse1500W (1.5kW)Power Line ProtectionNoApplicationsGeneral PurposeCapacitance @ Frequency-Operating Temperature-55°C ~ 175°C (TJ)Mounting TypeThrough HolePackage / CaseDO-201AA, DO-27, AxialSupplier Device Package1.5KE	Voltage - Clamping (Max) @ Ipp	7.5V
Power Line ProtectionNoApplicationsGeneral PurposeCapacitance @ Frequency-Operating Temperature-55°C ~ 175°C (TJ)Mounting TypeThrough HolePackage / CaseDO-201AA, DO-27, AxialSupplier Device Package1.5KE	Current - Peak Pulse (10/1000µs)	160A
ApplicationsGeneral PurposeCapacitance @ Frequency-Operating Temperature-55°C ~ 175°C (TJ)Mounting TypeThrough HolePackage / CaseDO-201AA, DO-27, AxialSupplier Device Package1.5KE	Power - Peak Pulse	1500W (1.5kW)
Capacitance @ Frequency-Operating Temperature-55°C ~ 175°C (TJ)Mounting TypeThrough HolePackage / CaseDO-201AA, DO-27, AxialSupplier Device Package1.5KE	Power Line Protection	No
Operating Temperature-55°C ~ 175°C (TJ)Mounting TypeThrough HolePackage / CaseDO-201AA, DO-27, AxialSupplier Device Package1.5KE	Applications	General Purpose
Mounting TypeThrough HolePackage / CaseDO-201AA, DO-27, AxialSupplier Device Package1.5KE	Capacitance @ Frequency	-
Package / CaseDO-201AA, DO-27, AxialSupplier Device Package1.5KE	Operating Temperature	-55°C ~ 175°C (TJ)
Supplier Device Package 1.5KE	Mounting Type	Through Hole
	Package / Case	DO-201AA, DO-27, Axial
Report errors?	Supplier Device Package	1.5KE
		Report errors?

1N6373-E3/51 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

1N6373-E3/51 Payment Methods





If you have any question about 1N6373-E3/51, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com