

2-1393818-2 Information

Heisener.com

Part Number 2-1393818-2

Manufacturer TE Connectivity Potter & Brumfield Relays

Category

Signal Relays, Up to 2 Amps

RELAY GEN PURPOSE DPDT 200MA 72V **Description**

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









2-1393818-2 Specifications

Manufacturer Part Number 2-1393818-2 Manufacturer TE Connectivity Potter & Brumfield Relays Category Relays Signal Relays, Up to 2 Amps Package - Series V23162, AXICOM Relay Type General Purpose Coil Type Non Latching Coil Current 9.5mA Coil Voltage 72VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 200mA Switching Voltage 30VAC, 36VDC - Max Turn On Voltage (Max) 48.4 VDC Turn Off Voltage (Min) - Operate Time 7.5ms Release Time 3ms Features Sealed - Hermetically Mounting Type Socketable Termination Style Plug In		
CategoryRelaysPackage-SeriesV23162, AXICOMRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current9.5mACoil Voltage72VDCContact FormDPDT (2 Form C)Contact Rating (Current)200mASwitching Voltage30VAC, 36VDC - MaxTurn On Voltage (Max)48.4 VDCTurn Off Voltage (Min)-Operate Time7.5msRelease Time3msFeaturesSealed - HermeticallyMounting TypeSocketable	Manufacturer Part Number	2-1393818-2
Package - Series V23162, AXICOM Relay Type General Purpose Coil Type Non Latching Coil Current 9.5mA Coil Voltage 72VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 200mA Switching Voltage 30VAC, 36VDC - Max Turn On Voltage (Max) 48.4 VDC Turn Off Voltage (Min) - Operate Time 7.5ms Release Time 3ms Features Sealed - Hermetically Mounting Type Socketable	Manufacturer	TE Connectivity Potter & Brumfield Relays
Package - V23162, AXICOM Relay Type General Purpose Coil Type Non Latching Coil Current 9.5mA Coil Voltage 72VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 200mA Switching Voltage 30VAC, 36VDC - Max Turn On Voltage (Max) 48.4 VDC Turn Off Voltage (Min) - Operate Time 7.5ms Release Time 3ms Features Sealed - Hermetically Mounting Type Socketable	Category	Relays
SeriesV23162, AXICOMRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current9.5mACoil Voltage72VDCContact FormDPDT (2 Form C)Contact Rating (Current)200mASwitching Voltage30VAC, 36VDC - MaxTurn On Voltage (Max)48.4 VDCTurn Off Voltage (Min)-Operate Time7.5msRelease Time3msFeaturesSealed - HermeticallyMounting TypeSocketable		Signal Relays, Up to 2 Amps
Relay TypeGeneral PurposeCoil TypeNon LatchingCoil Current9.5mACoil Voltage72VDCContact FormDPDT (2 Form C)Contact Rating (Current)200mASwitching Voltage30VAC, 36VDC - MaxTurn On Voltage (Max)48.4 VDCTurn Off Voltage (Min)-Operate Time7.5msRelease Time3msFeaturesSealed - HermeticallyMounting TypeSocketable	Package	-
Coil Type Non Latching Coil Current 9.5mA Coil Voltage 72VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 200mA Switching Voltage 30VAC, 36VDC - Max Turn On Voltage (Max) 48.4 VDC Turn Off Voltage (Min) - Operate Time 7.5ms Release Time 3ms Release Time 3ms Features Sealed - Hermetically Mounting Type Socketable	Series	V23162, AXICOM
Coil Current9.5mACoil Voltage72VDCContact FormDPDT (2 Form C)Contact Rating (Current)200mASwitching Voltage30VAC, 36VDC - MaxTurn On Voltage (Max)48.4 VDCTurn Off Voltage (Min)-Operate Time7.5msRelease Time3msFeaturesSealed - HermeticallyMounting TypeSocketable	Relay Type	General Purpose
Coil Voltage 72VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 200mA Switching Voltage 30VAC, 36VDC - Max Turn On Voltage (Max) 48.4 VDC Turn Off Voltage (Min) - Operate Time 7.5ms Release Time 3ms Features Sealed - Hermetically Mounting Type Socketable	Coil Type	Non Latching
Contact Form DPDT (2 Form C) Contact Rating (Current) 200mA Switching Voltage 30VAC, 36VDC - Max Turn On Voltage (Max) 48.4 VDC Turn Off Voltage (Min) - Operate Time 7.5ms Release Time 3ms Features Sealed - Hermetically Mounting Type Socketable	Coil Current	9.5mA
Contact Rating (Current) Switching Voltage 30VAC, 36VDC - Max Turn On Voltage (Max) 48.4 VDC Turn Off Voltage (Min) Operate Time 7.5ms Release Time 3ms Features Sealed - Hermetically Mounting Type Socketable	Coil Voltage	72VDC
Switching Voltage 30VAC, 36VDC - Max Turn On Voltage (Max) 48.4 VDC Turn Off Voltage (Min) - Operate Time 7.5ms Release Time 3ms Features Sealed - Hermetically Mounting Type Socketable	Contact Form	DPDT (2 Form C)
Turn On Voltage (Max) Turn Off Voltage (Min) Operate Time 7.5ms Release Time 3ms Features Sealed - Hermetically Mounting Type Socketable	Contact Rating (Current)	200mA
Turn Off Voltage (Min) Operate Time 7.5ms Release Time 3ms Features Sealed - Hermetically Mounting Type Socketable	Switching Voltage	30VAC, 36VDC - Max
Operate Time 7.5ms Release Time 3ms Features Sealed - Hermetically Mounting Type Socketable	Turn On Voltage (Max)	48.4 VDC
Release Time 3ms Features Sealed - Hermetically Mounting Type Socketable	Turn Off Voltage (Min)	-
Features Sealed - Hermetically Mounting Type Socketable	Operate Time	7.5ms
Mounting Type Socketable	Release Time	3ms
	Features	Sealed - Hermetically
Termination Style Plug In	Mounting Type	Socketable
	Termination Style	Plug In
Report errors?		Report errors?

2-1393818-2 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

2-1393818-2 Payment Methods



















2-1393818-2 Shipping Methods













If you have any question about 2-1393818-2, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com