

2-1415391-1 Information

Heisener.com

Part Number 2-1415391-1

Manufacturer TE Connectivity Potter & Brumfield Relays

Category

Power Relays, Over 2 Amps

Description RELAY GEN PURPOSE SPDT 5A 24V

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









2-1415391-1 Specifications

Manufacturer Part Number 2-1415391-1 Manufacturer TE Connectivity Potter & Brumfield Relays Category Relays Power Relays, Over 2 Amps Package - Series PE Bistable, SCHRACK Relay Type General Purpose Coil Type Latching, Single Coil Coil Current 8.7mA Coil Voltage 24VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 5A Switching Voltage 400VAC - Max Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) - Operate Time 8ms Release Time 8ms Features Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin		
CategoryRelaysPower Relays, Over 2 AmpsPackage-SeriesPE Bistable, SCHRACKRelay TypeGeneral PurposeCoil TypeLatching, Single CoilCoil Current8.7mACoil Voltage24VDCContact FormSPDT (1 Form C)Contact Rating (Current)5ASwitching Voltage400VAC - MaxTurn On Voltage (Max)18 VDCTurn Off Voltage (Min)-Operate Time8msRelease Time8msFeaturesSealed - Flux ProtectionMounting TypeThrough HoleTermination StylePC Pin	Manufacturer Part Number	2-1415391-1
Package-SeriesPE Bistable, SCHRACKRelay TypeGeneral PurposeCoil TypeLatching, Single CoilCoil Current8.7mACoil Voltage24VDCContact FormSPDT (1 Form C)Contact Rating (Current)5ASwitching Voltage400VAC - MaxTurn On Voltage (Max)18 VDCTurn Off Voltage (Min)-Operate Time8msRelease Time8msFeaturesSealed - Flux ProtectionMounting TypeThrough HoleTermination StylePC Pin	Manufacturer	TE Connectivity Potter & Brumfield Relays
Package-SeriesPE Bistable, SCHRACKRelay TypeGeneral PurposeCoil TypeLatching, Single CoilCoil Current8.7mACoil Voltage24VDCContact FormSPDT (1 Form C)Contact Rating (Current)5ASwitching Voltage400VAC - MaxTurn On Voltage (Max)18 VDCTurn Off Voltage (Min)-Operate Time8msRelease Time8msFeaturesSealed - Flux ProtectionMounting TypeThrough HoleTermination StylePC Pin	Category	Relays
SeriesPE Bistable, SCHRACKRelay TypeGeneral PurposeCoil TypeLatching, Single CoilCoil Current8.7mACoil Voltage24VDCContact FormSPDT (1 Form C)Contact Rating (Current)5ASwitching Voltage400VAC - MaxTurn On Voltage (Max)18 VDCTurn Off Voltage (Min)-Operate Time8msRelease Time8msFeaturesSealed - Flux ProtectionMounting TypeThrough HoleTermination StylePC Pin		Power Relays, Over 2 Amps
Relay TypeGeneral PurposeCoil TypeLatching, Single CoilCoil Current8.7mACoil Voltage24VDCContact FormSPDT (1 Form C)Contact Rating (Current)5ASwitching Voltage400VAC - MaxTurn On Voltage (Max)18 VDCTurn Off Voltage (Min)-Operate Time8msRelease Time8msFeaturesSealed - Flux ProtectionMounting TypeThrough HoleTermination StylePC Pin	Package	-
Coil Type	Series	PE Bistable, SCHRACK
Coil Current Coil Voltage 24VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 5A Switching Voltage 400VAC - Max Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) - Operate Time 8ms Release Time 8ms Features Sealed - Flux Protection Mounting Type Through Hole Termination Style 8.7mA 8.7mB 8	Relay Type	General Purpose
Coil Voltage 24VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 5A Switching Voltage 400VAC - Max Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) - Operate Time 8ms Release Time 8ms Features Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Coil Type	Latching, Single Coil
Contact Form SPDT (1 Form C) Contact Rating (Current) 5A Switching Voltage 400VAC - Max Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) - Operate Time 8ms Release Time 8ms Release Time 8ms Features Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Coil Current	8.7mA
Contact Rating (Current) Switching Voltage 400VAC - Max Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) Operate Time 8ms Release Time 8ms Features Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Coil Voltage	24VDC
Switching Voltage 400VAC - Max Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) - Operate Time 8ms Release Time 8ms Features Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Contact Form	SPDT (1 Form C)
Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) Operate Time 8ms Release Time 8ms Features Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Contact Rating (Current)	5A
Turn Off Voltage (Min) Operate Time 8ms Release Time 8ms Features Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Switching Voltage	400VAC - Max
Operate Time 8ms Release Time 8ms Features Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Turn On Voltage (Max)	18 VDC
Release Time 8ms Features Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Turn Off Voltage (Min)	-
Features Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Operate Time	8ms
Mounting Type Through Hole Termination Style PC Pin	Release Time	8ms
Termination Style PC Pin	Features	Sealed - Flux Protection
	Mounting Type	Through Hole
Report errors?	Termination Style	PC Pin
Report circles.		Report errors?

2-1415391-1 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

2-1415391-1 Payment Methods





















2-1415391-1 Shipping Methods













If you have any question about 2-1415391-1, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com