

2-1571550-5

Juote

2-1571550-5 Information

Heisener.com	 2-1571550-5 TE Connectivity AMP Connectors Connectors, Interconnects Sockets for ICs, Transistors CONN IC DIP SOCKET 18POS GOLD - For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Qu

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



2-1571550-5 Specifications

ManufacturerTE Connectivity AMP ConnectorsCategoryConnectors, InterconnectsSockets for ICs, TransistorsPackage-Series500TypeDIP, 0.3" (7.62mm) Row SpacingNumber of Positions or Pins (Grid)18 (2 x 9)Pitch - Mating0.100" (2.54mm)Contact Finish - MatingGoldContact Finish Thickness - Mating25µin (0.63µm)Contact Material - MatingBeryllium CopperMounting TypeThrough HoleFeaturesClosed FramePitch - Post0.100" (2.54mm)Contact Finish - PostSolderContact Finish - PostSolderContact Finish - PostGoldContact Finish - PostSolderContact Finish - PostGoldContact Finish - PostGoldContact Finish - PostGoldContact Finish Thickness - PostSipin (0.63µm)Contact Material - PostSipin (0.63µm)Contact Material - PostSipin (0.63µm)Contact Material - PostBeryllium CopperHousing MaterialPolycyclohexylenedimethylene Terephthalate (PCT), Polyester			
CategoryConnectors, InterconnectsSockets for ICs, TransistorsPackage-Series500TypeDIP, 0.3" (7.62mm) Row SpacingNumber of Positions or Pins (Grid)18 (2 x 9)Pitch - Mating0.100" (2.54mm)Contact Finish - MatingGoldContact Finish Thickness - MatingSpin (0.63µm)Contact Finish Thickness - MatingSpin (0.63µm)Contact Material - MatingGoldContact Finish Thickness - MatingSolderFeaturesClosed FramePitch - Post0.100" (2.54mm)Contact Finish - PostGoldContact Finish - PostGoldContact Finish Thickness - PostSolderContact Finish Thickness - PostGoldContact Finish Thickness - PostSpin (0.63µm)Contact Material - PostGoldContact Finish Thickness - PostSpin (0.63µm)Contact Finish Thickness - PostSpin (0.63µm)Contact Material - PostSpin (0.63µm)Contact Finish Thickness - PostSpin (0.63µm)Contact Material - PostSpin (0.63µm	Manufacturer Part Number	2-1571550-5	
AckageSockets for ICs, TransistorsPackage-Series500TypeDIP, 0.3" (7.62mm) Row SpacingNumber of Positions or Pins (Grid)18 (2 x 9)Pitch - Mating0.100" (2.54mm)Contact Finish - MatingGoldContact Finish Thickness - Mating25µin (0.63µm)Contact Material - MatingBeryllium CopperMounting TypeThrough HoleFeaturesClosed FrameTerminationSolderPitch - Post0.100" (2.54mm)Contact Finish Thickness - Post6oldContact Finish - Post52µin (0.63µm)Contact Finish - PostGoldContact Finish Thickness - Post8eryllium CopperPitch - Post9bil (0.63µm)Contact Finish Thickness - Post9clyuin (0.63µm)Contact Material - Post9clyuin CopperHousing MaterialPolycyclohexylenedimethylene Terephthalate (PCT), PolyesterOperating Temperature-55°C ~ 125°C	Manufacturer	TE Connectivity AMP Connectors	
Package-Series500TypeDIP, 0.3" (7.62mm) Row SpacingNumber of Positions or Pins (Grid)18 (2 x 9)Pitch - Mating0.100" (2.54mm)Contact Finish - MatingGoldContact Finish Thickness - Mating25µin (0.63µm)Contact Material - MatingBeryllium CopperMounting TypeThrough HoleFeaturesClosed FrameTerminationSolderPitch - Post0.100" (2.54mm)Contact Finish Thickness - PostGoldContact Finish Thickness - PostSolderPitch - Post50/GContact Finish Thickness - PostGoldContact Finish Thickness - PostBeryllium CopperPitnish Thickness - PostSolderContact Finish Thickness - PostGoldContact Material - PostSeryllium CopperHousing MaterialPolycyclohexylenedimethylene Terephthalate (PCT), PolyesterOperating Temperature-55°C ~ 125°C	Category	Connectors, Interconnects	
Series500TypeDIP, 0.3" (7.62mm) Row SpacingNumber of Positions or Pins (Grid)18 (2 x 9)Pitch - Mating0.100" (2.54mm)Contact Finish - MatingGoldContact Finish - Mating25µin (0.63µm)Contact Material - MatingBeryllium CopperMounting TypeThrough HoleFeaturesClosed FramePitch - Post0.100" (2.54mm)Contact Finish - PostSolderContact Finish - PostGoldContact Finish Thickness - PostSolderContact Finish Thickness - PostSolderContact Finish Thickness - PostSoldContact Finish Thickness - PostSolyin (0.63µm)Contact Material - PostBeryllium CopperHousing MaterialPolycyclohexylenedimethylene Terephthalate (PCT), PolyesterOperating Temperature-55°C ~ 125°C		Sockets for ICs, Transistors	
TypeDIP, 0.3" (7.62mm) Row SpacingNumber of Positions or Pins (Grid)18 (2 x 9)Pitch - Mating0.100" (2.54mm)Contact Finish - MatingGoldContact Finish Thickness - Mating25µin (0.63µm)Contact Material - MatingBeryllium CopperMounting TypeThrough HoleFeaturesClosed FrameTerminationSolderPitch - Post0.100" (2.54mm)Contact Finish Thickness - PostSolderContact Finish - Post0.100" (2.54mm)Contact Finish Thickness - PostSolderContact Finish Thickness - Post25µin (0.63µm)Contact Finish Thickness - Post25µin (0.63µm)Contact Material - PostBeryllium CopperHousing MaterialPolycyclohexylenedimethylene Terephthalate (PCT), PolyesterOperating Temperature-55°C ~ 125°C	Package	-	
Number of Positions or Pins (Grid)18 (2 x 9)Pitch - Mating0.100" (2.54mm)Contact Finish - MatingGoldContact Finish Thickness - Mating25µin (0.63µm)Contact Material - MatingBeryllium CopperMounting TypeThrough HoleFeaturesClosed FrameTerminationSolderPitch - Post0.100" (2.54mm)Contact Finish Thickness - NostGoldContact Finish - Post0.100" (2.54mm)Contact Finish - PostGoldContact Finish Thickness - PostSolderContact Material - PostGoldContact Material - PostBeryllium CopperHousing MaterialPolycyclohexylenedimethylene Terephthalate (PCT), PolyesterOperating Temperature-55°C ~ 125°C	Series	500	
Pitch - Mating0.100" (2.54mm)Contact Finish - MatingGoldContact Finish Thickness - Mating25µin (0.63µm)Contact Material - MatingBeryllium CopperMounting TypeThrough HoleFeaturesClosed FrameTerminationSolderPitch - Post0.100" (2.54mm)Contact Finish - PostGoldContact Finish - PostSolderContact Finish - PostSolderContact Finish - PostGoldContact Finish Thickness - Post25µin (0.63µm)Contact Material - PostBeryllium CopperHousing MaterialPolycyclohexylenedimethylene Terephthalate (PCT), PolyesterOperating Temperature-55°C ~ 125°C	Туре	DIP, 0.3" (7.62mm) Row Spacing	
Contact Finish - MatingGoldContact Finish Thickness - Mating25µin (0.63µm)Contact Material - MatingBeryllium CopperMounting TypeThrough HoleFeaturesClosed FrameTerminationSolderPitch - Post0.100" (2.54mm)Contact Finish - PostGoldContact Finish - PostSolderContact Finish - PostSolderContact Finish - PostSolderContact Finish Thickness - PostSolderContact Material - PostBeryllium CopperHousing MaterialPolycyclohexylenedimethylene Terephthalate (PCT), PolyesterOperating Temperature-55°C ~ 125°C	Number of Positions or Pins (Grid)	18 (2 x 9)	
Contact Finish Thickness - Mating25µin (0.63µm)Contact Material - MatingBeryllium CopperMounting TypeThrough HoleFeaturesClosed FrameTerminationSolderPitch - Post0.100" (2.54mm)Contact Finish - PostGoldContact Finish Thickness - Post25µin (0.63µm)Contact Finish Thickness - PostBeryllium CopperHousing Material - PostPolycyclohexylenedimethylene Terephthalate (PCT), PolyesterOperating Temperature-55°C ~ 125°C	Pitch - Mating	0.100" (2.54mm)	
Contact Material - MatingBeryllium CopperMounting TypeThrough HoleFeaturesClosed FrameTerminationSolderPitch - Post0.100" (2.54mm)Contact Finish - PostGoldContact Finish Thickness - Post25µin (0.63µm)Contact Finish Thickness - PostBeryllium CopperHousing Material - PostPolycyclohexylenedimethylene Terephthalate (PCT), PolyesterOperating Temperature-55°C ~ 125°C	Contact Finish - Mating	Gold	
Mounting TypeThrough HoleFeaturesClosed FrameTerminationSolderPitch - Post0.100" (2.54mm)Contact Finish - PostGoldContact Finish Thickness - Post25µin (0.63µm)Contact Material - PostBeryllium CopperHousing MaterialPolycyclohexylenedimethylene Terephthalate (PCT), PolyesterOperating Temperature-55°C ~ 125°C	Contact Finish Thickness - Mating	25µin (0.63µm)	
FeaturesClosed FrameTerminationSolderPitch - Post0.100" (2.54mm)Contact Finish - PostGoldContact Finish Thickness - Post25µin (0.63µm)Contact Material - PostBeryllium CopperHousing MaterialPolycyclohexylenedimethylene Terephthalate (PCT), PolyesterOperating Temperature-55°C ~ 125°C	Contact Material - Mating	Beryllium Copper	
TerminationSolderPitch - Post0.100" (2.54mm)Contact Finish - PostGoldContact Finish Thickness - Post25µin (0.63µm)Contact Material - PostBeryllium CopperHousing MaterialPolycyclohexylenedimethylene Terephthalate (PCT), PolyesterOperating Temperature-55°C ~ 125°C	Mounting Type	Through Hole	
Pitch - Post0.100" (2.54mm)Contact Finish - PostGoldContact Finish Thickness - Post25µin (0.63µm)Contact Material - PostBeryllium CopperHousing MaterialPolycyclohexylenedimethylene Terephthalate (PCT), PolyesterOperating Temperature-55°C ~ 125°C	Features	Closed Frame	
Contact Finish - PostGoldContact Finish Thickness - Post25µin (0.63µm)Contact Material - PostBeryllium CopperHousing MaterialPolycyclohexylenedimethylene Terephthalate (PCT), PolyesterOperating Temperature-55°C ~ 125°C	Termination	Solder	
Contact Finish Thickness - Post25µin (0.63µm)Contact Material - PostBeryllium CopperHousing MaterialPolycyclohexylenedimethylene Terephthalate (PCT), PolyesterOperating Temperature-55°C ~ 125°C	Pitch - Post	0.100" (2.54mm)	
Contact Material - PostBeryllium CopperHousing MaterialPolycyclohexylenedimethylene Terephthalate (PCT), PolyesterOperating Temperature-55°C ~ 125°C	Contact Finish - Post	Gold	
Housing MaterialPolycyclohexylenedimethylene Terephthalate (PCT), PolyesterOperating Temperature-55°C ~ 125°C	Contact Finish Thickness - Post	25µin (0.63µm)	
Operating Temperature $-55^{\circ}C \sim 125^{\circ}C$	Contact Material - Post	Beryllium Copper	
	Housing Material	Polycyclohexylenedimethylene Terephthalate (PCT), Polyester	
Report errors?	Operating Temperature	-55°C ~ 125°C	
			Report errors?

2-1571550-5 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

RVICE Se

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.



If you have any question about 2-1571550-5, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com