



20 INCH-G-4V-REF Information



For Reference Only

Part Number 20 INCH-G-4V-REF
Manufacturer All Sensors Corporation
Category Sensors, Transducers

Pressure Sensors, Transducers

Description SENSOR PRESS GAUGE 20" H2O 4SIP

Package 4-SIP Module

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









20 INCH-G-4V-REF Specifications

Manufacturer Part Number 20 INCH-G-4V-REF Manufacturer All Sensors Corporation Category Sensors, Transducers Package 4-SIP Module Series - Pressure Type Vented Gauge Operating Pressure 0.72 PSI (4.98 kPa) Output Type Analog Voltage Output 0.25 V ~ 4.25 V Accuracy ±0.25% Voltage - Supply 5.5 V ~ 16 V Port Size Male - 0.19" (4.83mm) Tube Port Style Barbless Features Amplified Output, Temperature Compensated Termination Style PCB Maximum Pressure 10.84 PSI (74.75 kPa) Operating Temperature -25°C ~ 85°C Package / Case 4-SIP Module Supplier Device Package - Report errors?		
CategorySensors, TransducersPackage4-SIP ModuleSeries-Pressure TypeVented GaugeOperating Pressure0.72 PSI (4.98 kPa)Output TypeAnalog VoltageOutput0.25 V ~ 4.25 VAccuracy±0.25%Voltage - Supply5.5 V ~ 16 VPort SizeMale - 0.19" (4.83mm) TubePort StyleBarblessFeaturesAmplified Output, Temperature CompensatedTermination StylePCBMaximum Pressure10.84 PSI (74.75 kPa)Operating Temperature-25°C ~ 85°CPackage / Case4-SIP ModuleSupplier Device Package-	Manufacturer Part Number	20 INCH-G-4V-REF
Package 4-SIP Module Series - Pressure Type Vented Gauge Operating Pressure Output Type Analog Voltage Output 0.25 V ~ 4.25 V Accuracy ±0.25% Voltage - Supply 5.5 V ~ 16 V Port Size Male - 0.19" (4.83mm) Tube Port Style Barbless Features Amplified Output, Temperature Compensated Termination Style PCB Maximum Pressure 10.84 PSI (74.75 kPa) Operating Temperature - 25°C ~ 85°C Package / Case 4-SIP Module Supplier Device Package	Manufacturer	All Sensors Corporation
Package 4-SIP Module Series - Pressure Type Vented Gauge Operating Pressure 0.72 PSI (4.98 kPa) Output Type Analog Voltage Output 0.25 V ~ 4.25 V Accuracy ±0.25% Voltage - Supply 5.5 V ~ 16 V Port Size Male - 0.19" (4.83mm) Tube Port Style Barbless Features Amplified Output, Temperature Compensated Termination Style PCB Maximum Pressure 10.84 PSI (74.75 kPa) Operating Temperature -25°C ~ 85°C Package / Case 4-SIP Module Supplier Device Package	Category	Sensors, Transducers
Pressure Type Vented Gauge Operating Pressure Operating Pressure Output Type Analog Voltage Output O		Pressure Sensors, Transducers
Pressure Type Vented Gauge Operating Pressure 0.72 PSI (4.98 kPa) Output Type Analog Voltage Output 0.25 V ~ 4.25 V Accuracy ±0.25% Voltage - Supply 5.5 V ~ 16 V Port Size Male - 0.19" (4.83mm) Tube Port Style Barbless Features Amplified Output, Temperature Compensated Termination Style PCB Maximum Pressure 10.84 PSI (74.75 kPa) Operating Temperature -25°C ~ 85°C Package / Case 4-SIP Module Supplier Device Package	Package	4-SIP Module
Operating Pressure Output Type Analog Voltage Output Output Output Output Output Output Output Output Accuracy ±0.25% Voltage - Supply Fort Size Male - 0.19" (4.83mm) Tube Port Style Barbless Features Amplified Output, Temperature Compensated Termination Style PCB Maximum Pressure I 0.84 PSI (74.75 kPa) Operating Temperature -25°C ~ 85°C Package / Case 4-SIP Module Supplier Device Package	Series	-
Output Type Analog Voltage Output 0.25 V ~ 4.25 V Accuracy ±0.25% Voltage - Supply 5.5 V ~ 16 V Port Size Male - 0.19" (4.83mm) Tube Port Style Barbless Features Amplified Output, Temperature Compensated Termination Style PCB Maximum Pressure 10.84 PSI (74.75 kPa) Operating Temperature -25°C ~ 85°C Package / Case 4-SIP Module Supplier Device Package -	Pressure Type	Vented Gauge
Output $0.25 \text{ V} \sim 4.25 \text{ V}$ Accuracy $\pm 0.25\%$ Voltage - Supply $5.5 \text{ V} \sim 16 \text{ V}$ Port Size $\text{Male - 0.19'' (4.83 mm) Tube}$ Port Style Barbless Features $\text{Amplified Output, Temperature Compensated}$ Termination Style PCB Maximum Pressure $10.84 \text{ PSI (74.75 kPa)}$ Operating Temperature $-25^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Package / Case 4-SIP Module Supplier Device Package $-$	Operating Pressure	0.72 PSI (4.98 kPa)
Accuracy ±0.25% Voltage - Supply 5.5 V ~ 16 V Port Size Male - 0.19" (4.83mm) Tube Port Style Barbless Features Amplified Output, Temperature Compensated Termination Style PCB Maximum Pressure 10.84 PSI (74.75 kPa) Operating Temperature -25°C ~ 85°C Package / Case 4-SIP Module Supplier Device Package	Output Type	Analog Voltage
Voltage - Supply 5.5 V ~ 16 V Port Size Male - 0.19" (4.83mm) Tube Port Style Barbless Features Amplified Output, Temperature Compensated Termination Style PCB Maximum Pressure 10.84 PSI (74.75 kPa) Operating Temperature -25°C ~ 85°C Package / Case 4-SIP Module Supplier Device Package	Output	0.25 V ~ 4.25 V
Port Size Port Style Barbless Features Amplified Output, Temperature Compensated Termination Style PCB Maximum Pressure 10.84 PSI (74.75 kPa) Operating Temperature -25°C ~ 85°C Package / Case 4-SIP Module Supplier Device Package	Accuracy	±0.25%
Port Style Features Amplified Output, Temperature Compensated Termination Style PCB Maximum Pressure 10.84 PSI (74.75 kPa) Operating Temperature -25°C ~ 85°C Package / Case 4-SIP Module Supplier Device Package	Voltage - Supply	5.5 V ~ 16 V
Features Amplified Output, Temperature Compensated PCB Maximum Pressure 10.84 PSI (74.75 kPa) Operating Temperature -25°C ~ 85°C Package / Case 4-SIP Module Supplier Device Package	Port Size	Male - 0.19" (4.83mm) Tube
Termination Style PCB Maximum Pressure 10.84 PSI (74.75 kPa) Operating Temperature -25°C ~ 85°C Package / Case 4-SIP Module Supplier Device Package -	Port Style	Barbless
Maximum Pressure 10.84 PSI (74.75 kPa) Operating Temperature -25°C ~ 85°C Package / Case 4-SIP Module Supplier Device Package -	Features	Amplified Output, Temperature Compensated
Operating Temperature -25°C ~ 85°C Package / Case 4-SIP Module Supplier Device Package -	Termination Style	PCB
Package / Case 4-SIP Module Supplier Device Package -	Maximum Pressure	10.84 PSI (74.75 kPa)
Supplier Device Package -	Operating Temperature	-25°C ~ 85°C
	Package / Case	4-SIP Module
Report errors?	Supplier Device Package	-
		Report errors?

20 INCH-G-4V-REF Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

20 INCH-G-4V-REF Payment Methods



















20 INCH-G-4V-REF Shipping Methods













If you have any question about 20 INCH-G-4V-REF, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com