

2000.0011.11 Information

Heisener.com

Part Number 2000.0011.11

Manufacturer Schurter Inc.

Category Circuit Protection

Electrical, Specialty Fuses

Description FUSE BRD MNT 1.25A 600VAC/125VDC

Package 2-SMD, Square End Block

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









2000.0011.11 Specifications

| Manufacturer Part Number 2000.0011.11 Manufacturer Schurter Inc. Category Circuit Protection Package 2-SMD, Square End Block Series TF600 Fuse Type Board Mount Current Rating 1.25A Voltage Rating - AC 600V Voltage Rating - DC 125V Response Time Slow Applications Telecom Features - Class - Approvals cURus Operating Temperature -55°C ~ 125°C Breaking Capacity @ Rated Voltage 60A Mounting Type Surface Mount Package / Case 2-SMD, Square End Block Size / Dimension 0.398" L x 0.127" W x 0.127" H (10.10mm x 3.22mm x 3.22mm) Report errors? | | | |
|--|-----------------------------------|--|----|
| Category Circuit Protection Electrical, Specialty Fuses Package 2-SMD, Square End Block Series TF600 Fuse Type Board Mount Current Rating 1.25A Voltage Rating - AC 600V Voltage Rating - DC 125V Response Time Slow Applications Telecom Features - Class - Approvals cURus Operating Temperature -55°C ~ 125°C Breaking Capacity @ Rated Voltage 60A Mounting Type Surface Mount Package / Case 2-SMD, Square End Block Size / Dimension 0.398" L x 0.127" W x 0.127" H (10.10mm x 3.22mm x 3.22mm) | Manufacturer Part Number | 2000.0011.11 | |
| Package 2-SMD, Square End Block Series TF600 Fuse Type Board Mount Current Rating 1.25A Voltage Rating - AC 600V Voltage Rating - DC 125V Response Time Slow Applications Telecom Features - Class - Approvals cURus Operating Temperature -55°C ~ 125°C Breaking Capacity @ Rated Voltage 60A Mounting Type Surface Mount Package / Case 2-SMD, Square End Block Size / Dimension 0.398" L x 0.127" W x 0.127" H (10.10mm x 3.22mm x 3.22mm) | Manufacturer | Schurter Inc. | |
| Package 2-SMD, Square End Block Series TF600 Fuse Type Board Mount Current Rating 1.25A Voltage Rating - AC 600V Voltage Rating - DC 125V Response Time Slow Applications Telecom Features - Class - Approvals cURus Operating Temperature -55°C ~ 125°C Breaking Capacity @ Rated Voltage 60A Mounting Type Surface Mount Package / Case 2-SMD, Square End Block Size / Dimension 0.398" L x 0.127" W x 0.127" H (10.10mm x 3.22mm x 3.22mm) | Category | Circuit Protection | |
| Series TF600 Fuse Type Board Mount Current Rating 1.25A Voltage Rating - AC 600V Voltage Rating - DC 125V Response Time Slow Applications Telecom Features - Class - Approvals cURus Operating Temperature -55°C ~ 125°C Breaking Capacity @ Rated Voltage 60A Mounting Type Surface Mount Package / Case 2-SMD, Square End Block Size / Dimension 0.398" L x 0.127" W x 0.127" H (10.10mm x 3.22mm x 3.22mm) | | Electrical, Specialty Fuses | |
| Fuse Type Board Mount Current Rating 1.25A Voltage Rating - AC 600V Voltage Rating - DC 125V Response Time Slow Applications Telecom Features - Class - Approvals cURus Operating Temperature -55°C ~ 125°C Breaking Capacity @ Rated Voltage 60A Mounting Type Surface Mount Package / Case 2-SMD, Square End Block Size / Dimension 0.398" L x 0.127" W x 0.127" H (10.10mm x 3.22mm x 3.22mm) | Package | 2-SMD, Square End Block | |
| Current Rating 1.25A Voltage Rating - AC 600V Voltage Rating - DC 125V Response Time Slow Applications Telecom Features - Class - Approvals cURus Operating Temperature -55°C ~ 125°C Breaking Capacity @ Rated Voltage 60A Mounting Type Surface Mount Package / Case 2-SMD, Square End Block Size / Dimension 0.398" L x 0.127" W x 0.127" H (10.10mm x 3.22mm x 3.22mm) | Series | TF600 | |
| Voltage Rating - AC Voltage Rating - DC 125V Response Time Slow Applications Telecom Features - Class Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Surface Mount Package / Case Size / Dimension 600V 125V 125V Response Time Slow Clecom Telecom - Clecom Class - APPOVA CURUS - CURUS 60A Surface Mount Package / Case 10.398" L x 0.127" W x 0.127" H (10.10mm x 3.22mm x 3.22mm) | Fuse Type | Board Mount | |
| Voltage Rating - DC Response Time Slow Applications Telecom Features - Class - Approvals CuRus Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Surface Mount Package / Case Size / Dimension 125V 125V 125V 126V 126V 126V 127 W x 0.127" W x 0.127" H (10.10mm x 3.22mm x 3.22mm) | Current Rating | 1.25A | |
| Response Time Applications Telecom Features - Class - Approvals Operating Temperature -55°C ~ 125°C Breaking Capacity @ Rated Voltage Mounting Type Surface Mount Package / Case 2-SMD, Square End Block Size / Dimension Slow Telecom - Class - Class - CURus -55°C ~ 125°C 60A Surface Mount 9 Surface Mount 2-SMD, Square End Block 0.398" L x 0.127" W x 0.127" H (10.10mm x 3.22mm x 3.22mm) | Voltage Rating - AC | 600V | |
| Applications Features - Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Surface Mount Package / Case Size / Dimension Telecom Telecom Telecom Telecom O Surface Mount - SURUS OVENUS OVENUS OVENUS OVENUS OVENUS OVENUS OVENUS SURUS OVENUS OVENUS OVENUS SURUS OVENUS OVENUS SURUS OVENUS OVE | Voltage Rating - DC | 125V | |
| Features - Class - Cla | Response Time | Slow | |
| Class - CURus Operating Temperature -55°C ~ 125°C Breaking Capacity @ Rated Voltage 60A Mounting Type Surface Mount Package / Case 2-SMD, Square End Block Size / Dimension 0.398" L x 0.127" W x 0.127" H (10.10mm x 3.22mm x 3.22mm) | Applications | Telecom | |
| Approvals CURus Operating Temperature -55°C ~ 125°C Breaking Capacity @ Rated Voltage 60A Mounting Type Surface Mount Package / Case 2-SMD, Square End Block Size / Dimension 0.398" L x 0.127" W x 0.127" H (10.10mm x 3.22mm x 3.22mm) | Features | - | |
| Operating Temperature -55°C ~ 125°C Breaking Capacity @ Rated Voltage 60A Mounting Type Surface Mount Package / Case 2-SMD, Square End Block Size / Dimension 0.398" L x 0.127" W x 0.127" H (10.10mm x 3.22mm x 3.22mm) | Class | - | |
| Breaking Capacity @ Rated Voltage 60A Mounting Type Surface Mount Package / Case 2-SMD, Square End Block Size / Dimension 0.398" L x 0.127" W x 0.127" H (10.10mm x 3.22mm x 3.22mm) | Approvals | cURus | |
| Mounting Type Surface Mount Package / Case 2-SMD, Square End Block Size / Dimension 0.398" L x 0.127" W x 0.127" H (10.10mm x 3.22mm x 3.22mm) | Operating Temperature | -55°C ~ 125°C | |
| Package / Case 2-SMD, Square End Block Size / Dimension 0.398" L x 0.127" W x 0.127" H (10.10mm x 3.22mm x 3.22mm) | Breaking Capacity @ Rated Voltage | 60A | |
| Size / Dimension 0.398" L x 0.127" W x 0.127" H (10.10mm x 3.22mm x 3.22mm) | Mounting Type | Surface Mount | |
| | Package / Case | 2-SMD, Square End Block | |
| Report errors? | Size / Dimension | 0.398" L x 0.127" W x 0.127" H (10.10mm x 3.22mm x 3.22mm) | |
| | | Report error | s? |

2000.0011.11 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

2000.0011.11 Payment Methods



















2000.0011.11 Shipping Methods













If you have any question about 2000.0011.11, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com