

2009-SHO

2009-SHO Information

	Part Number Manufacturer Category	LEDdynamics Inc. Power Supplies - External/Internal (Off-Board)	
www.hclence.com	Description Package	LED Drivers LED DRIVER CC BOOST 8V 500MA - For the pricing/inventory/lead time, please contact	
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



2009-SHO Specifications

Manufacturer LEDdynamics Inc. Power Supplies - External/Internal (Off-Board) IED Drivers Package - Series MicroPuck 2009 Type Constant Current Topology Boost Number of Outputs 1 Voltage - Input (Max) 3V Voltage - Output SolomA Voltage - Output (Max) 500mA Voltage - Solation - Voltage - Solation - Voltage - Output (Max) SV Voltage - Solation - Power (Watts) - Voltage - Solation - Power (Watts) - Potenter				
Actegory Power Supplies - External/Internal (Off-Board) LED Drivers Package - Series MicroPuck 2009 Type Constant Current Topology Boost Number of Outputs 1 Voltage - Input (Min) 0.8V Voltage - Input (Max) 3V Voltage - Output 8V Current - Output (Max) 500mA Voltage - Isolation - Dimming - Features - Ratings - Operating Temperature 40°C ~ 85°C Efficiency 80% Termination Style Wire Leads	Manufacturer Part Number	2009-SHO		
LED DriversPackage-SeriesMicroPuck 2009TypeConstant CurrentTopologyBoostNumber of Outputs1Voltage - Input (Min)0.8VVoltage - Input (Max)3VVoltage - Output8VCurrent - Output (Max)500mAPower (Watts)1.5WVoltage - Isolation-Dimming-Features-Ratings-Operating Temperature40°C ~ 85°CEfficiencyS0%Size / Dimension50% X 0.26° H (11.5mm x 7.6mm x 6.6mm)	Manufacturer	LEDdynamics Inc.		
Package.SeriesMicroPuck 2009TypeConstant CurrentTopologyBoostNumber of Outputs1Voltage - Input (Min)0.8VVoltage - Input (Max)3VVoltage - OutputSVVoltage - OutputSOmACurrent - Output (Max).Voltage - Isolation.Power (Wats).Voltage - Isolation.Potter Series.Potter Series.Pot	Category	Power Supplies - External/Internal (Off-Board)		
SeriesMicroPuck 2009TypeConstant CurrentTopologyBoostNumber of Outputs1Voltage - Input (Min)0.8VVoltage - Input (Max)3VVoltage - Output8VCurrent - Output (Max)500mAPower (Watts)1.5WVoltage - Isolation-Dimming-Features-Ratings-Operating Temperature40°C ~ 85°CEfficiencyBo%Size / Dimension0.45" L x 0.30" W x 0.26" H (11.5mm x 7.6mm x 6.6mm)		LED Drivers		
TypeConstant CurrentTopologyBoostNumber of Outputs1Voltage - Input (Min)0.8VVoltage - Input (Max)3VVoltage - Output8VCurrent - Output (Max)500mAPower (Watts)1.5WVoltage - Isolation-Dimming-Features-Ratings-Operating Temperature40°C ~ 85°CEfficiency80%Size / DimensionSize / DimensionSize / Dimension0.45° L x 0.30° W x 0.26° H (11.5mm x 7.6mm x 6.6mm)	Package	-		
Answission Boost Topology Boost Number of Outputs 1 Voltage - Input (Min) 0.8V Voltage - Input (Max) 3V Voltage - Output 8V Current - Output (Max) 500mA Power (Watts) 1.5W Voltage - Isolation - Dimming - Features - Ratings - Operating Temperature -40°C ~ 85°C Efficiency 80% Termination Style Wire Leads Size / Dimension 0.45" L x 0.30" W x 0.26" H (11.5mm x 7.6mm x 6.6mm)	Series	MicroPuck 2009		
Number of Outputs1Voltage - Input (Min)0.8VVoltage - Input (Max)3VVoltage - Output8VCurrent - Output (Max)500mAPower (Watts)1.5WVoltage - Isolation-Dimming-Features-Ratings-Operating Temperature40°C ~ 85°CEfficiency80%Size / Dimension0.45" L x 0.30" W x 0.26" H (11.5mm x 7.6mm x 6.6mm)	Туре	Constant Current		
Voltage - Input (Min) 0.8V Voltage - Input (Max) 3V Voltage - Output 8V Current - Output (Max) 500mA Current - Output (Max) 500mA Power (Wats) 1.5W Voltage - Isolation - Dimming - Features - Poperating Temperature - Operating Temperature 40°C ~ 85°C Efficiency 80% Termination Style Wire Leads Size / Dimension 0.45" L x 0.30" W x 0.26" H (11.5mm x 7.6mm x 6.6mm)	Topology	Boost		
Voltage - Input (Max)3VVoltage - Output8VCurrent - Output (Max)500mAPower (Watts)1.5WVoltage - Isolation-Dimming-Features-Ratings-Operating Temperature-40°C ~ 85°CEfficiency80%Termination StyleWire LeadsSize / Dimension0.45" L x 0.30" W x 0.26" H (11.5mm x 7.6mm x 6.6mm)	Number of Outputs	1		
Voltage - Output 8V Current - Output (Max) 500mA Power (Watts) 1.5W Voltage - Isolation - Dimming - Features - Ratings - Operating Temperature -40°C ~ 85°C Efficiency 80% Termination Style Wire Leads Size / Dimension 0.45" L x 0.30" W x 0.26" H (11.5mm x 7.6mm)	Voltage - Input (Min)	0.8V		
Current - Output (Max)500mAPower (Watts)1.5WVoltage - Isolation-Dimming-Features-Ratings-Operating Temperature-40°C ~ 85°CEfficiency80%Termination StyleWire LeadsSize / Dimension0.45" L x 0.30" W x 0.26" H (11.5mm x 7.6mm x 6.6mm)	Voltage - Input (Max)	3V		
Power (Watts) 1.5W Voltage - Isolation - Dimming - Features - Ratings - Operating Temperature -40°C ~ 85°C Efficiency 80% Termination Style Wire Leads Size / Dimension 0.45" L x 0.30" W x 0.26" H (11.5mm x 7.6mm x 6.6mm)	Voltage - Output	8V		
Voltage - Isolation-Dimming-Features-Features-Ratings-Operating Temperature-40°C ~ 85°CEfficiency80%Termination StyleWire LeadsSize / Dimension0.45" L x 0.30" W x 0.26" H (11.5mm x 7.6mm x 6.6mm)	Current - Output (Max)	500mA		
Dimming-Features-Ratings-Operating Temperature-40°C ~ 85°CEfficiency80%Termination StyleWire LeadsSize / Dimension0.45" L x 0.30" W x 0.26" H (11.5mm x 7.6mm x 6.6mm)	Power (Watts)	1.5W		
Features-Ratings-Operating Temperature-40°C ~ 85°CEfficiency80%Termination StyleWire LeadsSize / Dimension0.45" L x 0.30" W x 0.26" H (11.5mm x 7.6mm x 6.6mm)	Voltage - Isolation	-		
Ratings-Operating Temperature-40°C ~ 85°CEfficiency80%Termination StyleWire LeadsSize / Dimension0.45" L x 0.30" W x 0.26" H (11.5mm x 7.6mm x 6.6mm)	Dimming	-		
Operating Temperature-40°C ~ 85°CEfficiency80%Termination StyleWire LeadsSize / Dimension0.45" L x 0.30" W x 0.26" H (11.5mm x 7.6mm x 6.6mm)	Features	-		
Efficiency80%Termination StyleWire LeadsSize / Dimension0.45" L x 0.30" W x 0.26" H (11.5mm x 7.6mm x 6.6mm)	Ratings	-		
Termination StyleWire LeadsSize / Dimension0.45" L x 0.30" W x 0.26" H (11.5mm x 7.6mm x 6.6mm)	Operating Temperature	-40°C ~ 85°C		
Size / Dimension 0.45" L x 0.30" W x 0.26" H (11.5mm x 7.6mm x 6.6mm)	Efficiency	80%		
	Termination Style	Wire Leads		
Report errors?	Size / Dimension	0.45" L x 0.30" W x 0.26" H (11.5mm x 7.6mm x 6.6mm)		
		Report errors?		

2009-SHO Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.



If you have any question about 2009-SHO, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com