

# 200PK220MEFCGC16X31.5

### 200PK220MEFCGC16X31.5 Information



For Reference Only

Part Number 200PK220MEFCGC16X31.5

Manufacturer Rubycon
Category Capacitors

**Aluminum Electrolytic Capacitors** 

**Description** CAP ALUM 220UF 20% 200V RADIAL

Package Radial, Car

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## 200PK220MEFCGC16X31.5 Specifications

Manufacturer Part Number         200PK220MEFCGC16X31.5           Manufacturer         Rubycon           Category         Capacitors           Package         Radial, Can           Series         PK           Capacitance         220µF           Tolerance         ±20%           Voltage - Rated         200V           ESR (Equivalent Series Resistance)         -           Lifetime @ Temp.         2000 Hrs @ 85°C           Operating Temperature         -40°C ~ 85°C           Polarization         -           Applications         General Purpose           Ripple Current - Low Frequency         540mA @ 120Hz           Ripple Current - High Frequency         648mA @ 10kHz           Impedance         -           Lead Spacing         0.295" (7.50mm)           Size / Dimension         0.630" Dia (16.00mm)           Height - Seated (Max)         1.319" (33.50mm)           Surface Mount Land Size         -           Mounting Type         Through Hole           Package / Case         Radial, Can		
Category         Capacitors           Package         Radial, Can           Series         PK           Capacitance         220µF           Tolerance         ±20%           Voltage - Rated         200V           ESR (Equivalent Series Resistance)         -           Lifetime @ Temp.         2000 Hrs @ 85°C           Operating Temperature         -40°C ~ 85°C           Polarization         -           Applications         General Purpose           Ripple Current - Low Frequency         540mA @ 120Hz           Ripple Current - High Frequency         648mA @ 10kHz           Impedance         -           Lead Spacing         0.295" (7.50mm)           Size / Dimension         0.630" Dia (16.00mm)           Height - Seated (Max)         1.319" (33.50mm)           Surface Mount Land Size         -           Mounting Type         Through Hole	Manufacturer Part Number	200PK220MEFCGC16X31.5
Package         Radial, Can           Series         PK           Capacitance         220μF           Tolerance         ±20%           Voltage - Rated         200V           ESR (Equivalent Series Resistance)         -           Lifetime @ Temp.         2000 Hrs @ 85°C           Operating Temperature         -40°C ~ 85°C           Polarization         -           Applications         General Purpose           Ripple Current - Low Frequency         540mA @ 120Hz           Ripple Current - High Frequency         648mA @ 10kHz           Impedance         -           Lead Spacing         0.295" (7.50mm)           Size / Dimension         0.630" Dia (16.00mm)           Height - Seated (Max)         1.319" (33.50mm)           Surface Mount Land Size         -           Mounting Type         Through Hole	Manufacturer	Rubycon
Package         Radial, Can           Series         PK           Capacitance         220µF           Tolerance         ±20%           Voltage - Rated         200V           ESR (Equivalent Series Resistance)         -           Lifetime @ Temp.         2000 Hrs @ 85°C           Operating Temperature         -40°C ~ 85°C           Polarization         -           Applications         General Purpose           Ripple Current - Low Frequency         540mA @ 120Hz           Ripple Current - High Frequency         648mA @ 10kHz           Impedance         -           Lead Spacing         0.295" (7.50mm)           Size / Dimension         0.630" Dia (16.00mm)           Height - Seated (Max)         1.319" (33.50mm)           Surface Mount Land Size         -           Mounting Type         Through Hole	Category	Capacitors
Series         PK           Capacitance         220µF           Tolerance         ±20%           Voltage - Rated         200V           ESR (Equivalent Series Resistance)         -           Lifetime @ Temp.         2000 Hrs @ 85°C           Operating Temperature         -40°C ~ 85°C           Polarization         -           Applications         General Purpose           Ripple Current - Low Frequency         540mA @ 120Hz           Ripple Current - High Frequency         648mA @ 10kHz           Impedance         -           Lead Spacing         0.295" (7.50mm)           Size / Dimension         0.630" Dia (16.00mm)           Height - Seated (Max)         1.319" (33.50mm)           Surface Mount Land Size         -           Mounting Type         Through Hole		Aluminum Electrolytic Capacitors
Capacitance         220μF           Tolerance         ±20%           Voltage - Rated         200V           ESR (Equivalent Series Resistance)         -           Lifetime @ Temp.         2000 Hrs @ 85°C           Operating Temperature         -40°C ~ 85°C           Polarization         -           Applications         General Purpose           Ripple Current - Low Frequency         540mA @ 120Hz           Ripple Current - High Frequency         648mA @ 10kHz           Impedance         -           Lead Spacing         0.295" (7.50mm)           Size / Dimension         0.630" Dia (16.00mm)           Height - Seated (Max)         1.319" (33.50mm)           Surface Mount Land Size         -           Mounting Type         Through Hole	Package	Radial, Can
Tolerance ±20%  Voltage - Rated 200V  ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 85°C  Operating Temperature -40°C ~ 85°C  Polarization - Applications General Purpose Ripple Current - Low Frequency 540mA @ 120Hz  Ripple Current - High Frequency 648mA @ 10kHz  Impedance - Lead Spacing 0.295" (7.50mm)  Size / Dimension 0.630" Dia (16.00mm)  Height - Seated (Max) 1.319" (33.50mm)  Surface Mount Land Size -  Mounting Type Through Hole	Series	PK
Voltage - Rated200VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarization-ApplicationsGeneral PurposeRipple Current - Low Frequency540mA @ 120HzRipple Current - High Frequency648mA @ 10kHzImpedance-Lead Spacing0.295" (7.50mm)Size / Dimension0.630" Dia (16.00mm)Height - Seated (Max)1.319" (33.50mm)Surface Mount Land Size-Mounting TypeThrough Hole	Capacitance	220μF
ESR (Equivalent Series Resistance)  Lifetime @ Temp.  2000 Hrs @ 85°C  Operating Temperature  -40°C ~ 85°C  Polarization  - Applications  General Purpose  Ripple Current - Low Frequency  540mA @ 120Hz  Ripple Current - High Frequency  648mA @ 10kHz  Impedance  - Lead Spacing  0.295" (7.50mm)  Size / Dimension  Height - Seated (Max)  1.319" (33.50mm)  Surface Mount Land Size  - Mounting Type  Through Hole	Tolerance	±20%
Lifetime @ Temp.  Operating Temperature  -40°C ~ 85°C  Polarization  - Applications  General Purpose  Ripple Current - Low Frequency  540mA @ 120Hz  Ripple Current - High Frequency  648mA @ 10kHz  Impedance  - Lead Spacing  0.295" (7.50mm)  Size / Dimension  0.630" Dia (16.00mm)  Height - Seated (Max)  1.319" (33.50mm)  Surface Mount Land Size  - Mounting Type  Through Hole	Voltage - Rated	200V
Operating Temperature -40°C ~ 85°C  Polarization - Applications General Purpose Ripple Current - Low Frequency S40mA @ 120Hz Ripple Current - High Frequency 648mA @ 10kHz Impedance - Lead Spacing 0.295" (7.50mm) Size / Dimension 0.630" Dia (16.00mm) Height - Seated (Max) 1.319" (33.50mm) Surface Mount Land Size Mounting Type Through Hole	ESR (Equivalent Series Resistance)	-
Polarization - General Purpose Ripple Current - Low Frequency 540mA @ 120Hz Ripple Current - High Frequency 648mA @ 10kHz Impedance - Lead Spacing 0.295" (7.50mm) Size / Dimension 0.630" Dia (16.00mm) Height - Seated (Max) 1.319" (33.50mm) Surface Mount Land Size - Through Hole	Lifetime @ Temp.	2000 Hrs @ 85°C
Applications  Ripple Current - Low Frequency  S40mA @ 120Hz  Ripple Current - High Frequency  648mA @ 10kHz  Impedance  -  Lead Spacing  0.295" (7.50mm)  Size / Dimension  0.630" Dia (16.00mm)  Height - Seated (Max)  1.319" (33.50mm)  Surface Mount Land Size  Mounting Type  Through Hole	Operating Temperature	-40°C ~ 85°C
Ripple Current - Low Frequency  Ripple Current - High Frequency  648mA @ 10kHz  Impedance  Lead Spacing  0.295" (7.50mm)  Size / Dimension  0.630" Dia (16.00mm)  Height - Seated (Max)  1.319" (33.50mm)  Surface Mount Land Size  Mounting Type  Through Hole	Polarization	-
Ripple Current - High Frequency Impedance	Applications	General Purpose
Impedance         -           Lead Spacing         0.295" (7.50mm)           Size / Dimension         0.630" Dia (16.00mm)           Height - Seated (Max)         1.319" (33.50mm)           Surface Mount Land Size         -           Mounting Type         Through Hole	Ripple Current - Low Frequency	540mA @ 120Hz
Lead Spacing0.295" (7.50mm)Size / Dimension0.630" Dia (16.00mm)Height - Seated (Max)1.319" (33.50mm)Surface Mount Land Size-Mounting TypeThrough Hole	Ripple Current - High Frequency	648mA @ 10kHz
Size / Dimension0.630" Dia (16.00mm)Height - Seated (Max)1.319" (33.50mm)Surface Mount Land Size-Mounting TypeThrough Hole	Impedance	-
Height - Seated (Max)  Surface Mount Land Size  Mounting Type  1.319" (33.50mm)  - Through Hole	Lead Spacing	0.295" (7.50mm)
Surface Mount Land Size - Mounting Type Through Hole	Size / Dimension	0.630" Dia (16.00mm)
Mounting Type Through Hole	Height - Seated (Max)	1.319" (33.50mm)
	Surface Mount Land Size	-
Package / Case Radial, Can	Mounting Type	Through Hole
	Package / Case	Radial, Can
Report errors?		Report errors?

#### 200PK220MEFCGC16X31.5 Guarantees



#### **Ouality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### 200PK220MEFCGC16X31.5 Payment Methods



















## 200PK220MEFCGC16X31.5 Shipping Methods













If you have any question about 200PK220MEFCGC16X31.5, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com