



2016L260/24MR Information

www.neisener.com

For Reference Only

Part Number 2016L260/24MR

Manufacturer Littelfuse Inc.

Category Circuit Protection
PTC Resettable Fuses

Description PTC 24V POLYFUSE SURF MOUNT 2016

Package 2016 (5041 Metric), Concave

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









2016L260/24MR Specifications

Category Circuit Protection PTC Resettable Fuses Package 2016 (5041 Metric), Concave Series POLY-FUSE?, 2016L Type Polymeric Voltage - Max 24V Current - Max 40A Current - Hold (lh) (Max) 2.6A Current - Trip (lt) 5A Time to Trip 5s Resistance - Initial (Ri) (Min) 25 mOhms Resistance - Post Trip (R1) (Max) 75 mOhms Resistance - 25°C (Typ) - Operating Temperature -40°C ~ 85°C Ratings - Mounting Type Surface Mount Package / Case 2016 (5041 Metric), Concave Size / Dimension 0.200" L x 0.160" W (5.08mm x 4.07mm) Height - Seated (Max) - Thickness (Max) 0.063" (1.60mm) Lead Spacing -		
Category Circuit Protection PTC Resettable Fuses Package 2016 (5041 Metric), Concave Series POLY-FUSE?, 2016L Type Polymeric Voltage - Max 24V Current - Max 40A Current - Hold (lh) (Max) 2.6A Current - Trip (lt) 5A Time to Trip 5s Resistance - Initial (Ri) (Min) 25 mOhms Resistance - Post Trip (R1) (Max) 75 mOhms Resistance - 25°C (Typ) - Operating Temperature -40°C ~ 85°C Ratings - Mounting Type Surface Mount Package / Case 2016 (5041 Metric), Concave Size / Dimension 0.200" L x 0.160" W (5.08mm x 4.07mm) Height - Seated (Max) - Thickness (Max) 0.063" (1.60mm) Lead Spacing -	Manufacturer Part Number	2016L260/24MR
Package 2016 (5041 Metric), Concave Series POLY-FUSE?, 2016L Type Polymeric Voltage - Max 24V Current - Max 40A Current - Hold (Ih) (Max) 2.6A Current - Trip (It) 5A Time to Trip 5s Resistance - Initial (Ri) (Min) 25 mOhms Resistance - Post Trip (R1) (Max) 75 mOhms Resistance - 25°C (Typ) - Operating Temperature -40°C ~ 85°C Ratings - Mounting Type Surface Mount Package / Case 2016 (5041 Metric), Concave Size / Dimension 0.200" L x 0.160" W (5.08mm x 4.07mm) Height - Seated (Max) - Thickness (Max) 0.063" (1.60mm) Lead Spacing -	Manufacturer	Littelfuse Inc.
Package 2016 (5041 Metric), Concave Series POLY-FUSE?, 2016L Type Polymeric Voltage - Max 24V Current - Max 40A Current - Hold (Ih) (Max) 2.6A Current - Trip (It) 5A Time to Trip 5s Resistance - Initial (Ri) (Min) 25 mOhms Resistance - Post Trip (R1) (Max) 75 mOhms Resistance - 25°C (Typ) - Operating Temperature -40°C ~ 85°C Ratings - Mounting Type Surface Mount Package / Case 2016 (5041 Metric), Concave Size / Dimension 0.200" L x 0.160" W (5.08mm x 4.07mm) Height - Seated (Max) - Thickness (Max) 0.063" (1.60mm) Lead Spacing -	Category	Circuit Protection
Series POLY-FUSE?, 2016L Type Polymeric Voltage - Max 24V Current - Max 40A Current - Hold (Ih) (Max) 2.6A Current - Trip (It) 5A Time to Trip 5s Resistance - Initial (Ri) (Min) 25 mOhms Resistance - Post Trip (R1) (Max) 75 mOhms Resistance - 25°C (Typ) - Operating Temperature -40°C ~ 85°C Ratings - Mounting Type Surface Mount Package / Case 2016 (5041 Metric), Concave Size / Dimension 0.200" L x 0.160" W (5.08mm x 4.07mm) Height - Seated (Max) - Thickness (Max) 0.063" (1.60mm) Lead Spacing -		PTC Resettable Fuses
Type Polymeric Voltage - Max 24V Current - Max 40A Current - Hold (Ih) (Max) 2.6A Current - Trip (It) 5A Time to Trip 5s Resistance - Initial (Ri) (Min) 25 mOhms Resistance - Post Trip (R1) (Max) 75 mOhms Resistance - 25°C (Typ) - Operating Temperature -40°C ~ 85°C Ratings - Mounting Type Surface Mount Package / Case 2016 (5041 Metric), Concave Size / Dimension 0.200" L x 0.160" W (5.08mm x 4.07mm) Height - Seated (Max) - Thickness (Max) 0.063" (1.60mm) Lead Spacing -	Package	2016 (5041 Metric), Concave
Voltage - Max 24V Current - Max 40A Current - Hold (Ih) (Max) 2.6A Current - Trip (It) 5A Time to Trip 5s Resistance - Initial (Ri) (Min) 25 mOhms Resistance - Post Trip (R1) (Max) 75 mOhms Resistance - 25°C (Typ) - Operating Temperature -40°C ~ 85°C Ratings - Mounting Type Surface Mount Package / Case 2016 (5041 Metric), Concave Size / Dimension 0.200" L x 0.160" W (5.08mm x 4.07mm) Height - Seated (Max) - Thickness (Max) 0.063" (1.60mm) Lead Spacing -	Series	POLY-FUSE?, 2016L
Current - Max 40A Current - Hold (lh) (Max) 2.6A Current - Trip (It) 5A Time to Trip 5s Resistance - Initial (Ri) (Min) 25 mOhms Resistance - Post Trip (R1) (Max) 75 mOhms Resistance - 25°C (Typ) - Operating Temperature -40°C ~ 85°C Ratings - Mounting Type Surface Mount Package / Case 2016 (5041 Metric), Concave Size / Dimension 0.200" L x 0.160" W (5.08mm x 4.07mm) Height - Seated (Max) - Thickness (Max) 0.063" (1.60mm) Lead Spacing -	Туре	Polymeric
Current - Hold (Ih) (Max) 2.6A Current - Trip (It) 5A Time to Trip 5s Resistance - Initial (Ri) (Min) 25 mOhms Resistance - Post Trip (R1) (Max) 75 mOhms Resistance - 25°C (Typ) - Operating Temperature -40°C ~ 85°C Ratings - Mounting Type Surface Mount Package / Case 2016 (5041 Metric), Concave Size / Dimension 0.200" L x 0.160" W (5.08mm x 4.07mm) Height - Seated (Max) - Thickness (Max) 0.063" (1.60mm) Lead Spacing -	Voltage - Max	24V
Current - Trip (It) 5A Time to Trip 5s Resistance - Initial (Ri) (Min) 25 mOhms Resistance - Post Trip (R1) (Max) 75 mOhms Resistance - 25°C (Typ) - Operating Temperature -40°C ~ 85°C Ratings - Mounting Type Surface Mount Package / Case 2016 (5041 Metric), Concave Size / Dimension 0.200" L x 0.160" W (5.08mm x 4.07mm) Height - Seated (Max) - Thickness (Max) 0.063" (1.60mm) Lead Spacing -	Current - Max	40A
Time to Trip 5s Resistance - Initial (Ri) (Min) 25 mOhms Resistance - Post Trip (R1) (Max) 75 mOhms Resistance - 25°C (Typ) - Operating Temperature -40°C ~ 85°C Ratings - Mounting Type Surface Mount Package / Case 2016 (5041 Metric), Concave Size / Dimension 0.200" L x 0.160" W (5.08mm x 4.07mm) Height - Seated (Max) - Thickness (Max) 0.063" (1.60mm) Lead Spacing -	Current - Hold (Ih) (Max)	2.6A
Resistance - Initial (Ri) (Min) 25 mOhms Resistance - Post Trip (R1) (Max) 75 mOhms Resistance - 25°C (Typ) - Operating Temperature -40°C ~ 85°C Ratings - Mounting Type Surface Mount Package / Case 2016 (5041 Metric), Concave Size / Dimension 0.200" L x 0.160" W (5.08mm x 4.07mm) Height - Seated (Max) - Thickness (Max) 0.063" (1.60mm) Lead Spacing -	Current - Trip (It)	5A
Resistance - Post Trip (R1) (Max) Resistance - 25°C (Typ) Operating Temperature -40°C ~ 85°C Ratings - Mounting Type Surface Mount Package / Case 2016 (5041 Metric), Concave Size / Dimension Height - Seated (Max) Thickness (Max) 0.063" (1.60mm) Lead Spacing -	Time to Trip	5s
Resistance - 25°C (Typ) Operating Temperature -40°C ~ 85°C Ratings - Mounting Type Surface Mount Package / Case 2016 (5041 Metric), Concave Size / Dimension 0.200" L x 0.160" W (5.08mm x 4.07mm) Height - Seated (Max) - Thickness (Max) 0.063" (1.60mm) Lead Spacing -	Resistance - Initial (Ri) (Min)	25 mOhms
Operating Temperature -40°C ~ 85°C Ratings - Mounting Type Surface Mount Package / Case 2016 (5041 Metric), Concave Size / Dimension 0.200" L x 0.160" W (5.08mm x 4.07mm) Height - Seated (Max) - Thickness (Max) 0.063" (1.60mm) Lead Spacing -	Resistance - Post Trip (R1) (Max)	75 mOhms
Ratings - Surface Mount Package / Case 2016 (5041 Metric), Concave Size / Dimension 0.200" L x 0.160" W (5.08mm x 4.07mm) Height - Seated (Max) - Thickness (Max) 0.063" (1.60mm) Lead Spacing -	Resistance - 25°C (Typ)	-
Mounting Type Surface Mount Package / Case 2016 (5041 Metric), Concave Size / Dimension 0.200" L x 0.160" W (5.08mm x 4.07mm) Height - Seated (Max) - Thickness (Max) 0.063" (1.60mm) Lead Spacing -	Operating Temperature	-40°C ~ 85°C
Package / Case 2016 (5041 Metric), Concave Size / Dimension 0.200" L x 0.160" W (5.08mm x 4.07mm) Height - Seated (Max) - Thickness (Max) 0.063" (1.60mm) Lead Spacing -	Ratings	-
Size / Dimension 0.200" L x 0.160" W (5.08mm x 4.07mm) Height - Seated (Max) - Thickness (Max) 0.063" (1.60mm) Lead Spacing -	Mounting Type	Surface Mount
Height - Seated (Max) Thickness (Max) Lead Spacing - 0.063" (1.60mm) -	Package / Case	2016 (5041 Metric), Concave
Thickness (Max) 0.063" (1.60mm) Lead Spacing -	Size / Dimension	0.200" L x 0.160" W (5.08mm x 4.07mm)
Lead Spacing -	Height - Seated (Max)	-
	Thickness (Max)	0.063" (1.60mm)
Report errors?	Lead Spacing	-
Report chois:		Report errors?

2016L260/24MR Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

2016L260/24MR Payment Methods



















2016L260/24MR Shipping Methods













If you have any question about 2016L260/24MR, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com