



#### 202S43W682KV4E Information

For Reference Only

Part Number 202S43W682KV4E

Manufacturer Johanson Dielectrics Inc.

**Category** Capacitors

Ceramic Capacitors

**Description** CAP CER 6800PF 2KV X7R 1812

Package 1812 (4532 Metric)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

### **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## 202S43W682KV4E Specifications

Manufacturer Part Number         202843W682KV4E           Manufacturer         Johanson Dielectrics Inc.           Category         Capacitors           Package         1812 (4532 Metric)           Series         -           Capacitance         6800pF           Tolerance         ±10%           Voltage - Rated         2000V (2kV)           Temperature Coefficient         X7R           Operating Temperature         -55°C ~ 125°C           Features         High Voltage           Ratings         -           Applications         General Purpose           Failure Rate         -           Mounting Type         Surface Mount, MLCC           Package / Case         1812 (4532 Metric)           Size / Dimension         0.180" L x 0.125" W (4.57mm x 3.18mm)           Height - Seated (Max)         -           Thickness (Max)         0.110" (2.80mm)           Lead Spacing         -           Lead Style         -		
Category         Capacitors           Package         1812 (4532 Metric)           Series         -           Capacitance         6800pF           Tolerance         ±10%           Voltage - Rated         2000V (2kV)           Temperature Coefficient         X7R           Operating Temperature         -55°C ~ 125°C           Features         High Voltage           Ratings         -           Applications         General Purpose           Failure Rate         -           Mounting Type         Surface Mount, MLCC           Package / Case         1812 (4532 Metric)           Size / Dimension         0.180" L x 0.125" W (4.57mm x 3.18mm)           Height - Seated (Max)         -           Thickness (Max)         0.110" (2.80mm)           Lead Spacing         -           Lead Style         -	Manufacturer Part Number	202S43W682KV4E
Package         1812 (4532 Metric)           Series         -           Capacitance         6800pF           Tolerance         ±10%           Voltage - Rated         2000V (2kV)           Temperature Coefficient         X7R           Operating Temperature         -55°C ~ 125°C           Features         High Voltage           Ratings         -           Applications         General Purpose           Failure Rate         -           Mounting Type         Surface Mount, MLCC           Package / Case         1812 (4532 Metric)           Size / Dimension         0.180" L x 0.125" W (4.57mm x 3.18mm)           Height - Seated (Max)         -           Thickness (Max)         0.110" (2.80mm)           Lead Spacing         -           Lead Style         -	Manufacturer	Johanson Dielectrics Inc.
Package         1812 (4532 Metric)           Series         -           Capacitance         6800pF           Tolerance         ±10%           Voltage - Rated         2000V (2kV)           Temperature Coefficient         X7R           Operating Temperature         -55°C ~ 125°C           Features         High Voltage           Ratings         -           Applications         General Purpose           Failure Rate         -           Mounting Type         Surface Mount, MLCC           Package / Case         1812 (4532 Metric)           Size / Dimension         0.180" L x 0.125" W (4.57mm x 3.18mm)           Height - Seated (Max)         -           Thickness (Max)         0.110" (2.80mm)           Lead Spacing         -           Lead Style         -	Category	Capacitors
Series         -           Capacitance         6800pF           Tolerance         ±10%           Voltage - Rated         2000V (2kV)           Temperature Coefficient         X7R           Operating Temperature         -55°C ~ 125°C           Features         High Voltage           Ratings         -           Applications         General Purpose           Failure Rate         -           Mounting Type         Surface Mount, MLCC           Package / Case         1812 (4532 Metric)           Size / Dimension         0.180" L x 0.125" W (4.57mm x 3.18mm)           Height - Seated (Max)         -           Thickness (Max)         0.110" (2.80mm)           Lead Spacing         -           Lead Style         -		Ceramic Capacitors
Capacitance         6800pF           Tolerance         ±10%           Voltage - Rated         2000V (2kV)           Temperature Coefficient         X7R           Operating Temperature         -55°C ~ 125°C           Features         High Voltage           Ratings         -           Applications         General Purpose           Failure Rate         -           Mounting Type         Surface Mount, MLCC           Package / Case         1812 (4532 Metric)           Size / Dimension         0.180" L x 0.125" W (4.57mm x 3.18mm)           Height - Seated (Max)         -           Thickness (Max)         0.110" (2.80mm)           Lead Spacing         -           Lead Style         -	Package	1812 (4532 Metric)
Tolerance ±10%  Voltage - Rated 2000V (2kV)  Temperature Coefficient X7R  Operating Temperature -55°C ~ 125°C  Features High Voltage  Ratings -  Applications General Purpose  Failure Rate -  Mounting Type Surface Mount, MLCC  Package / Case 1812 (4532 Metric)  Size / Dimension 0.180" L x 0.125" W (4.57mm x 3.18mm)  Height - Seated (Max) -  Thickness (Max) 0.110" (2.80mm)  Lead Spacing -  Lead Style -	Series	-
Voltage - Rated2000V (2kV)Temperature CoefficientX7ROperating Temperature-55°C ~ 125°CFeaturesHigh VoltageRatings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1812 (4532 Metric)Size / Dimension0.180" L x 0.125" W (4.57mm x 3.18mm)Height - Seated (Max)-Thickness (Max)0.110" (2.80mm)Lead Spacing-Lead Style-	Capacitance	6800pF
Temperature Coefficient  ATR  Operating Temperature  -55°C ~ 125°C  Features  High Voltage  Ratings  - Applications  General Purpose  Failure Rate  - Mounting Type  Surface Mount, MLCC  Package / Case  1812 (4532 Metric)  Size / Dimension  0.180" L x 0.125" W (4.57mm x 3.18mm)  Height - Seated (Max)  Thickness (Max)  1.10" (2.80mm)  Lead Spacing  - Lead Style  -  ATR  ATR  ATR  ATR  ATR  ATR  ATR	Tolerance	±10%
Operating Temperature-55°C ~ 125°CFeaturesHigh VoltageRatings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1812 (4532 Metric)Size / Dimension0.180" L x 0.125" W (4.57mm x 3.18mm)Height - Seated (Max)-Thickness (Max)0.110" (2.80mm)Lead Spacing-Lead Style-	Voltage - Rated	2000V (2kV)
Features High Voltage Ratings - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1812 (4532 Metric) Size / Dimension 0.180" L x 0.125" W (4.57mm x 3.18mm) Height - Seated (Max) - Thickness (Max) 0.110" (2.80mm) Lead Spacing - Lead Style -	Temperature Coefficient	X7R
Ratings - General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1812 (4532 Metric) Size / Dimension 0.180" L x 0.125" W (4.57mm x 3.18mm) Height - Seated (Max) - Thickness (Max) 0.110" (2.80mm) Lead Spacing - Lead Style	Operating Temperature	-55°C ~ 125°C
Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1812 (4532 Metric) Size / Dimension 0.180" L x 0.125" W (4.57mm x 3.18mm) Height - Seated (Max) - Thickness (Max) 0.110" (2.80mm) Lead Spacing - Lead Style -	Features	High Voltage
Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1812 (4532 Metric) Size / Dimension 0.180" L x 0.125" W (4.57mm x 3.18mm) Height - Seated (Max) - Thickness (Max) 0.110" (2.80mm) Lead Spacing - Lead Style -	Ratings	-
Mounting Type Surface Mount, MLCC Package / Case 1812 (4532 Metric) Size / Dimension 0.180" L x 0.125" W (4.57mm x 3.18mm) Height - Seated (Max) - Thickness (Max) 0.110" (2.80mm) Lead Spacing - Lead Style -	Applications	General Purpose
Package / Case       1812 (4532 Metric)         Size / Dimension       0.180" L x 0.125" W (4.57mm x 3.18mm)         Height - Seated (Max)       -         Thickness (Max)       0.110" (2.80mm)         Lead Spacing       -         Lead Style       -	Failure Rate	-
Size / Dimension       0.180" L x 0.125" W (4.57mm x 3.18mm)         Height - Seated (Max)       -         Thickness (Max)       0.110" (2.80mm)         Lead Spacing       -         Lead Style       -	Mounting Type	Surface Mount, MLCC
Height - Seated (Max)  Thickness (Max)  Lead Spacing  Lead Style  -  -  -  -  -  -  -  -  -  -  -  -  -	Package / Case	1812 (4532 Metric)
Thickness (Max) 0.110" (2.80mm)  Lead Spacing -  Lead Style -	Size / Dimension	0.180" L x 0.125" W (4.57mm x 3.18mm)
Lead Spacing - Lead Style -	Height - Seated (Max)	-
Lead Style -	Thickness (Max)	0.110" (2.80mm)
	Lead Spacing	-
Report errors?	Lead Style	-
		Report errors?

#### 202S43W682KV4E Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

#### 202S43W682KV4E Payment Methods





















# 202S43W682KV4E Shipping Methods













If you have any question about 202S43W682KV4E, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com