

# **2030.0026 Information**

Heisener.com

Part Number 2030.0026

Manufacturer Schurter Inc.

Category Circuit Protection

Electrical, Specialty Fuses

**Description** FUSE BRD MNT 3.15A 125VAC/VDC

Package Radial, Can, Vertical

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

### **Certified Quality**

For Reference Only

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# 2030.0026 Specifications

Manufacturer Part Number  Schurter Inc.  Category  Circuit Protection  Electrical, Specialty Fuses  Package  Radial, Can, Vertical  Series  MSU 125  Fuse Type  Board Mount  Current Rating  3.15A  Voltage Rating - AC  Voltage Rating - DC  Response Time  Fast  Applications  Features  - Class  - Approvals  Operating Temperature  Breaking Capacity @ Rated Voltage  Mounting Type  Response Time Aradial, Can, Vertical  Through Hole  Rackage / Case  Radial, Can, Vertical  Size / Dimension  Report errors?		
CategoryCircuit Protection Electrical, Specialty FusesPackageRadial, Can, VerticalSeriesMSU 125Fuse TypeBoard MountCurrent Rating3.15AVoltage Rating - AC125VVoltage Rating - DC125VResponse TimeFastApplicationsTelecomFeatures-Class-ApprovalscURusOperating Temperature-25°C ~ 85°CBreaking Capacity @ Rated Voltage100AMounting TypeThrough HolePackage / CaseRadial, Can, VerticalSize / Dimension0.252" Dia x 0.346" L (6.40mm x 8.80mm)	Manufacturer Part Number	2030.0026
Package Radial, Can, Vertical Series MSU 125 Fuse Type Board Mount Current Rating 3.15A Voltage Rating - AC 125V Voltage Rating - DC 125V Response Time Fast Applications Telecom Features - Class - Approvals cURus Operating Temperature -25°C ~ 85°C Breaking Capacity @ Rated Voltage 100A Mounting Type Through Hole Package / Case Radial, Can, Vertical Size / Dimension (SUL 125 )  Residual, Can, Vertical Size / Dimension (SUL 125 )  Redial, Can, Vertical Size / Dimension (SUL 125 )  Redial, Can, Vertical Size / Dimension (SUL 125 )  Redial, Can, Vertical Size / Dimension (SUL 125 )  Redial, Can, Vertical Size / Dimension (SUL 125 )  Redial, Can, Vertical Size / Dimension (SUL 125 )  Redial, Can, Vertical Size / Dimension (SUL 125 )  Redial, Can, Vertical	Manufacturer	Schurter Inc.
PackageRadial, Can, VerticalSeriesMSU 125Fuse TypeBoard MountCurrent Rating3.15AVoltage Rating - AC125VVoltage Rating - DC125VResponse TimeFastApplicationsTelecomFeatures-Class-ApprovalscURusOperating Temperature-25°C ~ 85°CBreaking Capacity @ Rated Voltage100AMounting TypeThrough HolePackage / CaseRadial, Can, VerticalSize / Dimension0.252" Dia x 0.346" L (6.40mm x 8.80mm)	Category	Circuit Protection
SeriesMSU 125Fuse TypeBoard MountCurrent Rating3.15AVoltage Rating - AC125VVoltage Rating - DC125VResponse TimeFastApplicationsTelecomFeatures-Class-ApprovalscURusOperating Temperature-25°C ~ 85°CBreaking Capacity @ Rated Voltage100AMounting TypeThrough HolePackage / CaseRadial, Can, VerticalSize / Dimension0.252" Dia x 0.346" L (6.40mm x 8.80mm)		Electrical, Specialty Fuses
Fuse Type         Board Mount           Current Rating         3.15A           Voltage Rating - AC         125V           Voltage Rating - DC         125V           Response Time         Fast           Applications         Telecom           Features         -           Class         -           Approvals         cURus           Operating Temperature         -25°C ~ 85°C           Breaking Capacity @ Rated Voltage         100A           Mounting Type         Through Hole           Package / Case         Radial, Can, Vertical           Size / Dimension         0.252" Dia x 0.346" L (6.40mm x 8.80mm)	Package	Radial, Can, Vertical
Current Rating  Oltage Rating - AC  Voltage Rating - DC  Response Time  Fast  Applications  Telecom  Features  - Class  - Approvals  Operating Temperature  Breaking Capacity @ Rated Voltage  Mounting Type  Through Hole  Package / Case  Size / Dimension  3.15A  3.15A  3.15A  3.15A  125V  105V  Response Time  Fast  Clasv  - Clasv  - Clecom  Telecom  Clurus  - CURus  - CURus  - CURus  - CURus  - CURus  - Current Rating  Approvals  CURus  - CURus  - Current Rating  - Current Rati	Series	MSU 125
Voltage Rating - AC  Voltage Rating - DC  125V  Response Time Fast  Applications  Features - Class - Approvals  Operating Temperature Breaking Capacity @ Rated Voltage  Mounting Type Through Hole  Package / Case Size / Dimension  125V  125V	Fuse Type	Board Mount
Voltage Rating - DC  Response Time Fast  Applications Telecom  Features - Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Package / Case Size / Dimension  125V Fast Fast Fast Fast Clecom - Clecom - Clecom - Clecom - Clecom - CuRus	Current Rating	3.15A
Response Time Applications Telecom  Features - Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Through Hole Package / Case Radial, Can, Vertical Size / Dimension Fast Cless CuRus - CURus -25°C ~ 85°C -25°C ~ 85°C Through Hole -25°C ~ 85°C	Voltage Rating - AC	125V
Applications  Features  - Class  - Approvals  Operating Temperature  -25°C ~ 85°C  Breaking Capacity @ Rated Voltage  Mounting Type  Through Hole  Package / Case  Radial, Can, Vertical  Size / Dimension  Telecom  Telecom  Telecom  Through  Approvals  - CURus  -25°C ~ 85°C  Through Hole  Through Hole  Radial, Can, Vertical  0.252" Dia x 0.346" L (6.40mm x 8.80mm)	Voltage Rating - DC	125V
Features - Class - Class - CURus  Operating Temperature -25°C ~ 85°C  Breaking Capacity @ Rated Voltage 100A  Mounting Type Through Hole  Package / Case Radial, Can, Vertical  Size / Dimension 0.252" Dia x 0.346" L (6.40mm x 8.80mm)	Response Time	Fast
Class - CURus Operating Temperature -25°C ~ 85°C Breaking Capacity @ Rated Voltage 100A Mounting Type Through Hole Package / Case Radial, Can, Vertical Size / Dimension 0.252" Dia x 0.346" L (6.40mm x 8.80mm)	Applications	Telecom
Approvals  CURus  Operating Temperature  -25°C ~ 85°C  Breaking Capacity @ Rated Voltage  100A  Mounting Type  Through Hole  Package / Case  Radial, Can, Vertical  Size / Dimension  CURus  -25°C ~ 85°C  Through Hole  100A  Through Hole  Radial, Can, Vertical  0.252" Dia x 0.346" L (6.40mm x 8.80mm)	Features	-
Operating Temperature  -25°C ~ 85°C  Breaking Capacity @ Rated Voltage  100A  Mounting Type  Through Hole  Package / Case  Radial, Can, Vertical  Size / Dimension  0.252" Dia x 0.346" L (6.40mm x 8.80mm)	Class	-
Breaking Capacity @ Rated Voltage  Mounting Type  Through Hole  Package / Case  Radial, Can, Vertical  Size / Dimension  0.252" Dia x 0.346" L (6.40mm x 8.80mm)	Approvals	cURus
Mounting Type Through Hole Package / Case Radial, Can, Vertical Size / Dimension 0.252" Dia x 0.346" L (6.40mm x 8.80mm)	Operating Temperature	-25°C ~ 85°C
Package / Case Radial, Can, Vertical Size / Dimension 0.252" Dia x 0.346" L (6.40mm x 8.80mm)	Breaking Capacity @ Rated Voltage	100A
Size / Dimension 0.252" Dia x 0.346" L (6.40mm x 8.80mm)	Mounting Type	Through Hole
	Package / Case	Radial, Can, Vertical
Report errors?	Size / Dimension	0.252" Dia x 0.346" L (6.40mm x 8.80mm)
Time		Report errors?

### 2030.0026 Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

# 2030.0026 Payment Methods





















### 2030.0026 Shipping Methods













If you have any question about 2030.0026, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com