

2058299-3 Information



For Reference Only

Part Number 2058299-3

Manufacturer TE Connectivity AMP Connectors

Category Connectors, Interconnects Solid State Lighting Connectors

Description CONN HSNG RCPT&BLADE 6POS NATRL

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









2058299-3 Specifications

Manufacturer Part Number 2058299-3 Manufacturer TE Connectivity AMP Connectors Category Connectors, Interconnects Solid State Lighting Connectors Package - Series - Style Board to Cable/Wire Connector Type Blade and Receptacle Housing Number of Positions 6 Mounting Type Free Hanging (In-Line) Termination Crimp Pitch 0.157" (4.00mm) Fastening Type Latch Lock Features - Housing Color Natural Wire Gauge - Contact Material - Contact Finish - Housing Material Polybutylene Terephthalate (PBT) Operating Temperature -40°C ~ 105°C		
CategoryConnectors, InterconnectsSolid State Lighting ConnectorsPackage-Series-StyleBoard to Cable/WireConnector TypeBlade and Receptacle HousingNumber of Positions6Mounting TypeFree Hanging (In-Line)TerminationCrimpPitch0.157" (4.00mm)Fastening TypeLatch LockFeatures-Housing ColorNaturalWire Gauge-Contact Material-Contact Finish-Housing MaterialPolybutylene Terephthalate (PBT)Operating Temperature-40°C ~ 105°C	Manufacturer Part Number	2058299-3
Package - Series - Style Board to Cable/Wire Connector Type Blade and Receptacle Housing Number of Positions 6 Mounting Type Free Hanging (In-Line) Termination Crimp Pitch 0.157" (4.00mm) Fastening Type Latch Lock Features - Housing Color Natural Wire Gauge - Contact Material - Contact Finish - Housing Material Polybutylene Terephthalate (PBT) Operating Temperature	Manufacturer	TE Connectivity AMP Connectors
Package-Series-StyleBoard to Cable/WireConnector TypeBlade and Receptacle HousingNumber of Positions6Mounting TypeFree Hanging (In-Line)TerminationCrimpPitch0.157" (4.00mm)Fastening TypeLatch LockFeatures-Housing ColorNaturalWire Gauge-Contact Material-Contact Finish-Housing MaterialPolybutylene Terephthalate (PBT)Operating Temperature-40°C ~ 105°C	Category	Connectors, Interconnects
Series-StyleBoard to Cable/WireConnector TypeBlade and Receptacle HousingNumber of Positions6Mounting TypeFree Hanging (In-Line)TerminationCrimpPitch0.157" (4.00mm)Fastening TypeLatch LockFeatures-Housing ColorNaturalWire Gauge-Contact Material-Contact Finish-Housing MaterialPolybutylene Terephthalate (PBT)Operating Temperature-40°C ~ 105°C		Solid State Lighting Connectors
StyleBoard to Cable/WireConnector TypeBlade and Receptacle HousingNumber of Positions6Mounting TypeFree Hanging (In-Line)TerminationCrimpPitch0.157" (4.00mm)Fastening TypeLatch LockFeatures-Housing ColorNaturalWire Gauge-Contact Material-Contact Finish-Housing MaterialPolybutylene Terephthalate (PBT)Operating Temperature-40°C ~ 105°C	Package	-
Connector Type Blade and Receptacle Housing Number of Positions 6 Mounting Type Free Hanging (In-Line) Crimp Pitch O.157" (4.00mm) Fastening Type Latch Lock Features - Housing Color Natural Wire Gauge Contact Material Contact Finish - Housing Material Operating Temperature Blade and Receptacle Housing A Receptacle Housing Natural Free Hanging (In-Line) A Urimp A Urimp A Unimp A U	Series	-
Number of Positions6Mounting TypeFree Hanging (In-Line)TerminationCrimpPitch0.157" (4.00mm)Fastening TypeLatch LockFeatures-Housing ColorNaturalWire Gauge-Contact Material-Contact Finish-Housing MaterialPolybutylene Terephthalate (PBT)Operating Temperature-40°C ~ 105°C	Style	Board to Cable/Wire
Mounting TypeFree Hanging (In-Line)TerminationCrimpPitch0.157" (4.00mm)Fastening TypeLatch LockFeatures-Housing ColorNaturalWire Gauge-Contact Material-Contact Finish-Housing MaterialPolybutylene Terephthalate (PBT)Operating Temperature-40°C ~ 105°C	Connector Type	Blade and Receptacle Housing
TerminationCrimpPitch0.157" (4.00mm)Fastening TypeLatch LockFeatures-Housing ColorNaturalWire Gauge-Contact Material-Contact Finish-Housing MaterialPolybutylene Terephthalate (PBT)Operating Temperature-40°C ~ 105°C	Number of Positions	6
Pitch 0.157" (4.00mm) Fastening Type Latch Lock Features - Housing Color Natural Wire Gauge - Contact Material - Contact Finish - Housing Material Polybutylene Terephthalate (PBT) Operating Temperature -40°C ~ 105°C	Mounting Type	Free Hanging (In-Line)
Fastening Type Latch Lock Features - Housing Color Natural Wire Gauge - Contact Material Contact Finish - Housing Material Operating Temperature Latch Lock - Latch Lock - Polybutylene Terephthalate (PBT) -40°C ~ 105°C	Termination	Crimp
Features - Housing Color Natural - Wire Gauge - Contact Material - Contact Finish - Housing Material Polybutylene Terephthalate (PBT) - 40°C ~ 105°C	Pitch	0.157" (4.00mm)
Housing Color Wire Gauge Contact Material Contact Finish Housing Material Polybutylene Terephthalate (PBT) Operating Temperature Natural Polybutylene Terephthalate (PBT)	Fastening Type	Latch Lock
Wire Gauge - Contact Material - Contact Finish - Housing Material Polybutylene Terephthalate (PBT) Operating Temperature -40°C ~ 105°C	Features	-
Contact Material - Contact Finish - Housing Material Polybutylene Terephthalate (PBT) Operating Temperature -40°C ~ 105°C	Housing Color	Natural
Contact Finish - Housing Material Polybutylene Terephthalate (PBT) $-40^{\circ}\text{C} \sim 105^{\circ}\text{C}$	Wire Gauge	-
Housing Material Polybutylene Terephthalate (PBT) Operating Temperature $-40^{\circ}\text{C} \sim 105^{\circ}\text{C}$	Contact Material	-
Operating Temperature $-40^{\circ}\text{C} \sim 105^{\circ}\text{C}$	Contact Finish	-
	Housing Material	Polybutylene Terephthalate (PBT)
Report errors?	Operating Temperature	-40°C ~ 105°C
±		Report errors?

2058299-3 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

2058299-3 Payment Methods



















2058299-3 Shipping Methods













If you have any question about 2058299-3, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com