



205PMB122KN Information



For Reference Only

Part Number 205PMB122KN
Manufacturer Illinois Capacitor
Category Capacitors
Film Capacitors

Description CAP FILM 2UF 10% 1.2KVDC CHAS MT

Package Rectangular Box

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









205PMB122KN Specifications

Manufacturer Part Number 205PMB122KN Manufacturer Illinois Capacitors Category Capacitors Package Rectangular Box Series PMB Capacitance 2μF Tolerance ±10% Voltage Rating - AC 630V Voltage Rating - DC 1200V (1.2kV) Dielectric Material Polypropylene (PP), Metallized ESR (Equivalent Series Resistance) 2.4 mOhm Operating Temperature 40°C ~ 85°C Mounting Type Chassis Mount Package / Case Rectangular Box Size / Dimension 2.264" L x 1.181" W (57.50mm x 30.00mm) Height - Seated (Max) 1.772" (45.00mm) Termination - Lead Spacing - Applications DC Link, DC Filtering; High Frequency, Switching; Snubber Features - Report errors?	•		
CategoryCapacitorsPackageRectangular BoxSeriesPMBCapacitance2μFTolerance±10%Voltage Rating - AC630VVoltage Rating - DC1200V (1.2kV)Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)2.4 mOhmOperating Temperature-40°C ~ 85°CMounting TypeChassis MountPackage / CaseRectangular BoxSize / Dimension2.264" L x 1.181" W (57.50mm x 30.00mm)Height - Seated (Max)1.772" (45.00mm)Termination-Lead Spacing-ApplicationsDC Link, DC Filtering; High Frequency, Switching; SnubberFeatures-	Manufacturer Part Number	205PMB122KN	
PackageRectangular BoxSeriesPMBCapacitance2μFTolerance±10%Voltage Rating - AC630VVoltage Rating - DC1200V (1.2kV)Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)2.4 mOhmOperating Temperature-40°C ~ 85°CMounting TypeChassis MountPackage / CaseRectangular BoxSize / Dimension2.264" L x 1.181" W (57.50mm x 30.00mm)Height - Seated (Max)1.772" (45.00mm)Termination-Lead Spacing-ApplicationsDC Link, DC Filtering; High Frequency, Switching; SnubberFeatures-	Manufacturer	Illinois Capacitor	
PackageRectangular BoxSeriesPMBCapacitance2μFTolerance±10%Voltage Rating - AC630VVoltage Rating - DC1200V (1.2kV)Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)2.4 mOhmOperating Temperature-40°C ~ 85°CMounting TypeChassis MountPackage / CaseRectangular BoxSize / Dimension2.264" L x 1.181" W (57.50mm x 30.00mm)Height - Seated (Max)1.772" (45.00mm)Termination-Lead Spacing-ApplicationsDC Link, DC Filtering; High Frequency, Switching; SnubberFeatures-	Category	Capacitors	
SeriesPMBCapacitance2μFTolerance±10%Voltage Rating - AC630VVoltage Rating - DC1200V (1.2kV)Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)2.4 mOhmOperating Temperature-40°C ~ 85°CMounting TypeChassis MountPackage / CaseRectangular BoxSize / Dimension2.264" L x 1.181" W (57.50mm x 30.00mm)Height - Seated (Max)1.772" (45.00mm)Termination-Lead Spacing-ApplicationsDC Link, DC Filtering; High Frequency, Switching; SnubberFeatures-		Film Capacitors	
Capacitance $2\mu F$ Tolerance $\pm 10\%$ Voltage Rating - AC $630V$ Voltage Rating - DC $1200V (1.2kV)$ Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance) 2.4 mOhm Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Mounting TypeChassis MountPackage / CaseRectangular BoxSize / Dimension $2.264^{\circ}\text{L} \times 1.181^{\circ}\text{W} (57.50 \text{mm} \times 30.00 \text{mm})$ Height - Seated (Max) 1.772° (45.00mm)Termination-Lead Spacing-ApplicationsDC Link, DC Filtering; High Frequency, Switching; SnubberFeatures-	Package	Rectangular Box	
Tolerance ±10% Voltage Rating - AC 630V Voltage Rating - DC 1200V (1.2kV) Dielectric Material Polypropylene (PP), Metallized ESR (Equivalent Series Resistance) 2.4 mOhm Operating Temperature -40°C ~ 85°C Mounting Type Chassis Mount Package / Case Rectangular Box Size / Dimension 2.264" L x 1.181" W (57.50mm x 30.00mm) Height - Seated (Max) 1.772" (45.00mm) Termination - Lead Spacing - Applications DC Link, DC Filtering; High Frequency, Switching; Snubber Features -	Series	PMB	
Voltage Rating - AC Voltage Rating - DC 1200V (1.2kV) Dielectric Material Polypropylene (PP), Metallized ESR (Equivalent Series Resistance) 2.4 mOhm Operating Temperature -40°C ~ 85°C Mounting Type Chassis Mount Package / Case Rectangular Box Size / Dimension 2.264" L x 1.181" W (57.50mm x 30.00mm) Height - Seated (Max) 1.772" (45.00mm) Termination Lead Spacing Applications DC Link, DC Filtering; High Frequency, Switching; Snubber Features	Capacitance	2μF	
Voltage Rating - DC Dielectric Material Polypropylene (PP), Metallized ESR (Equivalent Series Resistance) 2.4 mOhm Operating Temperature -40°C ~ 85°C Mounting Type Chassis Mount Package / Case Rectangular Box Size / Dimension 2.264" L x 1.181" W (57.50mm x 30.00mm) Height - Seated (Max) 1.772" (45.00mm) Termination - Lead Spacing Applications DC Link, DC Filtering; High Frequency, Switching; Snubber Features -	Tolerance	±10%	
Dielectric Material Polypropylene (PP), Metallized ESR (Equivalent Series Resistance) 2.4 mOhm Operating Temperature -40°C ~ 85°C Mounting Type Chassis Mount Package / Case Rectangular Box Size / Dimension 2.264" L x 1.181" W (57.50mm x 30.00mm) Height - Seated (Max) 1.772" (45.00mm) Termination - Lead Spacing - Applications DC Link, DC Filtering; High Frequency, Switching; Snubber Features -	Voltage Rating - AC	630V	
ESR (Equivalent Series Resistance) Operating Temperature -40°C ~ 85°C Mounting Type Chassis Mount Package / Case Rectangular Box Size / Dimension 2.264" L x 1.181" W (57.50mm x 30.00mm) Height - Seated (Max) 1.772" (45.00mm) Termination Lead Spacing Applications DC Link, DC Filtering; High Frequency, Switching; Snubber Features -	Voltage Rating - DC	1200V (1.2kV)	
Operating Temperature -40°C ~ 85°C Mounting Type Chassis Mount Package / Case Rectangular Box Size / Dimension 2.264" L x 1.181" W (57.50mm x 30.00mm) Height - Seated (Max) 1.772" (45.00mm) Termination - Lead Spacing - Applications DC Link, DC Filtering; High Frequency, Switching; Snubber Features -	Dielectric Material	Polypropylene (PP), Metallized	
Mounting Type Chassis Mount Package / Case Rectangular Box Size / Dimension 2.264" L x 1.181" W (57.50mm x 30.00mm) Height - Seated (Max) 1.772" (45.00mm) Termination - Lead Spacing - Applications DC Link, DC Filtering; High Frequency, Switching; Snubber Features -	ESR (Equivalent Series Resistance)	2.4 mOhm	
Package / Case Rectangular Box Size / Dimension 2.264" L x 1.181" W (57.50mm x 30.00mm) Height - Seated (Max) 1.772" (45.00mm) Termination - Lead Spacing - Applications DC Link, DC Filtering; High Frequency, Switching; Snubber Features -	Operating Temperature	-40°C ~ 85°C	
Size / Dimension 2.264" L x 1.181" W (57.50mm x 30.00mm) Height - Seated (Max) 1.772" (45.00mm) - Lead Spacing - Applications DC Link, DC Filtering; High Frequency, Switching; Snubber Features -	Mounting Type	Chassis Mount	
Height - Seated (Max) Termination Lead Spacing Applications DC Link, DC Filtering; High Frequency, Switching; Snubber Features -	Package / Case	Rectangular Box	
Termination - Lead Spacing - Applications DC Link, DC Filtering; High Frequency, Switching; Snubber Features -	Size / Dimension	2.264" L x 1.181" W (57.50mm x 30.00mm)	
Lead Spacing - Applications DC Link, DC Filtering; High Frequency, Switching; Snubber Features -	Height - Seated (Max)	1.772" (45.00mm)	
Applications DC Link, DC Filtering; High Frequency, Switching; Snubber Features -	Termination	-	
Features -	Lead Spacing	-	
	Applications	DC Link, DC Filtering; High Frequency, Switching; Snubber	
Report errors?	Features	-	
			Report errors?

205PMB122KN Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

205PMB122KN Payment Methods



















205PMB122KN Shipping Methods













If you have any question about 205PMB122KN, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com