

### 207532-4 Information



For Reference Only

Part Number 207532-4

Manufacturer TE Connectivity AMP Connectors

Category Connectors, Interconnects

Rectangular Connectors - Headers, Receptacles,

Female Sockets

**Description** SKT HDR ASSY,24 POSN,METRIMATE

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# 207532-4 Specifications

Manufacturer Part Number         207532-4           Manufacturer         TE Connectivity AMP Connectors           Category         Connectors, Interconnects           Package         -           Series         Metrimate           Connector Type         Header           Contact Type         Board to Cable/Wire           Number of Positions         24           Number of Positions Loaded         All           Pitch - Mating         0.197" (5.00mm)           Number of Rows         4           Row Spacing - Mating         0.197" (5.00mm)           Mounting Type         Through Hole           Testening Type         Latch Holder           Contact Finish - Mating         Gold           Contact Finish Thickness - Mating         30μin (0.76μm)           Insulation Color         Red           Insulation Height         0.565" (14.35mm)           Contact Length - Post         0.181" (4.60mm)           Operating Temperature         -55°C ~ 130°C           Material Flammability Rating         UL94 V-0		
Category         Connectors, Interconnects           Package         -           Series         Metrimate           Connector Type         Header           Contact Type         Female Socket           Style         Board to Cable/Wire           Number of Positions         24           Number of Positions Loaded         All           Pitch - Mating         0.197" (5.00mm)           Number of Rows         4           Row Spacing - Mating         0.197" (5.00mm)           Mounting Type         Through Hole           Termination         Solder           Fastening Type         Latch Holder           Contact Finish - Mating         Gold           Contact Finish Thickness - Mating         30µin (0.76µm)           Insulation Color         Red           Insulation Height         0.565" (14.35mm)           Contact Length - Post         0.181" (4.60mm)           Operating Temperature         -55°C ~ 130°C	Manufacturer Part Number	207532-4
Rectangular Connectors - Headers, Receptacles, Female Sockets  Package - Series Metrimate Connector Type Header Contact Type Female Socket Style Board to Cable/Wire Number of Positions 24 Number of Positions Loaded All Pitch - Mating 0.197" (5.00mm) Number of Rows 4 Row Spacing - Mating 0.197" (5.00mm) Mounting Type Through Hole Termination Solder Fastening Type Latch Holder Contact Finish - Mating Gold Contact Finish Thickness - Mating Insulation Color Red Insulation Height Contact Length - Post 0.181" (4.60mm) Coperating Temperature -55°C ~ 130°C	Manufacturer	TE Connectivity AMP Connectors
Package         -           Series         Metrimate           Connector Type         Header           Contact Type         Female Socket           Style         Board to Cable/Wire           Number of Positions         24           Number of Positions Loaded         All           Pitch - Mating         0.197" (5.00mm)           Number of Rows         4           Row Spacing - Mating         0.197" (5.00mm)           Mounting Type         Through Hole           Termination         Solder           Fastening Type         Latch Holder           Contact Finish - Mating         Gold           Contact Finish Thickness - Mating         30μin (0.76μm)           Insulation Color         Red           Insulation Height         0.565" (14.35mm)           Contact Length - Post         0.181" (4.60mm)           Operating Temperature         -55°C ~ 130°C	Category	Connectors, Interconnects
Series         Metrimate           Connector Type         Header           Contact Type         Female Socket           Style         Board to Cable/Wire           Number of Positions         24           Number of Positions Loaded         All           Pitch - Mating         0.197" (5.00mm)           Number of Rows         4           Row Spacing - Mating         0.197" (5.00mm)           Mounting Type         Through Hole           Termination         Solder           Fastening Type         Latch Holder           Contact Finish - Mating         Gold           Contact Finish Thickness - Mating         30μin (0.76μm)           Insulation Color         Red           Insulation Height         0.565" (14.35mm)           Contact Length - Post         0.181" (4.60mm)           Operating Temperature         -55°C ~ 130°C		Rectangular Connectors - Headers, Receptacles, Female Sockets
Connector TypeHeaderContact TypeFemale SocketStyleBoard to Cable/WireNumber of Positions24Number of Positions LoadedAllPitch - Mating0.197" (5.00mm)Number of Rows4Row Spacing - Mating0.197" (5.00mm)Mounting TypeThrough HoleTerminationSolderFastening TypeLatch HolderContact Finish - MatingGoldContact Finish Thickness - Mating30μin (0.76μm)Insulation ColorRedInsulation Height0.565" (14.35mm)Contact Length - Post0.181" (4.60mm)Operating Temperature-55°C ~ 130°C	Package	-
Contact TypeFemale SocketStyleBoard to Cable/WireNumber of Positions24Number of Positions LoadedAllPitch - Mating0.197" (5.00mm)Number of Rows4Row Spacing - Mating0.197" (5.00mm)Mounting TypeThrough HoleTerminationSolderFastening TypeLatch HolderContact Finish - MatingGoldContact Finish Thickness - Mating30μin (0.76μm)Insulation ColorRedInsulation Height0.565" (14.35mm)Contact Length - Post0.181" (4.60mm)Operating Temperature-55°C ~ 130°C	Series	Metrimate
StyleBoard to Cable/WireNumber of Positions24Number of Positions LoadedAllPitch - Mating0.197" (5.00mm)Number of Rows4Row Spacing - Mating0.197" (5.00mm)Mounting TypeThrough HoleTerminationSolderFastening TypeLatch HolderContact Finish - MatingGoldContact Finish Thickness - Mating30μin (0.76μm)Insulation ColorRedInsulation Height0.565" (14.35mm)Contact Length - Post0.181" (4.60mm)Operating Temperature-55°C ~ 130°C	Connector Type	Header
Number of Positions         24           Number of Positions Loaded         All           Pitch - Mating         0.197" (5.00mm)           Number of Rows         4           Row Spacing - Mating         0.197" (5.00mm)           Mounting Type         Through Hole           Termination         Solder           Fastening Type         Latch Holder           Contact Finish - Mating         Gold           Contact Finish Thickness - Mating         30μin (0.76μm)           Insulation Color         Red           Insulation Height         0.565" (14.35mm)           Contact Length - Post         0.181" (4.60mm)           Operating Temperature         -55°C ~ 130°C	Contact Type	Female Socket
Number of Positions LoadedAllPitch - Mating0.197" (5.00mm)Number of Rows4Row Spacing - Mating0.197" (5.00mm)Mounting TypeThrough HoleTerminationSolderFastening TypeLatch HolderContact Finish - MatingGoldContact Finish Thickness - Mating30μin (0.76μm)Insulation ColorRedInsulation Height0.565" (14.35mm)Contact Length - Post0.181" (4.60mm)Operating Temperature-55°C ~ 130°C	Style	Board to Cable/Wire
Pitch - Mating0.197" (5.00mm)Number of Rows4Row Spacing - Mating0.197" (5.00mm)Mounting TypeThrough HoleTerminationSolderFastening TypeLatch HolderContact Finish - MatingGoldContact Finish Thickness - Mating30μin (0.76μm)Insulation ColorRedInsulation Height0.565" (14.35mm)Contact Length - Post0.181" (4.60mm)Operating Temperature-55°C ~ 130°C	Number of Positions	24
Number of Rows 4  Row Spacing - Mating 0.197" (5.00mm)  Mounting Type Through Hole  Termination Solder  Fastening Type Latch Holder  Contact Finish - Mating Gold  Contact Finish Thickness - Mating 30 $\mu$ in (0.76 $\mu$ m)  Insulation Color Red  Insulation Height 0.565" (14.35mm)  Contact Length - Post 0.181" (4.60mm)  Operating Temperature -55°C ~ 130°C	Number of Positions Loaded	All
Row Spacing - Mating0.197" (5.00mm)Mounting TypeThrough HoleTerminationSolderFastening TypeLatch HolderContact Finish - MatingGoldContact Finish Thickness - Mating30μin (0.76μm)Insulation ColorRedInsulation Height0.565" (14.35mm)Contact Length - Post0.181" (4.60mm)Operating Temperature-55°C ~ 130°C	Pitch - Mating	0.197" (5.00mm)
Mounting TypeThrough HoleTerminationSolderFastening TypeLatch HolderContact Finish - MatingGoldContact Finish Thickness - Mating30μin (0.76μm)Insulation ColorRedInsulation Height0.565" (14.35mm)Contact Length - Post0.181" (4.60mm)Operating Temperature-55°C ~ 130°C	Number of Rows	4
Termination Solder  Fastening Type Latch Holder  Contact Finish - Mating Gold  Contact Finish Thickness - Mating 30 $\mu$ in (0.76 $\mu$ m)  Insulation Color Red  Insulation Height 0.565" (14.35mm)  Contact Length - Post 0.181" (4.60mm)  Operating Temperature -55°C ~ 130°C	Row Spacing - Mating	0.197" (5.00mm)
Fastening Type Latch Holder  Contact Finish - Mating Gold  Contact Finish Thickness - Mating $30\mu$ in $(0.76\mu$ m)  Insulation Color Red  Insulation Height $0.565$ " $(14.35$ mm)  Contact Length - Post $0.181$ " $(4.60$ mm)  Operating Temperature $-55$ °C $\sim 130$ °C	Mounting Type	Through Hole
Contact Finish - Mating Gold  Contact Finish Thickness - Mating $30\mu in (0.76\mu m)$ Insulation Color Red  Insulation Height $0.565" (14.35mm)$ Contact Length - Post $0.181" (4.60mm)$ Operating Temperature $-55^{\circ}\text{C} \sim 130^{\circ}\text{C}$	Termination	Solder
Contact Finish Thickness - Mating $30\mu$ in $(0.76\mu m)$ Insulation Color Red  Insulation Height $0.565$ " $(14.35mm)$ Contact Length - Post $0.181$ " $(4.60mm)$ Operating Temperature $-55$ °C $\sim 130$ °C	Fastening Type	Latch Holder
Insulation ColorRedInsulation Height $0.565"$ (14.35mm)Contact Length - Post $0.181"$ (4.60mm)Operating Temperature $-55^{\circ}\text{C} \sim 130^{\circ}\text{C}$	Contact Finish - Mating	Gold
Insulation Height $0.565" (14.35mm)$ Contact Length - Post $0.181" (4.60mm)$ Operating Temperature $-55^{\circ}\text{C} \sim 130^{\circ}\text{C}$	Contact Finish Thickness - Mating	30μin (0.76μm)
Contact Length - Post $0.181" (4.60 \text{mm})$ Operating Temperature $-55^{\circ}\text{C} \sim 130^{\circ}\text{C}$	Insulation Color	Red
Operating Temperature $-55^{\circ}\text{C} \sim 130^{\circ}\text{C}$	Insulation Height	0.565" (14.35mm)
	Contact Length - Post	0.181" (4.60mm)
Material Flammability Rating UL94 V-0	Operating Temperature	-55°C ~ 130°C
	Material Flammability Rating	UL94 V-0

Contact Finish - Post	Tin-Lead
Mated Stacking Heights	-
Ingress Protection	-
Features	-
	Report errors?

### 207532-4 Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## 207532-4 Payment Methods



















## 207532-4 Shipping Methods













If you have any question about 207532-4, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com