

20800003122 Information

Heisener.com

20800003122 Part Number Manufacturer HARTING

Category Power Supplies - External/Internal (Off-Board)

AC DC Converters

Description AC/DC CONVERTER 48V 60W

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









20800003122 Specifications

Manufacturer Part Number 20800003122 Manufacturer HARTING Category Power Supplies - External/Internal (Off-Board) ACD Converters Package - Series - Type Enclosed Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 48V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 1A Power (Watts) 60W Applications ITE (Commercial) Voltage - Isolation - Efficiency 92% Operating Temperature -10°C ~ 70°C Features Adjustable Output, DC Input Capable, Universal Input Mounting Type DIN Rail Size / Dimension 4.13" L x 1.77" W x 2.95" H (105.0mm x 45.0mm x 75.0mm)		
Category Power Supplies - External/Internal (Off-Board) AC DC Converters Package - Series - Type Enclosed Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 48V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 1A Power (Watts) 60W Applications ITE (Commercial) Voltage - Isolation - Efficiency 92% Operating Temperature -10°C ~ 70°C Features Adjustable Output, DC Input Capable, Universal Input Mounting Type DIN Rail Size / Dimension 4.13" L x 1.77" W x 2.95" H (105.0mm x 45.0mm x 75.0mm)	Manufacturer Part Number	20800003122
Package - Series - Type Enclosed Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 48V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 1A Power (Watts) 60W Applications ITE (Commercial) Voltage - Isolation - Efficiency 92% Operating Temperature -10°C ~ 70°C Features Adjustable Output, DC Input Capable, Universal Input Mounting Type DIN Rail Size / Dimension 4.13" L x 1.77" W x 2.95" H (105.0mm x 45.0mm x 75.0mm)	Manufacturer	HARTING
Package - Series - Type Enclosed Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 48V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 1A Power (Watts) 60W Applications ITE (Commercial) Voltage - Isolation - Efficiency 92% Operating Temperature -10°C ~ 70°C Features Adjustable Output, DC Input Capable, Universal Input Mounting Type DIN Rail Size / Dimension 4.13" L x 1.77" W x 2.95" H (105.0mm x 45.0mm x 75.0mm)	Category	Power Supplies - External/Internal (Off-Board)
Series - Type Enclosed Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 48V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 1A Power (Watts) 60W Applications ITE (Commercial) Voltage - Isolation - Efficiency 92% Operating Temperature -10°C ~ 70°C Features Adjustable Output, DC Input Capable, Universal Input Mounting Type DIN Rail Size / Dimension 4.13" L x 1.77" W x 2.95" H (105.0mm x 45.0mm x 75.0mm)		AC DC Converters
Type Enclosed Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 48V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 1A Power (Watts) 60W Applications ITE (Commercial) Voltage - Isolation - Efficiency 92% Operating Temperature -10°C ~ 70°C Features Adjustable Output, DC Input Capable, Universal Input Mounting Type DIN Rail Size / Dimension 4.13" L x 1.77" W x 2.95" H (105.0mm x 45.0mm x 75.0mm)	Package	-
Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 48V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 1A Power (Watts) 60W Applications ITE (Commercial) Voltage - Isolation - Efficiency 92% Operating Temperature -10°C ~ 70°C Features Adjustable Output, DC Input Capable, Universal Input Mounting Type DIN Rail Size / Dimension 4.13" L x 1.77" W x 2.95" H (105.0mm x 45.0mm x 75.0mm)	Series	-
Voltage - Input 85 ~ 264 VAC Voltage - Output 1 48V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 1A Power (Watts) 60W Applications ITE (Commercial) Voltage - Isolation - Efficiency 92% Operating Temperature -10°C ~ 70°C Features Adjustable Output, DC Input Capable, Universal Input Mounting Type DIN Rail Size / Dimension 4.13" L x 1.77" W x 2.95" H (105.0mm x 45.0mm x 75.0mm)	Туре	Enclosed
Voltage - Output 1 Voltage - Output 2 - Voltage - Output 3 Voltage - Output 4 - Current - Output (Max) Applications ITE (Commercial) Voltage - Isolation Efficiency Operating Temperature Features Adjustable Output, DC Input Capable, Universal Input Mounting Type DIN Rail Size / Dimension 4.13" L x 1.77" W x 2.95" H (105.0mm x 45.0mm x 75.0mm)	Number of Outputs	1
Voltage - Output 2 Voltage - Output 3 - Voltage - Output 4 Current - Output (Max) Applications ITE (Commercial) Voltage - Isolation Fifficiency Operating Temperature Features Adjustable Output, DC Input Capable, Universal Input Mounting Type DIN Rail Size / Dimension - - - - - - - - - - - - -	Voltage - Input	85 ~ 264 VAC
Voltage - Output 3 Voltage - Output 4 - Current - Output (Max) Applications ITE (Commercial) Voltage - Isolation - Efficiency Operating Temperature Features Adjustable Output, DC Input Capable, Universal Input Mounting Type Size / Dimension - Augusta 1.3" L x 1.77" W x 2.95" H (105.0mm x 45.0mm x 75.0mm)	Voltage - Output 1	48V
Voltage - Output 4 Current - Output (Max) Power (Watts) Applications ITE (Commercial) Voltage - Isolation - Efficiency 92% Operating Temperature -10°C ~ 70°C Features Adjustable Output, DC Input Capable, Universal Input Mounting Type DIN Rail Size / Dimension 4.13" L x 1.77" W x 2.95" H (105.0mm x 45.0mm x 75.0mm)	Voltage - Output 2	-
Current - Output (Max) Power (Watts) Applications ITE (Commercial) Voltage - Isolation - Efficiency 92% Operating Temperature -10°C ~ 70°C Features Adjustable Output, DC Input Capable, Universal Input Mounting Type DIN Rail Size / Dimension 4.13" L x 1.77" W x 2.95" H (105.0mm x 45.0mm x 75.0mm)	Voltage - Output 3	-
Power (Watts) 60W Applications ITE (Commercial) Voltage - Isolation - Efficiency 92% Operating Temperature -10°C ~ 70°C Features Adjustable Output, DC Input Capable, Universal Input Mounting Type DIN Rail Size / Dimension 4.13" L x 1.77" W x 2.95" H (105.0mm x 45.0mm x 75.0mm)	Voltage - Output 4	-
Applications ITE (Commercial) Voltage - Isolation - Efficiency 92% Operating Temperature -10°C ~ 70°C Features Adjustable Output, DC Input Capable, Universal Input Mounting Type DIN Rail Size / Dimension 4.13" L x 1.77" W x 2.95" H (105.0mm x 45.0mm x 75.0mm)	Current - Output (Max)	1A
Voltage - Isolation Efficiency 92% Operating Temperature -10°C ~ 70°C Features Adjustable Output, DC Input Capable, Universal Input Mounting Type DIN Rail Size / Dimension 4.13" L x 1.77" W x 2.95" H (105.0mm x 45.0mm x 75.0mm)	Power (Watts)	60W
Efficiency 92% Operating Temperature $-10^{\circ}\text{C} \sim 70^{\circ}\text{C}$ Features Adjustable Output, DC Input Capable, Universal Input Mounting Type DIN Rail Size / Dimension $4.13^{\circ}\text{L} \times 1.77^{\circ}\text{W} \times 2.95^{\circ}\text{H} (105.0\text{mm} \times 45.0\text{mm} \times 75.0\text{mm})$	Applications	ITE (Commercial)
Operating Temperature -10°C ~ 70°C Adjustable Output, DC Input Capable, Universal Input Mounting Type DIN Rail Size / Dimension 4.13" L x 1.77" W x 2.95" H (105.0mm x 45.0mm x 75.0mm)	Voltage - Isolation	-
Features Adjustable Output, DC Input Capable, Universal Input Mounting Type DIN Rail Size / Dimension 4.13" L x 1.77" W x 2.95" H (105.0mm x 45.0mm x 75.0mm)	Efficiency	92%
Mounting Type DIN Rail Size / Dimension 4.13" L x 1.77" W x 2.95" H (105.0mm x 45.0mm x 75.0mm)	Operating Temperature	-10°C ~ 70°C
Size / Dimension 4.13" L x 1.77" W x 2.95" H (105.0mm x 45.0mm x 75.0mm)	Features	Adjustable Output, DC Input Capable, Universal Input
	Mounting Type	DIN Rail
Report errors?	Size / Dimension	4.13" L x 1.77" W x 2.95" H (105.0mm x 45.0mm x 75.0mm)
		Report errors?

20800003122 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

20800003122 Payment Methods



















20800003122 Shipping Methods













If you have any question about 20800003122, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com