

20KPA132CA-B

Request a Quote

20KPA132CA-B Information

		20WDA 122CA D
	Part Number	20KPA132CA-B
	Manufacturer	Littelfuse Inc.
www.nelseper.com	Category	Circuit Protection TVS - Diodes
~	Description	TVS DIODE 132VWM 213VC P600
	Package	P600, Axial
		For the pricing/inventory/lead time, please contact us
For Reference Only		Website: https://www.heisener.com E-mail: salesdept@heisener.com

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



20KPA132CA-B Specifications

Manufacturer Part Number20KPA132CA-BManufacturerLittelfuse Inc.CategoryCircuit ProtectionPackageP600, AxialSeries20KPATypeZenerUndirectional Channels-Bidirectional Channels1Voltage - Reverse Standoff (Typ)32VVoltage - Clamping (Max) @ Ipp213VVoltage - Clamping (Max) @ Ipp2000W (20KW)Power - Peak Pulse2000W (20KW)Power Line ProtectionNoApplicationsGeneral PurposeOperating Temperature-Operating Temperature-55°C ~ 175°C (TJ)Mounting TypeP600, AxialPackage / CaseP600, Axial		
CategoryCircuit ProtectionTVS - DiodesPackageP600, AxialSeriesOKPATypeZenerUnidirectional Channels-Bidirectional Channels1Voltage - Reverse Standoff (Typ)J32VVoltage - Breakdown (Min)147.4VVoltage - Clamping (Max) @ IppJ13VPower - Peak Pulse (10/100µs)94.8APower Line ProtectionNoApplicationsGeneral PurposeApplicationsSolow (20kW)Power Line ProtectionSolow (20kW)ApplicationsSolow (20kW)ApplicationsSolow (20kW)ApplicationsSolow (20kW)Mounting TypeSolow (20kW)Package / CaseFrough Hole	Manufacturer Part Number	20KPA132CA-B
TVS - DiodesPackageP600, AxialSeries20KPATypeZenerUnidirectional Channels-Bidirectional Channels1Voltage - Reverse Standoff (Typ)132VVoltage - Breakdown (Min)147.4VVoltage - Clamping (Max) @ Ipp213VCurrent - Peak Pulse (10/1000µs)94.8APower - Peak Pulse20000W (20kW)Power Line ProtectionNoApplicationsGeneral PurposeCapacitance @ Frequency-Operating Temperature-55°C ~175°C (TJ)Mounting TypeF000, Axial	Manufacturer	Littelfuse Inc.
PackageP600, AxialSeries20KPATypeZenerUndirectional Channels-Bidirectional Channels1Voltage - Reverse Standoff (Typ)132VVoltage - Reverse Standoff (Typ)147.4VVoltage - Clamping (Max) @ Ipp213VCurrent - Peak Pulse (10/100µs)94.8APower Line ProtectionNoApplicationsGeneral PurposeCapacitance @ Frequency-Operating Temperature55°C ~ 175°C (TJ)Mounting TypeFoko, Axial	Category	Circuit Protection
Series20KPATypeZenerUnidirectional Channels-Bidirectional Channels1Voltage - Reverse Standoff (Typ)132VVoltage - Breakdown (Min)147.4VVoltage - Clamping (Max) @ Ipp213VCurrent - Peak Pulse (10/1000µs)94.8APower - Peak Pulse2000W (20kW)Power Line ProtectionNoApplicationsGeneral PurposeCapacitance @ Frequency-Operating Temperature-55°C ~175°C (TJ)Mounting TypeP600, Axial		TVS - Diodes
TypeZenerUnidirectional Channels-Bidirectional Channels1Voltage - Reverse Standoff (Typ)132VVoltage - Breakdown (Min)147.4VVoltage - Clamping (Max) @ Ipp213VCurrent - Peak Pulse (10/1000µs)94.8APower - Peak Pulse2000W (20kW)Power Line ProtectionNoApplicationsGeneral PurposeCapacitance @ Frequency-Operating Temperature-55°C ~175°C (TJ)Mounting TypeFolo, Axial	Package	P600, Axial
Unidirectional Channels-Bidirectional Channels1Voltage - Reverse Standoff (Typ)132VVoltage - Breakdown (Min)147.4VVoltage - Clamping (Max) @ Ipp213VCurrent - Peak Pulse (10/1000µs)94.8APower - Peak Pulse20000W (20kW)Power Line ProtectionNoApplicationsGeneral PurposeCapacitance @ Frequency-Operating Temperature55°C ~ 175°C (TJ)Mounting TypeP600, Axial	Series	20KPA
Bidirectional Channels1Voltage - Reverse Standoff (Typ)132VVoltage - Breakdown (Min)147.4VVoltage - Clamping (Max) @ Ipp213VCurrent - Peak Pulse (10/1000µs)94.8APower - Peak Pulse2000W (20kW)Power Line ProtectionNoApplicationsGeneral PurposeCapacitance @ Frequency-Operating Temperature.55°C ~ 175°C (TJ)Mounting TypeFotog AcialPackage / CaseP600, Axial	Туре	Zener
Voltage - Reverse Standoff (Typ)132VVoltage - Breakdown (Min)147.4VVoltage - Clamping (Max) @ Ipp213VCurrent - Peak Pulse (10/100µs)94.8APower - Peak Pulse2000W (20kW)Power Line ProtectionNoApplicationsGeneral PurposeCapacitance @ Frequency-Operating Temperature-55°C ~175°C (TJ)Mounting TypePoto, Axial	Unidirectional Channels	-
Voltage - Breakdown (Min)147.4VVoltage - Clamping (Max) @ Ipp213VCurrent - Peak Pulse (10/1000µs)94.8APower - Peak Pulse (10/1000µs)20000W (20kW)Power Line ProtectionNoApplicationsGeneral PurposeCapacitance @ Frequency-Operating Temperature-55°C ~ 175°C (TJ)Mounting TypeThrough HolePackage / CaseP600, Axial	Bidirectional Channels	1
Voltage - Clamping (Max) @ Ipp213VCurrent - Peak Pulse (10/1000µs)94.8APower - Peak Pulse20000W (20kW)Power Line ProtectionNoApplicationsGeneral PurposeCapacitance @ Frequency-Operating Temperature-55°C ~ 175°C (TJ)Mounting TypeThrough HolePackage / CaseP600, Axial	Voltage - Reverse Standoff (Typ)	132V
Current - Peak Pulse (10/1000µs)94.8APower - Peak Pulse2000W (20kW)Power Line ProtectionNoApplicationsGeneral PurposeCapacitance @ Frequency-Operating Temperature-55°C ~ 175°C (TJ)Mounting TypeThrough HolePackage / CaseP600, Axial	Voltage - Breakdown (Min)	147.4V
Power - Peak Pulse2000W (20kW)Power Line ProtectionNoApplicationsGeneral PurposeCapacitance @ Frequency-Operating Temperature-55°C ~ 175°C (TJ)Mounting TypeThrough HolePackage / Case9600, Axial	Voltage - Clamping (Max) @ Ipp	213V
Power Line ProtectionNoApplicationsGeneral PurposeCapacitance @ Frequency-Operating Temperature-55°C ~ 175°C (TJ)Mounting TypeThrough HolePackage / Case9600, Axial	Current - Peak Pulse (10/1000µs)	94.8A
ApplicationsGeneral PurposeCapacitance @ Frequency-Operating Temperature-55°C ~ 175°C (TJ)Mounting TypeThrough HolePackage / Case9600, Axial	Power - Peak Pulse	20000W (20kW)
Capacitance @ Frequency-Operating Temperature-55°C ~ 175°C (TJ)Mounting TypeThrough HolePackage / CaseP600, Axial	Power Line Protection	No
Operating Temperature-55°C ~ 175°C (TJ)Mounting TypeThrough HolePackage / CaseP600, Axial	Applications	General Purpose
Mounting TypeThrough HolePackage / CaseP600, Axial	Capacitance @ Frequency	-
Package / Case P600, Axial	Operating Temperature	-55°C ~ 175°C (TJ)
-	Mounting Type	Through Hole
Supplier Device Package P600	Package / Case	P600, Axial
	Supplier Device Package	P600
Report error		Report errors?

20KPA132CA-B Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

20KPA132CA-B Payment Methods



20KPA132CA-B Shipping Methods



If you have any question about 20KPA132CA-B, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com