

20KPA204A-B

20KPA204A-B Information

www.telseper.com	Part Number Manufacturer Category Description Package	20KPA204A-B Littelfuse Inc. Circuit Protection TVS - Diodes TVS DIODE 204VWM 329VC P600 P600, Axial	
	8	For the pricing/inventory/lead time, please contact us	
For Reference Only		Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



20KPA204A-B Specifications

Manufacturer Part Number20KPA204A-BManufacturerLittelfuse Inc.CategoryCircuit ProtectionTVS - DiodesTVS - DiodesPackageP600, AxialSeries20KPATypeZenerUnidirectional Channels1Bidirectional Channels-Voltage - Reverse Standoff (Typ)204VVoltage - Breakdown (Min)227.9VVoltage - Clamping (Max) @ Ipp329VCurrent - Peak Pulse (10/1000µs)61.4APower - Peak Pulse (10/1000µs)General PurposeApplicationsGeneral PurposeCapacitance @ Frequency-Mounting TypeThrough HolePackage / CaseP600, AxialSupplice CaseP600, Axial		
Category Circuit Protection TVS - Diodes Package P600, Axial Series 20KPA Type Zener Undirectional Channels 20er Bidirectional Channels - Voltage - Reverse Standoff (Typ) 204V Voltage - Breakdown (Min) 2019V Voltage - Clamping (Max) @ Ipp 329V Current - Peak Pulse (10/100µs) 614A Power - Peak Pulse 2000W (20kW) Power Line Protection No Applications General Purpose Capacitance @ Frequency - Operating Temperature 55° C r175° C (TJ) Mounting Type Honogh Hole Package / Case 600, Axial Supplier Device Package F000, Axial	Manufacturer Part Number	20KPA204A-B
TVS - DiodesPackageP600, AxialSeries20KPATypeZenerUnidirectional Channels1Bidirectional Channels-Voltage - Reverse Standoff (Typ)204VVoltage - Breakdown (Min)227.9VVoltage - Clamping (Max) @ Ipp329VCurrent - Peak Pulse (10/1000µs)61.4APower Jeak Pulse20000W (20kW)Power Line ProtectionNoApplicationsGeneral PurposeCapacitance @ Frequency-Operating Temperature-55°C ~ 175°C (TJ)Mounting TypeFrodo, AxialPackage / CaseP600, AxialSupplier Device PackageP600	Manufacturer	Littelfuse Inc.
PackageP600, AxialSeries20KPATypeZenerUnidirectional Channels1Bidirectional Channels-Voltage - Reverse Standoff (Typ)204VVoltage - Breakdown (Min)227.9VVoltage - Clamping (Max) @ Ipp329VCurrent - Peak Pulse (10/100µs)61.4APower - Peak Pulse2000W (20kW)Power Jene ArgungGeneral PurposeApplicationsGeneral PurposeCapacitance @ Frequency-Mounting Type55°C ~ 175°C (TJ)Mounting TypeFrodo, AxialPackage / CaseP600	Category	Circuit Protection
Series20KPATypeZenerUndirectional Channels1Bidirectional Channels-Voltage - Reverse Standoff (Typ)204VVoltage - Breakdown (Min)227.9VVoltage - Clamping (Max) @ Ipp329VCurrent - Peak Pulse (10/100µs)61.4APower - Peak Pulse2000W (20kW)Power Line ProtectionNoApplicationsGeneral PurposeCapacitance @ Frequency-Operating Temperature-55°C ~175°C (TJ)Mounting TypeP600 Axial		TVS - Diodes
TypeZenerUndirectional Channels1Bidirectional Channels-Voltage - Reverse Standoff (Typ)204VVoltage - Breakdown (Min)207.9VVoltage - Clamping (Max) @ Ipp329VCurrent - Peak Pulse (10/1000µs)61.4APower - Peak Pulse2000W (20kW)Power Line ProtectionNoApplicationsGeneral PurposeCapacitance @ Frequency-Operating Type55°C ~ 175°C (TJ)Mounting TypeFolog AcialPackage / CaseP600, AxialSupplier Device PackageP600	Package	P600, Axial
Unidirectional Channels1Bidirectional Channels-Voltage - Reverse Standoff (Typ)204VVoltage - Breakdown (Min)227.9VVoltage - Clamping (Max) @ Ipp329VCurrent - Peak Pulse (10/100µs)61.4APower - Peak Pulse2000W (20kW)Power Line ProtectionNoApplicationsGeneral PurposeCapacitance @ Frequency-Operating Temperature55°C ~ 175°C (TJ)Mounting TypeFoloy AxialPackage / CasePeotoSupplier Device PackagePeoto	Series	20KPA
Bidirectional Channels-Voltage - Reverse Standoff (Typ)204VVoltage - Breakdown (Min)227.9VVoltage - Clamping (Max) @ Ipp329VCurrent - Peak Pulse (10/1000µs)61.4APower - Peak Pulse2000W (20kW)Power Line ProtectionNoApplicationsGeneral PurposeCapacitance @ Frequency-Operating Temperature55°C ~ 175°C (TJ)Mounting TypeThrough HolePackage / CaseP600, AxialSupplier Device PackageP600	Туре	Zener
Voltage - Reverse Standoff (Typ)204VVoltage - Breakdown (Min)227.9VVoltage - Clamping (Max) @ Ipp329VCurrent - Peak Pulse (10/1000µs)61.4APower - Peak Pulse20000W (20kW)Power Line ProtectionNoApplicationsGeneral PurposeCapacitance @ Frequency-Operating Temperature-55°C ~ 175°C (TJ)Mounting TypeThrough HolePackage / CaseP600, AxialSupplier Device PackageP600	Unidirectional Channels	1
Voltage - Breakdown (Min)227.9VVoltage - Clamping (Max) @ Ipp329VCurrent - Peak Pulse (10/1000µs)61.4APower - Peak Pulse20000W (20kW)Power Line ProtectionNoApplicationsGeneral PurposeCapacitance @ Frequency-Operating Temperature-55°C ~ 175°C (TJ)Mounting TypeThrough HolePackage / CaseP600, Axial	Bidirectional Channels	-
Voltage - Clamping (Max) @ Ipp329VCurrent - Peak Pulse (10/1000µs)61.4APower - Peak Pulse20000W (20kW)Power Line ProtectionNoApplicationsGeneral PurposeCapacitance @ Frequency-Operating Temperature-55°C ~ 175°C (TJ)Mounting TypeThrough HolePackage / CaseP600, AxialSupplier Device PackageP600	Voltage - Reverse Standoff (Typ)	204V
Current - Peak Pulse (10/1000µs)61.4APower - Peak Pulse20000W (20kW)Power Line ProtectionNoApplicationsGeneral PurposeCapacitance @ Frequency-Operating Temperature-55°C ~175°C (TJ)Mounting TypeThrough HolePackage / CaseP600, AxialSupplier Device PackageP600	Voltage - Breakdown (Min)	227.9V
Power - Peak Pulse2000W (20kW)Power Line ProtectionNoApplicationsGeneral PurposeCapacitance @ Frequency-Operating Temperature-55°C ~ 175°C (TJ)Mounting TypeThrough HolePackage / CaseP600, AxialSupplier Device PackageP600	Voltage - Clamping (Max) @ Ipp	329V
Power Line ProtectionNoApplicationsGeneral PurposeCapacitance @ Frequency-Operating Temperature-55°C ~ 175°C (TJ)Mounting TypeThrough HolePackage / CaseP600, AxialSupplier Device PackageP600	Current - Peak Pulse (10/1000µs)	61.4A
ApplicationsGeneral PurposeCapacitance @ Frequency-Operating Temperature-55°C ~ 175°C (TJ)Mounting TypeThrough HolePackage / CaseP600, AxialSupplier Device PackageP600	Power - Peak Pulse	20000W (20kW)
Capacitance @ Frequency-Operating Temperature-55°C ~ 175°C (TJ)Mounting TypeThrough HolePackage / CaseP600, AxialSupplier Device PackageP600	Power Line Protection	No
Operating Temperature-55°C ~ 175°C (TJ)Mounting TypeThrough HolePackage / CaseP600, AxialSupplier Device PackageP600	Applications	General Purpose
Mounting TypeThrough HolePackage / CaseP600, AxialSupplier Device PackageP600	Capacitance @ Frequency	-
Package / CaseP600, AxialSupplier Device PackageP600	Operating Temperature	-55°C ~ 175°C (TJ)
Supplier Device Package P600	Mounting Type	Through Hole
	Package / Case	P600, Axial
Report errors ⁶	Supplier Device Package	P600
		Report errors?

20KPA204A-B Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

20KPA204A-B Payment Methods



20KPA204A-B Shipping Methods



If you have any question about 20KPA204A-B, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com