

210-13-320-41-001000

210-13-320-41-001000 Information

Heisener.com	 210-13-320-41-001000 Mill-Max Manufacturing Corp. Connectors, Interconnects Sockets for ICs, Transistors CONN IC DIP SOCKET 20POS GOLD - For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



210-13-320-41-001000 Specifications

Manufacturer Part Number210-13-320-41-001000ManufacturerMill-Max Manufacturing Corp.CategoryConnectors, InterconnectsSockets for ICs, TransistorsPackage-Series210TypeDIP, 0.3" (7.62mm) Row SpacingNumber of Positions or Pins (Grid)20 (2 x 10)Pitch - Mating0.100" (2.54mm)Contact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)Mounting TypeThrough HoleFeaturesClosed FramePitch - Post0.100" (2.54mm)FeaturesClosed FrameFortinationSolderFitch - Post0.100" (2.54mm)Contact Finish - MatingGoldGoldContact Finish - MatingMounting TypeThrough HoleFeaturesClosed FrameContact Finish - Post0.100" (2.54mm)Contact Finish - PostGoldContact Finish - Post0.100" (2.54mm)Contact Finish Thickness - PostBujin (0.52µm)Contact Material - PostSolderContact Material - PostSolderContact Material - PostDipuin (0.52µm)Contact Material - PostBrass AlloyHousing MaterialPolycyclohexyLenedimethyLene Terephhalate (PCT), PolyesterOperating Termerature55°C - 125°C			
CategoryConnectors, InterconnectsCacegoryConnectors, InterconnectsPackage-Series210TypeDIP, 0.3" (7.62mm) Row SpacingNumber of Positions or Pins (Grid)20 (2 x 10)Pitch - Mating0.100" (2.54mm)Contact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)Contact Material - MatingBeryllium CopperMounting TypeThrough HoleFeaturesClosed FramePitch - Post0.100" (2.54mm)Contact Finish - NatingSolderTerminationSolderFeaturesClosed FrameOther SpaceGoldContact Finish - PostGoldContact Finish - PostGoldContact Finish Thickness - PostIoµin (0.25µm)Contact Finish Thickness - PostBass AlloyHousing MaterialPolycyclohexylenedimethylene Terephthalate (PCT), Polyester	Manufacturer Part Number	210-13-320-41-001000	
NumberSockets for ICs, TransistorsPackage-Series210TypeDIP, 0.3" (7.62mm) Row SpacingNumber of Positions or Pins (Grid)20 (2 x 10)Pitch - Mating0.100" (2.54mm)Contact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)Contact Material - MatingBeryllium CopperMounting TypeThrough HoleFeaturesClosed FramePitch - Post0.100" (2.54mm)Contact Finish - PostGoldContact Finish - PostGoldContact Finish Thickness - PostBras AlloyHousing MaterialPolycyclohexylenedimethylene Terephthalate (PCT), Polyester	Manufacturer	Mill-Max Manufacturing Corp.	
Package-Series210TypeDIP, 0.3" (7.62mm) Row SpacingNumber of Positions or Pins (Grid)20 (2 x 10)Pitch - Mating0.100" (2.54mm)Contact Finish - MatingGoldContact Finish - Mating30µin (0.76µm)Contact Finish Thickness - MatingBeryllium CopperMounting TypeThrough HoleFeaturesClosed FrameFreminationSolderPitch - PostGoldContact Finish - PostGoldContact Finish - PostGoldFortart Finish - PostGoldFortart Finish - PostGoldContact Finish - PostGoldContact Finish - PostGoldContact Finish - PostGoldFortart Finish - PostGoldContact Finish - PostGoldFortart Finish - PostGoldFortart Finish - PostGoldFortart Finish - PostBras AlloyHousing MaterialPolycychenetinethylene Frephthalate (PCT), Polyester	Category	Connectors, Interconnects	
Series210TypeDIP, 0.3" (7.62mm) Row SpacingNumber of Positions or Pins (Grid)20 (2 x 10)Pitch - Mating0.100" (2.54mm)Contact Finish - MatingGoldContact Finish - Mating30µin (0.76µm)Contact Finish Thickness - MatingBeryllium CopperMounting TypeThrough HoleFeaturesClosed FramePitch - Post0.100" (2.54mm)Contact Finish - PostSolderContact Finish - Post0.100" (2.54mm)Contact Finish - Post0.100" (2.54mm)Contact Finish - PostGoldContact Finish - PostGoldContact Finish - PostBeryllium (0.25µm)Contact Finish - PostBeryllium (0.25µm)Contact Finish - PostBrass AlloyHousing MaterialPolycyclohexylenedimethylene Terephthalate (PCT), Polyester		Sockets for ICs, Transistors	
TypeDIP, 0.3" (7.62mm) Row SpacingTypeDIP, 0.3" (7.62mm) Row SpacingNumber of Positions or Pins (Grid)20 (2 x 10)Pitch - Mating0.100" (2.54mm)Contact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)Contact Finish Thickness - MatingBeryllium CopperMounting TypeThrough HoleFeaturesClosed FrameFeaturesSolderPitch - Post0.100" (2.54mm)Contact Finish Thickness - PostGoldContact Finish Thickness - PostGoldContact Material - Post10µin (0.25µm)Contact Material - PostBrass AlloyHousing MaterialPolycyclohexylenedimethylene Terephthalate (PCT), Polyester	Package	-	
Number of Positions or Pins (Grid)20 (2 x 10)Pitch - Mating0.100" (2.54mm)Contact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)Contact Material - MatingBeryllium CopperMounting TypeThrough HoleFeaturesClosed FrameTerminationSolderPitch - Post0.100" (2.54mm)Contact Finish - PostGoldContact Finish - PostGoldContact Finish - PostGoldContact Finish - PostJ0µin (0.25µm)Contact Finish Thickness - PostI0µin (0.25µm)Housing Material - PostBrass AlloyPostPolycyclohexylenedimethylene Terephthalate (PCT), Polyester	Series	210	
Pitch - Mating0.100" (2.54mm)Contact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)Contact Material - MatingBeryllium CopperMounting TypeThrough HoleFeaturesClosed FrameTerminationSolderPitch - Post0.100" (2.54mm)Contact Finish - PostGoldContact Finish - PostGoldContact Finish Thickness - Post10µin (0.25µm)Contact Finish Thickness - PostBrass AlloyHousing MaterialPolycyclohexylenedimethylene Terephthalate (PCT), Polyester	Туре	DIP, 0.3" (7.62mm) Row Spacing	
Contact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)Contact Material - MatingBeryllium CopperMounting TypeThrough HoleFeaturesClosed FrameTerminationSolderPitch - Post0.100" (2.54mm)Contact Finish - PostGoldContact Finish - Post10µin (0.25µm)Contact Finish - PostBrass AlloyHousing Material - PostBrass Alloy	Number of Positions or Pins (Grid)	20 (2 x 10)	
Contact Finish Thickness - Mating30µin (0.76µm)Contact Material - MatingBeryllium CopperMounting TypeThrough HoleFeaturesClosed FrameFeaturesSolderTerminationSolderPitch - Post0.100" (2.54mm)Contact Finish - PostGoldContact Finish - Post10µin (0.25µm)Contact Finish Thickness - PostBrass AlloyHousing MaterialPolycyclohexylenedingene freephthalate (PCT), Polyester	Pitch - Mating	0.100" (2.54mm)	
Contact Material - MatingBeryllium CopperMounting TypeThrough HoleFeaturesClosed FrameTerminationSolderPitch - Post0.100" (2.54mm)Contact Finish - PostGoldContact Finish - Post10µin (0.25µm)Contact Finish Thickness - PostBrass AlloyHousing MaterialPolycyclohexylenedinettylene Terephthalate (PCT), Polyester	Contact Finish - Mating	Gold	
Mounting TypeThrough HoleFeaturesClosed FrameTerminationSolderPitch - Post0.100" (2.54mm)Contact Finish - PostGoldContact Finish Thickness - Post10µin (0.25µm)Contact Material - PostBrass AlloyHousing MaterialPolycyclohexylenedimethylene Terephthalate (PCT), Polyester	Contact Finish Thickness - Mating	30µin (0.76µm)	
FeaturesClosed FrameTerminationSolderPitch - Post0.100" (2.54mm)Contact Finish - PostGoldContact Finish Thickness - Post10µin (0.25µm)Contact Material - PostBrass AlloyHousing MaterialPolycyclohexylenedimethylene Terephthalate (PCT), Polyester	Contact Material - Mating	Beryllium Copper	
TerminationSolderPitch - Post0.100" (2.54mm)Contact Finish - PostGoldContact Finish Thickness - Post10µin (0.25µm)Contact Material - PostBrass AlloyHousing MaterialPolycyclohexylene Terephthalate (PCT), Polyester	Mounting Type	Through Hole	
Pitch - Post0.100" (2.54mm)Contact Finish - PostGoldContact Finish Thickness - Post10µin (0.25µm)Contact Material - PostBrass AlloyHousing MaterialPolycyclohexylenedimethylene Terephthalate (PCT), Polyester	Features	Closed Frame	
Contact Finish - PostGoldContact Finish Thickness - Post10µin (0.25µm)Contact Material - PostBrass AlloyHousing MaterialPolycyclohexylenedimethylene Terephthalate (PCT), Polyester	Termination	Solder	
Contact Finish Thickness - Post10μin (0.25μm)Contact Material - PostBrass AlloyHousing MaterialPolycyclohexylenedimethylene Terephthalate (PCT), Polyester	Pitch - Post	0.100" (2.54mm)	
Contact Material - PostBrass AlloyHousing MaterialPolycyclohexylenedimethylene Terephthalate (PCT), Polyester	Contact Finish - Post	Gold	
Housing Material Polycyclohexylenedimethylene Terephthalate (PCT), Polyester	Contact Finish Thickness - Post	10µin (0.25µm)	
	Contact Material - Post	Brass Alloy	
Operating Temperature $-55^{\circ}C \sim 125^{\circ}C$	Housing Material	Polycyclohexylenedimethylene Terephthalate (PCT), Polyester	
-1	Operating Temperature	-55°C ~ 125°C	
Report errors ⁶			Report errors?

210-13-320-41-001000 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

210-13-320-41-001000 Payment Methods





If you have any question about 210-13-320-41-001000, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com