

# 210-43-316-41-001000

#### 210-43-316-41-001000 Information

A A A A A A A A A A A A A A A A A A A	 210-43-316-41-001000 Mill-Max Manufacturing Corp. Connectors, Interconnects Sockets for ICs, Transistors CONN IC DIP SOCKET 16POS GOLD - For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

### **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



# 210-43-316-41-001000 Specifications

Manufacturer Part Number210-43-316-41-001000ManufacturerMill-Max Manufacturing Corp.CategoryConnectors, InterconnectsSockets for ICs, TransistorsPackage-Series210TypeDIP, 0.3" (7.62mm) Row SpacingNumber of Positions or Pins (Grid)16 (2 x 8)Pitch - Mating0.100" (2.54mm)Contact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)Mounting TypeThrough HoleFeaturesClosed FramePitch - Post0.100" (2.54mm)Features0.100" (2.54mm)FeaturesClosed FramePitch - Post0.100" (2.54mm)Contact Finish - Post0.100" (2.54mm)Features0.100" (2.54mm)Contact Finish - Post0.100" (2.54mm)Contact Finish - Post0.100" (2.54mm)Fourt Finish Thickness - Post20µin (5.08µm)Contact Finish Thickness - Post20µin (5.08µm)Housing Material - PostBrass Alloy			
CategoryCanactorial or preserveCategorySockets for ICs, InterconnectsPackage-Series210TypeDIP, 0.3" (7.62mm) Row SpacingNumber of Positions or Pins (Grid)16 (2 x 8)Pitch - Mating0.100" (2.54mm)Contact Finish - MatingGoldContact Material - MatingBeryllium CopperMounting TypeThrough HoleFeaturesClosed FramePitch - Post0.100" (2.54mm)Contact Finish - PostSolderContact Finish - PostSolderContact Finish - PostSolderContact Finish Thickness - Post20µin (5.08µm)Contact Finish Thickness - PostBrass Alloy	Manufacturer Part Number	210-43-316-41-001000	
PackageSockets for ICs, TransistorsPackage-Series210TypeDIP, 0.3" (7.62mm) Row SpacingNumber of Positions or Pins (Grid)16 (2 x 8)Pitch - Mating0.100" (2.54mm)Contact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)Contact Finish Thickness - MatingBeryllium CopperMounting TypeThrough HoleFeaturesClosed FramePitch - Post0.100" (2.54mm)Contact Finish - Post0.100" (2.54mm)Contact Finish - PostSolderContact Finish - Post0.100" (2.54mm)Contact Finish Thickness - Post30µin (0.76µm)Contact Material - PostBrass Alloy	Manufacturer	Mill-Max Manufacturing Corp.	
Package-Series210TypeDIP, 0.3" (7.62mm) Row SpacingNumber of Positions or Pins (Grid)16 (2 x 8)Pitch - Mating0.100" (2.54mm)Contact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)Contact Material - MatingBeryllium CopperMounting TypeThrough HoleFeaturesClosed FramePitch - Post0.100" (2.54mm)Contact Finish - Post50lderContact Finish - Post0.100" (2.54mm)Contact Finish - PostTinContact Finish Thickness - PostSolquin (5.08µm)Contact Finish Thickness - PostSolquin (5.08µm)Contact Finish Thickness - PostBrass Alloy	Category	Connectors, Interconnects	
Series210TypeDIP, 0.3" (7.62mm) Row SpacingNumber of Positions or Pins (Grid)16 (2 x 8)Pitch - Mating0.100" (2.54mm)Contact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)Contact Material - MatingBeryllium CopperMounting TypeThrough HoleFeaturesClosed FrameTerminationSolderPitch - Post0.100" (2.54mm)Contact Finish - PostSolderContact Finish Thickness - PostSiloyin (0.50gm)Contact Finish Thickness - PostSolopin (5.08µm)Contact Material - PostBrass Alloy		Sockets for ICs, Transistors	
TypeDIP, 0.3" (7.62mm) Row SpacingNumber of Positions or Pins (Grid)16 (2 x 8)Pitch - Mating0.100" (2.54mm)Contact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)Contact Material - MatingBeryllium CopperMounting TypeThrough HoleFeaturesClosed FrameTerminationSolderPitch - Post0.100" (2.54mm)Contact Finish - PostSolderContact Finish - PostSoldpin (0.76µm)Contact Finish - PostSolderContact Finish - PostSolupin (5.08µm)Contact Finish Thickness - PostBrass Alloy	Package	-	
Number of Positions or Pins (Grid)16 (2 x 8)Pitch - Mating0.100" (2.54mm)Contact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)Contact Material - MatingBeryllium CopperMounting TypeThrough HoleFeaturesClosed FrameTerminationSolderPitch - Post0.100" (2.54mm)Contact Finish Thickness - PostTinContact Finish Thickness - PostSoloµin (5.08µm)Contact Finish Thickness - PostBrass Alloy	Series	210	
Pitch - Mating0.100" (2.54mm)Contact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)Contact Material - MatingBeryllium CopperMounting TypeThrough HoleFeaturesClosed FrameTerminationSolderPitch - Post0.100" (2.54mm)Contact Finish - PostTinContact Finish Thickness - Post200µin (5.08µm)Contact Material - PostBrass Alloy	Туре	DIP, 0.3" (7.62mm) Row Spacing	
Contact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)Contact Material - MatingBeryllium CopperMounting TypeThrough HoleFeaturesClosed FrameFreminationSolderPitch - Post0.100" (2.54mm)Contact Finish - PostTinContact Finish Thickness - Post20µin (5.08µm)Contact Finish Thickness - PostBrass Alloy	Number of Positions or Pins (Grid)	16 (2 x 8)	
Contact Finish Thickness - Mating30µin (0.76µm)Contact Material - MatingBeryllium CopperMounting TypeThrough HoleFeaturesClosed FrameTerminationSolderPitch - Post0.100" (2.54mm)Contact Finish - PostTinContact Finish Thickness - Post200µin (5.08µm)Contact Finish Thickness - PostBrass Alloy	Pitch - Mating	0.100" (2.54mm)	
Contact Material - MatingBeryllium CopperMounting TypeThrough HoleFeaturesClosed FrameTerminationSolderPitch - Post0.100" (2.54mm)Contact Finish - PostTinContact Finish Thickness - Post200µin (5.08µm)Contact Material - PostBrass Alloy	Contact Finish - Mating	Gold	
Mounting TypeThrough HoleFeaturesClosed FrameTerminationSolderPitch - Post0.100" (2.54mm)Contact Finish - PostTinContact Finish Thickness - Post200µin (5.08µm)Contact Material - PostBrass Alloy	Contact Finish Thickness - Mating	30µin (0.76µm)	
FeaturesClosed FrameTerminationSolderPitch - Post0.100" (2.54mm)Contact Finish - PostTinContact Finish Thickness - Post200µin (5.08µm)Contact Material - PostBrass Alloy	Contact Material - Mating	Beryllium Copper	
TerminationSolderPitch - Post0.100" (2.54mm)Contact Finish - PostTinContact Finish Thickness - Post200µin (5.08µm)Contact Material - PostBrass Alloy	Mounting Type	Through Hole	
Pitch - Post0.100" (2.54mm)Contact Finish - PostTinContact Finish Thickness - Post200µin (5.08µm)Contact Material - PostBrass Alloy	Features	Closed Frame	
Contact Finish - PostTinContact Finish Thickness - Post200µin (5.08µm)Contact Material - PostBrass Alloy	Termination	Solder	
Contact Finish Thickness - Post200µin (5.08µm)Contact Material - PostBrass Alloy	Pitch - Post	0.100" (2.54mm)	
Contact Material - Post Brass Alloy	Contact Finish - Post	Tin	
	Contact Finish Thickness - Post	200µin (5.08µm)	
Housing Material Polycyclohexylenedimethylene Terephthalate (PCT), Polyester	Contact Material - Post	Brass Alloy	
	Housing Material	Polycyclohexylenedimethylene Terephthalate (PCT), Polyester	
Operating Temperature $-55^{\circ}C \sim 125^{\circ}C$	Operating Temperature	-55°C ~ 125°C	
Report errors			Report errors?

#### 210-43-316-41-001000 Guarantees



**Quality Guarantees** 

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

# SERVICE BUARANTEE

#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

## 210-43-316-41-001000 Payment Methods





If you have any question about 210-43-316-41-001000, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com