

210-99-314-41-001000

210-99-314-41-001000 Information

Now.IfeIsener.com	 210-99-314-41-001000 Mill-Max Manufacturing Corp. Connectors, Interconnects Sockets for ICs, Transistors CONN IC DIP SOCKET 14POS TINLEAD - For the pricing/inventory/lead time, please contact	
For Reference Only	Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



210-99-314-41-001000 Specifications

Manufacturer Part Number210-99-314-41-00100Manufacturing Corp.Mill-Max Manufacturing Corp.CategoryConnectors, InterconnectsPackage-Scokets for ICs, TransistorsInterconnectsPackage-Stries210TypeDIP, 0.3" (7.62mm) Row SpacingNumber of Positions or Pins (Grid)14 (2 x 7)Pitch - Mating0.100" (2.54mm)Contact Finish - Mating100µin (2.54µm)Contact Finish - Mating100µin (2.54µm)Contact Material - Mating100µin (2.54µm)Mounting TypeHorogeneFaturesClosed FramePitch - PostSiderContact Finish - PostSiderContact Material - PostSiderContact Materi			
Category Connectors, Interconnects Sockets for ICs, Transistors Package Series 210 Type DIP, 0.3" (7.62mm) Row Spacing Number of Positions or Pins (Grid) 14 (2 x 7) Pitch - Mating Contact Finish - Mating Beryllium Copper Mounting Type Features Closed Frame Formation Solder Termination Ontou" (2.54mm) Contact Finish - Post Contact Finish - Post Contact Finish - Post Contact Finish - Post Contact Finish Thickness - Post Contact Finish Thickness - Post Contact Material - Post Brass Alloy Hous	Manufacturer Part Number	210-99-314-41-001000	
NumberSockets for ICs, TransistorsPackage-Series210TypeDIP, 0.3" (7.62mm) Row SpacingNumber of Positions or Pins (Grid)14 (2 x 7)Pitch - Mating0.100" (2.54mm)Contact Finish - Mating100µin (2.54µm)Contact Finish Thickness - Mating100µin (2.54µm)Contact Material - MatingBeryllium CopperMounting TypeThrough HoleFeaturesClosed FrameTerminationSolderPitch - Post0.100" (2.54mm)Contact Finish Thickness - Post200µin (5.08µm)Contact Finish Thickness - Post200µin (5.08µm)Contact Finish Thickness - PostBrass AlloyHousing MaterialPolycyclohexylenedimethylene Terepthalate (PCT), PolyesterOperating Temperature-5°C ~ 125°C	Manufacturer	Mill-Max Manufacturing Corp.	
Package-Series210TypeDIP,0.3" (7.62mn) Row SpacingNumber of Positions or Pins (Grid)14 (2 x 7)Pitch - Mating0.100" (2.54mn)Contact Finish - Mating100µin (2.54µn)Contact Finish Thickness - Mating100µin (2.54µn)Contact Material - MatingBeryliun CopperMounting TypeThrough HoleFeaturesClosed FrameFeatures0.100" (2.54mn)Contact Finish - Post0.100" (2.54mn)Contact Finish Thickness - Post80µin (5.08µm)Contact Finish Thickness - PostBras AlloyHousing Material - PostPolycyclonexylenedimethylene Terephthalate (PCT), PolyesterPoreating Temperature-55°C ~ 125°C	Category	Connectors, Interconnects	
Series210TypeDIP, 0.3" (7.62mm) Row SpacingNumber of Positions or Pins (Grid)14 (2 x 7)Pitch - Mating0.100" (2.54mm)Contact Finish - MatingTin-LeadContact Finish Thickness - Mating100µin (2.54µm)Contact Material - MatingBeryllium CopperMounting TypeThrough HoleFeaturesClosed FrameTerminationSolderPitch - Post0.100" (2.54µm)Contact Finish Thickness - Post0.100" (2.54µm)Contact Finish - PostSolderPost0.100" (2.54µm)Contact Finish Thickness - Post20µin (5.08µm)Housing Material - PostPolycyclohexylenedimethylene Terephthalate (PCT), PolyesterPogerating Temperature-55°C ~ 125°C		Sockets for ICs, Transistors	
TypeDIP, 0.3" (7.62mm) Row SpacingNumber of Positions or Pins (Grid)14 (2 x 7)Pitch - Mating0.100" (2.54mm)Contact Finish - MatingTin-LeadContact Finish Thickness - Mating100µin (2.54µm)Contact Material - MatingBeryllium CopperMounting TypeThrough HoleFeaturesClosed FrameTerminationSolderPitch - Post0.100" (2.54µm)Contact Finish Thickness - Post0.100" (2.54µm)Contact Finish - PostSolderContact Finish - Post0.100" (2.54µm)Contact Finish Thickness - Post0.100" (2.54µm)Contact Material - PostSolderHousing Material - Post90µin (5.08µm)Fornat Finish Thickness - PostSolopµin (5.08µm)Contact Material - PostBrass AlloyHousing MaterialPolycyclohexylenedimethylene Terephthalate (PCT), PolyesterOperating Temperature-55°C ~ 125°C	Package	-	
Number of Positions or Pins (Grid)14 (2 x 7)Pitch - Mating0.100" (2.54mm)Contact Finish - MatingTin-LeadContact Finish Thickness - Mating100µin (2.54µm)Contact Finish Thickness - MatingBeryllium CopperMounting TypeThrough HoleFeaturesClosed FrameTerminationSolderPitch - Post0.100" (2.54µm)Contact Finish - Post0.100" (2.54µm)Contact Finish - Post0.100" (2.54µm)Contact Finish - Post0.100" (2.54µm)Contact Finish Thickness - Post0.100" (2.54µm)Contact Material - PostBrass AlloyHousing MaterialPolycyclohexylenedimethylene Terephthalate (PCT), PolyesterOperating Temperature-55°C ~ 125°C	Series	210	
Pitch - Mating0.100" (2.54mm)Contact Finish - MatingTin-LeadContact Finish Thickness - Mating100µin (2.54µm)Contact Material - MatingBeryllium CopperMounting TypeThrough HoleFeaturesClosed FrameTerminationSolderPitch - Post0.100" (2.54µm)Contact Finish - Post0.100" (2.54µm)Contact Finish - Post0.100" (2.54µm)Contact Finish - Post0.100" (2.54µm)Contact Finish - Post200µin (5.08µm)Contact Finish Thickness - PostSolderHousing Material - PostPolycyclohexylenedimethylene Terephthalate (PCT), PolyesterPoperating Temperature-55°C ~ 125°C	Туре	DIP, 0.3" (7.62mm) Row Spacing	
Contact Finish - MatingTin-LeadContact Finish Thickness - Mating100µin (2.54µm)Contact Material - MatingBeryllium CopperMounting TypeThrough HoleFeaturesClosed FrameTerminationSolderPitch - Post0.100" (2.54mm)Contact Finish - Post0.100" (2.54mm)Contact Finish - Post200µin (5.08µm)Contact Finish Thickness - PostBrass AlloyHousing Material - PostPolycyclohexylenedimethylene Terephthalate (PCT), PolyesterOperating Temperature.55°C ~ 125°C	Number of Positions or Pins (Grid)	14 (2 x 7)	
Contact Finish Thickness - Mating100µin (2.54µm)Contact Material - MatingBeryllium CopperMounting TypeThrough HoleFeaturesClosed FrameTerminationSolderPitch - Post0.100" (2.54mm)Contact Finish - PostTin-LeadContact Finish Thickness - Post200µin (5.08µm)Contact Material - PostBrass AlloyHousing MaterialPolycyclohexylenedimethylene Terephthalate (PCT), PolyesterOperating Temperature-55°C ~ 125°C	Pitch - Mating	0.100" (2.54mm)	
Contact Material - MatingBeryllium CopperMounting TypeThrough HoleFeaturesClosed FrameTerminationSolderPitch - Post0.100" (2.54mm)Contact Finish - PostTin-LeadContact Finish Thickness - Post200µin (5.08µm)Contact Material - PostBrass AlloyHousing MaterialPolycyclohexylenedimethylene Terephthalate (PCT), PolyesterOperating Temperature-55°C ~ 125°C	Contact Finish - Mating	Tin-Lead	
Mounting TypeThrough HoleFeaturesClosed FrameTerminationSolderPitch - Post0.100" (2.54mm)Contact Finish - PostTin-LeadContact Finish Thickness - Post200µin (5.08µm)Contact Material - PostBrass AlloyHousing MaterialPolycyclohexylenedimethylene Terephthalate (PCT), PolyesterOperating Temperature-55°C ~ 125°C	Contact Finish Thickness - Mating	100µin (2.54µm)	
FeaturesClosed FrameTerminationSolderPitch - Post0.100" (2.54mm)Contact Finish - PostTin-LeadContact Finish Thickness - Post200µin (5.08µm)Contact Material - PostBrass AlloyHousing MaterialPolycyclohexylenedimethylene Terephthalate (PCT), PolyesterOperating Temperature-55°C ~ 125°C	Contact Material - Mating	Beryllium Copper	
TerminationSolderPitch - Post0.100" (2.54mm)Contact Finish - PostTin-LeadContact Finish Thickness - Post200µin (5.08µm)Contact Material - PostBrass AlloyHousing MaterialPolycyclohexylenedimethylene Terephthalate (PCT), PolyesterOperating Temperature-55°C ~ 125°C	Mounting Type	Through Hole	
Pitch - Post0.100" (2.54mm)Contact Finish - PostTin-LeadContact Finish Thickness - Post200µin (5.08µm)Contact Material - PostBrass AlloyHousing MaterialPolycyclohexylenedimethylene Terephthalate (PCT), PolyesterOperating Temperature-55°C ~ 125°C	Features	Closed Frame	
Contact Finish - PostTin-LeadContact Finish Thickness - Post200µin (5.08µm)Contact Material - PostBrass AlloyHousing MaterialPolycyclohexylenedimethylene Terephthalate (PCT), PolyesterOperating Temperature-55°C ~ 125°C	Termination	Solder	
Contact Finish Thickness - Post200µin (5.08µm)Contact Material - PostBrass AlloyHousing MaterialPolycyclohexylenedimethylene Terephthalate (PCT), PolyesterOperating Temperature-55°C ~ 125°C	Pitch - Post	0.100" (2.54mm)	
Contact Material - PostBrass AlloyHousing MaterialPolycyclohexylenedimethylene Terephthalate (PCT), PolyesterOperating Temperature-55°C ~ 125°C	Contact Finish - Post	Tin-Lead	
Housing MaterialPolycyclohexylenedimethylene Terephthalate (PCT), PolyesterOperating Temperature-55°C ~ 125°C	Contact Finish Thickness - Post	200µin (5.08µm)	
Operating Temperature $-55^{\circ}\text{C} \sim 125^{\circ}\text{C}$	Contact Material - Post	Brass Alloy	
	Housing Material	Polycyclohexylenedimethylene Terephthalate (PCT), Polyester	
Report errors	Operating Temperature	-55°C ~ 125°C	
Report chois			Report errors?

210-99-314-41-001000 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

210-99-314-41-001000 Payment Methods





If you have any question about 210-99-314-41-001000, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com