

### 21033814804 Information



For Reference Only

**Part Number** 21033814804 **Manufacturer** HARTING

Category Connectors, Interconnects Circular Connectors

**Description** CONN RCPT 8POS PNL MT T/H RA SKT

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## 21033814804 Specifications

Manufacturer Part Number21033814804ManufacturerHARTINGCategoryConnectors, InterconnectsPackage-SeriesHar-Speed M12Connector TypeReceptacle, Female SocketsNumber of Positions8Shell Size - InsertM12-8Shell Size, MIL-Mounting TypePanel Mount, Bulkhead; Through Hole, Right AngleTerminationSolderFastening TypeThreadedOrientationXIngress ProtectionIP65/67 - Dust Tight, Water Resistant, WaterproofShell Material, Finish-Contact Finish-FeaturesShieldedVoltage - Rated50VCurrent Rating4AReport errors?		
Category Circular Connectors  Package - Series Har-Speed M12 Connector Type Receptacle, Female Sockets Number of Positions 8 Shell Size - Insert M12-8 Shell Size, MIL - Mounting Type Panel Mount, Bulkhead; Through Hole, Right Angle Termination Solder Fastening Type Threaded Orientation X Ingress Protection Shell Material, Finish - Contact Finish - Features Shielded Voltage - Rated Current Rating  Connectors, Interconnects Circular Connectors  - Connectors Interconnectors  - Connectors  - Connectors Interconnectors  - Connectors Interconnectors  - Connectors Interconnectors  - Connectors Interconnectors  - Connectors  - Connectors Interconnectors  - Connectors  - Connectors Interconnectors  - Connectors  - Connectors	Manufacturer Part Number	21033814804
Circular Connectors  Package - Series Har-Speed M12 Connector Type Receptacle, Female Sockets  Number of Positions 8 Shell Size - Insert M12-8 Shell Size, MIL - Mounting Type Panel Mount, Bulkhead; Through Hole, Right Angle Termination Solder Fastening Type Threaded Orientation X Ingress Protection IP65/67 - Dust Tight, Water Resistant, Waterproof Shell Material, Finish - Contact Finish - Features Shielded Voltage - Rated 50V Current Rating 4A	Manufacturer	HARTING
Package-SeriesHar-Speed M12Connector TypeReceptacle, Female SocketsNumber of Positions8Shell Size - InsertM12-8Shell Size, MIL-Mounting TypePanel Mount, Bulkhead; Through Hole, Right AngleTerminationSolderFastening TypeThreadedOrientationXIngress ProtectionIP65/67 - Dust Tight, Water Resistant, WaterproofShell Material, Finish-Contact Finish-FeaturesShieldedVoltage - Rated50VCurrent Rating4A	Category	Connectors, Interconnects
SeriesHar-Speed M12Connector TypeReceptacle, Female SocketsNumber of Positions8Shell Size - InsertM12-8Shell Size, MIL-Mounting TypePanel Mount, Bulkhead; Through Hole, Right AngleTerminationSolderFastening TypeThreadedOrientationXIngress ProtectionIP65/67 - Dust Tight, Water Resistant, WaterproofShell Material, Finish-Contact Finish-FeaturesShieldedVoltage - Rated50VCurrent Rating4A		Circular Connectors
Connector TypeReceptacle, Female SocketsNumber of Positions8Shell Size - InsertM12-8Shell Size, MIL-Mounting TypePanel Mount, Bulkhead; Through Hole, Right AngleTerminationSolderFastening TypeThreadedOrientationXIngress ProtectionIP65/67 - Dust Tight, Water Resistant, WaterproofShell Material, Finish-Contact Finish-FeaturesShieldedVoltage - Rated50VCurrent Rating4A	Package	-
Number of Positions8Shell Size - InsertM12-8Shell Size, MIL-Mounting TypePanel Mount, Bulkhead; Through Hole, Right AngleTerminationSolderFastening TypeThreadedOrientationXIngress ProtectionIP65/67 - Dust Tight, Water Resistant, WaterproofShell Material, Finish-Contact Finish-FeaturesShieldedVoltage - Rated50VCurrent Rating4A	Series	Har-Speed M12
Shell Size - Insert  Shell Size, MIL  Mounting Type  Panel Mount, Bulkhead; Through Hole, Right Angle  Termination  Solder  Fastening Type  Threaded  Orientation  X  Ingress Protection  IP65/67 - Dust Tight, Water Resistant, Waterproof  Shell Material, Finish  - Contact Finish  - Features  Shielded  Voltage - Rated  50V  Current Rating  4A	Connector Type	Receptacle, Female Sockets
Shell Size, MIL  Mounting Type Panel Mount, Bulkhead; Through Hole, Right Angle Termination Solder Fastening Type Threaded Orientation X Ingress Protection IP65/67 - Dust Tight, Water Resistant, Waterproof Shell Material, Finish - Contact Finish - Features Shielded Voltage - Rated Current Rating 4A	Number of Positions	8
Mounting TypePanel Mount, Bulkhead; Through Hole, Right AngleTerminationSolderFastening TypeThreadedOrientationXIngress ProtectionIP65/67 - Dust Tight, Water Resistant, WaterproofShell Material, Finish-Contact Finish-FeaturesShieldedVoltage - Rated50VCurrent Rating4A	Shell Size - Insert	M12-8
Termination Solder Fastening Type Threaded Orientation X Ingress Protection IP65/67 - Dust Tight, Water Resistant, Waterproof Shell Material, Finish - Contact Finish - Features Shielded Voltage - Rated 50V Current Rating 4A	Shell Size, MIL	-
Fastening Type Orientation X Ingress Protection IP65/67 - Dust Tight, Water Resistant, Waterproof Shell Material, Finish - Contact Finish - Features Shielded Voltage - Rated Current Rating 4A	Mounting Type	Panel Mount, Bulkhead; Through Hole, Right Angle
Orientation X Ingress Protection IP65/67 - Dust Tight, Water Resistant, Waterproof Shell Material, Finish - Contact Finish - Features Shielded Voltage - Rated 50V Current Rating 4A	Termination	Solder
Ingress Protection  IP65/67 - Dust Tight, Water Resistant, Waterproof  Shell Material, Finish  Contact Finish  Features  Shielded  Voltage - Rated  Current Rating  4A	Fastening Type	Threaded
Shell Material, Finish  Contact Finish  Features  Shielded  Voltage - Rated  Current Rating  4A	Orientation	X
Contact Finish - Features Shielded  Voltage - Rated 50V  Current Rating 4A	Ingress Protection	IP65/67 - Dust Tight, Water Resistant, Waterproof
Features Shielded  Voltage - Rated 50V  Current Rating 4A	Shell Material, Finish	-
Voltage - Rated 50V Current Rating 4A	Contact Finish	-
Current Rating 4A	Features	Shielded
	Voltage - Rated	50V
Report errors?	Current Rating	4A
		Report errors?

#### **21033814804 Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### 21033814804 Payment Methods



















### 21033814804 Shipping Methods













If you have any question about 21033814804, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com