

### **2106135-2 Information**



For Reference Only

**Part Number** 2106135-2

Manufacturer TE Connectivity AMP Connectors

Category Connectors, Interconnects

Solid State Lighting Connectors

**Description** CONN SSL PLUG HSG 2POS 3.5MM

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# 2106135-2 Specifications

Manufacturer Part Number     2106135-2       Manufacturer     TE Connectivity AMP Connectors       Category     Connectors, Interconnects       Package     -       Series     SlimSeal       Style     Cable/Wire to Cable/Wire or Board       Connector Type     Plug Housing for Socket Contact       Number of Positions     2       Mounting Type     Free Hanging (In-Line)       Termination     Crimp       Pitch     0.138" (3.50mm)       Fastening Type     Latch Lock       Features     -       Housing Color     Black       Wire Gauge     -       Contact Material     -       Contact Finish     -       Housing Material     Polycarbonate (PC)       Operating Temperature     -40°C ~ 105°C		
Category Connectors, Interconnects Solid State Lighting Connectors  Package - Series SlimSeal Style Cable/Wire to Cable/Wire or Board Connector Type Plug Housing for Socket Contact Number of Positions 2 Mounting Type Free Hanging (In-Line) Crimp Pitch Connector Type Latch Lock Features - Housing Color Black Wire Gauge Contact Material Contact Finish Housing Material Polycarbonate (PC) Operating Temperature  Connector SlimSeal SlimSeal Cable/Wire or Board Contact Finish - Housing Material Polycarbonate (PC) -40°C ~ 105°C	Manufacturer Part Number	2106135-2
Solid State Lighting Connectors  Package  Series  SlimSeal  Style  Cable/Wire to Cable/Wire or Board  Connector Type  Plug Housing for Socket Contact  Number of Positions  2  Mounting Type  Free Hanging (In-Line)  Termination  Crimp  Pitch  0.138" (3.50mm)  Fastening Type  Latch Lock  Features  - Housing Color  Black  Wire Gauge  - Contact Material  Contact Finish  - Housing Material  Polycarbonate (PC)  Operating Temperature	Manufacturer	TE Connectivity AMP Connectors
Package - Stines SlimSeal  Style Cable/Wire to Cable/Wire or Board  Connector Type Plug Housing for Socket Contact  Number of Positions 2  Mounting Type Free Hanging (In-Line)  Termination Crimp  Pitch 0.138" (3.50mm)  Fastening Type Latch Lock  Features - Housing Color Black  Wire Gauge - Contact Material - Contact Material - Contact Finish - Housing Material Polycarbonate (PC)  Operating Temperature - 40°C ~ 105°C	Category	Connectors, Interconnects
Series SlimSeal  Style Cable/Wire to Cable/Wire or Board  Connector Type Plug Housing for Socket Contact  Number of Positions 2  Mounting Type Free Hanging (In-Line)  Termination Crimp  Pitch 0.138" (3.50mm)  Fastening Type Latch Lock  Features  Housing Color Black  Wire Gauge  Contact Material  Contact Finish  Housing Material Polycarbonate (PC)  Operating Temperature		Solid State Lighting Connectors
StyleCable/Wire to Cable/Wire or BoardConnector TypePlug Housing for Socket ContactNumber of Positions2Mounting TypeFree Hanging (In-Line)TerminationCrimpPitch0.138" (3.50mm)Fastening TypeLatch LockFeatures-Housing ColorBlackWire Gauge-Contact Material-Contact Finish-Housing MaterialPolycarbonate (PC)Operating Temperature-40°C ~ 105°C	Package	-
Connector Type Plug Housing for Socket Contact  Number of Positions 2  Mounting Type Free Hanging (In-Line)  Termination Crimp  Pitch 0.138" (3.50mm)  Fastening Type Latch Lock  Features -  Housing Color Black  Wire Gauge -  Contact Material -  Contact Finish -  Housing Material Polycarbonate (PC)  Operating Temperature -40°C ~ 105°C	Series	SlimSeal
Number of Positions2Mounting TypeFree Hanging (In-Line)TerminationCrimpPitch0.138" (3.50mm)Fastening TypeLatch LockFeatures-Housing ColorBlackWire Gauge-Contact Material-Contact Finish-Housing MaterialPolycarbonate (PC)Operating Temperature-40°C ~ 105°C	Style	Cable/Wire to Cable/Wire or Board
Mounting TypeFree Hanging (In-Line)TerminationCrimpPitch0.138" (3.50mm)Fastening TypeLatch LockFeatures-Housing ColorBlackWire Gauge-Contact Material-Contact Finish-Housing MaterialPolycarbonate (PC)Operating Temperature-40°C ~ 105°C	Connector Type	Plug Housing for Socket Contact
Termination Crimp  Pitch 0.138" (3.50mm)  Fastening Type Latch Lock  Features - Housing Color Black  Wire Gauge - Contact Material - Contact Finish - Housing Material Polycarbonate (PC) Operating Temperature -40°C ~ 105°C	Number of Positions	2
Pitch 0.138" (3.50mm)  Fastening Type Latch Lock  Features - Housing Color Black  Wire Gauge - Contact Material - Contact Finish - Housing Material Polycarbonate (PC) Operating Temperature -40°C ~ 105°C	Mounting Type	Free Hanging (In-Line)
Fastening Type Latch Lock  Features - Housing Color Black Wire Gauge - Contact Material - Contact Finish - Housing Material Polycarbonate (PC) Operating Temperature  Latch Lock -  Polycarbonate -  Latch Lock  Polycarbonate -  Housing Color  Black -  Polycarbonate -  Polycarbonate -  -  -  -  -  -  -  -  -  -  -  -  -	Termination	Crimp
Features - Housing Color Black Wire Gauge - Contact Material - Contact Finish - Housing Material Polycarbonate (PC) Operating Temperature -40°C ~ 105°C	Pitch	0.138" (3.50mm)
Housing Color  Wire Gauge  Contact Material  Contact Finish  Housing Material  Polycarbonate (PC)  Operating Temperature  Black	Fastening Type	Latch Lock
Wire Gauge - Contact Material - Contact Finish - Housing Material Polycarbonate (PC) Operating Temperature -40°C ~ 105°C	Features	-
Contact Material Contact Finish Housing Material Polycarbonate (PC) Operating Temperature -40°C $\sim$ 105°C	Housing Color	Black
Contact Finish Housing Material Polycarbonate (PC) Operating Temperature $-40^{\circ}\text{C} \sim 105^{\circ}\text{C}$	Wire Gauge	-
Housing Material Polycarbonate (PC) Operating Temperature $-40^{\circ}\text{C} \sim 105^{\circ}\text{C}$	Contact Material	-
Operating Temperature $-40^{\circ}\text{C} \sim 105^{\circ}\text{C}$	Contact Finish	-
	Housing Material	Polycarbonate (PC)
Report errors?	Operating Temperature	-40°C ~ 105°C
		Report errors?

### **2106135-2 Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## 2106135-2 Payment Methods





















## 2106135-2 Shipping Methods













If you have any question about 2106135-2, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com