

# 214-99-640-01-670800

#### 214-99-640-01-670800 Information

antitive helsener town	 214-99-640-01-670800 Mill-Max Manufacturing Corp. Connectors, Interconnects Sockets for ICs, Transistors CONN IC DIP SOCKET 40POS TINLEAD - For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

### **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



## 214-99-640-01-670800 Specifications

Manufacturer Mill-Max Manufacturing Corp.   Connectors, Interconnects Sockets for ICs, Transistors   Package -   Series 214   Type DIP, 0.6" (15.24mm) Row Spacing   Number of Positions or Pins (Grid) 40 (2 x 20)   Pitch - Mating 0.100" (2.54mm) Row Spacing   Contact Finish - Mating 100µin (2.54µm)   Contact Finish Thickness - Mating 100µin (2.54µm)   Contact Material - Mating Beryllium Copper   Mounting Type Surface Mount   Features Closed Frame   Pitch - Post 0.100" (2.54µm)   Contact Finish Thickness - Post 0.100" (2.54µm)   Contact Finish - Post 0.100" (2.54µm)   Contact Material - Mating Beryllium Copper   Pitch - Post 0.100" (2.54µm)   Contact Finish Thickness - Post 0.100" (2.54µm)   Contact Finish Thickness - Post 0.100" (2.54µm)   Contact Finish Thickness - Post<			
CategoryConnectors, Interconnects Sockets for ICs, TransistorsPackage-Series214TypeDIP, 0.6" (15.24mm) Row SpacingNumber of Positions or Pins (Grid)40 (2 x 20)Pitch - Mating0.100" (2.54mm)Contact Finish - Mating100µin (2.54µm)Contact Finish - MatingBeryllium CopperContact Finish Thickness - MatingBeryllium CopperContact Finish Thickness - MatingSurface MountContact Finish - MatingSurface MountContact Finish - MatingSurface MountContact Finish - MatingSurface MountContact Thirsh - MatingSurface MountContact Material - MatingSolderContact Material - MatingSolderContact Finish - PostClosed FrameContact Finish - PostSolderContact Finish - PostSolderContact Finish Thickness - Post200µin (5.08µm)Contact Material - PostBrass AlloyHousing MaterialPolycyclohexylenedimethylene Terephthalate (PCT), PolyesterOperating Temperature-55°C ~ 125°C	Manufacturer Part Number	214-99-640-01-670800	
Sockets for ICs, TransistorsPackage-Series214TypeDIP, 0.6" (15.24mm) Row SpacingNumber of Positions or Pins (Grid)40 (2 x 20)Pitch - Mating0.100" (2.54mm)Contact Finish - Mating100µin (2.54µm)Contact Finish Thickness - Mating100µin (2.54µm)Contact Finish Thickness - MatingBeryllium CopperMounting TypeSurface MountFeaturesClosed FramePitch - Post0.100" (2.54mm)Contact Finish - PostTin-LeadContact Finish - Post50lderContact Finish Thickness - Post200µin (5.08µm)Contact Finish Thickness - Post200µin (5.08µm)Contact Material - PostBrass AlloyHousing MaterialPolycyclohexylenedimethylene Terephthalate (PCT), PolyesterOperating Temperature-55°C ~ 125°C	Manufacturer	Mill-Max Manufacturing Corp.	
Package-Series214TypeDIP, 0.6" (15.24mm) Row SpacingNumber of Positions or Pins (Grid)40 (2 x 20)Pitch - Mating0.100" (2.54mm)Contact Finish - MatingTin-LeadContact Finish Thickness - Mating100µin (2.54µm)Contact Material - MatingBeryllium CopperMounting TypeSurface MountFeaturesClosed FramePitch - Post0.100" (2.54mm)Contact Finish Thickness - PostSolderContact Finish - Post0.100" (2.54mm)Contact Finish Thickness - Post200µin (5.08µm)Contact Finish Thickness - PostBrass AlloyContact Material - PostPolycyclohexylenedimethylene Terephthalate (PCT), PolyesterOperating Temperature-55°C ~ 125°C	Category	Connectors, Interconnects	
Series 214   Type DIP, 0.6" (15.24mm) Row Spacing   Number of Positions or Pins (Grid) 40 (2 x 20)   Pitch - Mating 0.100" (2.54mm)   Contact Finish - Mating Tin-Lead   Contact Finish Thickness - Mating 100µin (2.54µm)   Contact Finish Thickness - Mating Beryllium Copper   Contact Material - Mating Beryllium Copper   Mounting Type Surface Mount   Features Closed Frame   Pitch - Post 0.100" (2.54mm)   Contact Finish Thickness - Post Solder   Contact Finish - Post Onton" (2.54mm)   Contact Finish - Post Solder   Contact Finish Thickness - Post Solder   Contact Finish Thickness - Post 200µin (5.08µm)   Contact Material - Post Brass Alloy   Housing Material Polycyclonexylenedimethylene Terephthalate (PCT), Polyester   Operating Temperature -55°C ~ 125°C		Sockets for ICs, Transistors	
Type DIP, 0.6" (15.24mm) Row Spacing   Number of Positions or Pins (Grid) 40 (2 x 20)   Pitch - Mating 0.100" (2.54mm)   Contact Finish - Mating Tin-Lead   Contact Finish Thickness - Mating 100µin (2.54µm)   Contact Material - Mating Beryllium Copper   Mounting Type Beryllium Copper   Features Closed Frame   Premination Solder   Pitch - Post 0.100" (2.54µm)   Contact Finish Thickness - Post Solder   Contact Finish - Post 0.100" (2.54µm)   Contact Finish - Post 0.100" (2.54µm)   Contact Finish Thickness - Post Solder   Contact Finish Thickness - Post 200µin (5.08µm)   Contact Material - Post Brass Alloy   Housing Material Polycyclohexylenedimethylene Terephthalate (PCT), Polyester   Operating Temperature -55°C ~ 125°C	Package	-	
Number of Positions or Pins (Grid) $40 (2 \times 20)$ Pitch - Mating $0.100" (2.54mm)$ Contact Finish - MatingTin-LeadContact Finish Thickness - Mating $100\mu$ in $(2.54\mu m)$ Contact Material - MatingBeryllium CopperMounting TypeSurface MountFeaturesClosed FrameTerminationSolderPitch - Post $0.100" (2.54mm)$ Contact Finish Thickness - Post $0.100" (2.54mm)$ Contact Finish - PostTin-LeadContact Finish - Post $0.100" (2.54mm)$ Contact Material - Post $0.100" (2.54mm)$ Contact Finish - Post $0.100" (2.54mm)$ Contact Finish Thickness - Post $0.100" (2.54mm)$ Contact Finish - Post $0.100" (2.54mm)$ Contact Finish - Post $0.100" (2.54mm)$ Contact Finish - Post $0.100" (2.54mm)$ Contact Material - Post $0.100" (2.54mm)$ Contact Finish Thickness - Post $0.00\mu in (5.08\mum)$ Contact Material - PostBrass AlloyHousing MaterialPolycyclohexylenedimethylene Terephthalate (PCT), PolyesterOperating Temperature $-55°C ~ 125°C$	Series	214	
Pitch - Mating0.100" (2.54mm)Contact Finish - MatingTin-LeadContact Finish Thickness - Mating100µin (2.54µm)Contact Material - MatingBeryllium CopperMounting TypeSurface MountFeaturesClosed FrameTerminationSolderPitch - Post0.100" (2.54mm)Contact Finish - Post0.100" (2.54mm)Contact Finish - Post200µin (5.08µm)Contact Material - PostBrass AlloyHousing MaterialPolycyclohexylenedimethylene Terephthalate (PCT), PolyesterOperating Temperature-55°C ~ 125°C	Туре	DIP, 0.6" (15.24mm) Row Spacing	
Contact Finish - MatingTin-LeadContact Finish Thickness - Mating100µin (2.54µm)Contact Material - MatingBeryllium CopperMounting TypeSurface MountFeaturesClosed FrameTerminationSolderPitch - Post0.100" (2.54µm)Contact Finish - PostTin-LeadContact Finish - Post200µin (5.08µm)Contact Finish Thickness - PostBrass AlloyHousing Material - PostPolycyclohexylenedimethylene Terephthalate (PCT), PolyesterOperating Temperature-55°C ~ 125°C	Number of Positions or Pins (Grid)	40 (2 x 20)	
Contact Finish Thickness - Mating100µin (2.54µm)Contact Material - MatingBeryllium CopperMounting TypeSurface MountFeaturesClosed FrameTerminationSolderPitch - Post0.100" (2.54mm)Contact Finish - PostTin-LeadContact Finish Thickness - Post200µin (5.08µm)Contact Finish Thickness - PostBrass AlloyHousing Material - PostPolycyclohexylenedimethylene Terephthalate (PCT), PolyesterOperating Temperature-55°C ~ 125°C	Pitch - Mating	0.100" (2.54mm)	
Contact Material - MatingBeryllium CopperMounting TypeSurface MountMounting TypeClosed FrameFeaturesClosed FrameTerminationSolderPitch - Post0.100" (2.54mm)Contact Finish - PostTin-LeadContact Finish Thickness - Post200µin (5.08µm)Contact Material - PostBrass AlloyHousing MaterialPolycyclohexylenedimethylene Terephthalate (PCT), PolyesterOperating Temperature-55°C ~ 125°C	Contact Finish - Mating	Tin-Lead	
Mounting TypeSurface MountFeaturesClosed FrameTerminationSolderPitch - Post0.100" (2.54mm)Contact Finish - PostTin-LeadContact Finish Thickness - Post200µin (5.08µm)Contact Finish Thickness - PostBrass AlloyHousing MaterialPolycyclohexylenedimethylene Terephthalate (PCT), PolyesterOperating Temperature-55°C ~ 125°C	Contact Finish Thickness - Mating	100µin (2.54µm)	
FeaturesClosed FrameFerminationSolderPitch - Post0.100" (2.54mm)Contact Finish - PostTin-LeadContact Finish Thickness - Post200µin (5.08µm)Contact Material - PostBrass AlloyHousing MaterialPolycyclohexylenedimethylene Terephthalate (PCT), PolyesterOperating Temperature-55°C ~ 125°C	Contact Material - Mating	Beryllium Copper	
TerminationSolderPitch - Post0.100" (2.54mm)Contact Finish - PostTin-LeadContact Finish Thickness - Post200µin (5.08µm)Contact Material - PostBrass AlloyHousing MaterialPolycyclohexylenedimethylene Terephthalate (PCT), PolyesterOperating Temperature-55°C ~ 125°C	Mounting Type	Surface Mount	
Pitch - Post0.100" (2.54mm)Contact Finish - PostTin-LeadContact Finish Thickness - Post200µin (5.08µm)Contact Material - PostBrass AlloyHousing MaterialPolycyclohexylenedimethylene Terephthalate (PCT), PolyesterOperating Temperature-55°C ~ 125°C	Features	Closed Frame	
Contact Finish - PostTin-LeadContact Finish Thickness - Post200µin (5.08µm)Contact Material - PostBrass AlloyHousing MaterialPolycyclohexylenedimethylene Terephthalate (PCT), PolyesterOperating Temperature-55°C ~ 125°C	Termination	Solder	
Contact Finish Thickness - Post200µin (5.08µm)Contact Material - PostBrass AlloyHousing MaterialPolycyclohexylenedimethylene Terephthalate (PCT), PolyesterOperating Temperature-55°C ~ 125°C	Pitch - Post	0.100" (2.54mm)	
Contact Material - PostBrass AlloyHousing MaterialPolycyclohexylenedimethylene Terephthalate (PCT), PolyesterOperating Temperature-55°C ~ 125°C	Contact Finish - Post	Tin-Lead	
Housing MaterialPolycyclohexylenedimethylene Terephthalate (PCT), PolyesterOperating Temperature-55°C ~ 125°C	Contact Finish Thickness - Post	200µin (5.08µm)	
Operating Temperature $-55^{\circ}C \sim 125^{\circ}C$	Contact Material - Post	Brass Alloy	
	Housing Material	Polycyclohexylenedimethylene Terephthalate (PCT), Polyester	
Report errors <sup>2</sup>	Operating Temperature	-55°C ~ 125°C	
			Report errors?

#### 214-99-640-01-670800 Guarantees



**Quality Guarantees** 

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

# SERVICE BUARANTEE

#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

#### 214-99-640-01-670800 Payment Methods





If you have any question about 214-99-640-01-670800, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com