

2204-12-311 Information



For Reference Only

Part Number 2204-12-311
Manufacturer Coto Technology

Category Relays

Signal Relays, Up to 2 Amps

Description RELAY REED SPST 500MA 12V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









2204-12-311 Specifications

Manufacturer Part Number 2204-12-311 Manufacturer Coto Technology Category Relays Signal Relays, Up to 2 Amps Package - Series 2200 Relay Type Reed Coil Type Non Latching Coil Current 8mA Coil Voltage 12VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 500mA Switching Voltage 200VAC, 200VDC - Max Turn On Voltage (Max) 9 VDC Turn Off Voltage (Min) 1 VDC Operate Time 0.5ms Release Time 0.1ms Features Sealed - Hermetically Mounting Type Through Hole Termination Style PC Pin		
CategoryRelaysPackage-Series2200Relay TypeReedCoil TypeNon LatchingCoil Current8mACoil Voltage12VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)500mASwitching Voltage200VAC, 200VDC - MaxTurn On Voltage (Max)9 VDCTurn Off Voltage (Min)1 VDCOperate Time0.5msRelease Time0.1msFeaturesSealed - HermeticallyMounting TypeThrough HoleTermination StylePC Pin	Manufacturer Part Number	2204-12-311
Package - Series 2200 Relay Type Reed Coil Type Non Latching Coil Current 8mA Coil Voltage 12VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 500mA Switching Voltage 200VAC, 200VDC - Max Turn On Voltage (Max) 9 VDC Turn Off Voltage (Min) 1 VDC Operate Time 0.5ms Release Time 0.1ms Features Sealed - Hermetically Mounting Type Through Hole Termination Style PC Pin	Manufacturer	Coto Technology
Package - Series 2200 Relay Type Reed Coil Type Non Latching Coil Current 8mA Coil Voltage 12VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 500mA Switching Voltage 200VAC, 200VDC - Max Turn On Voltage (Max) 9 VDC Turn Off Voltage (Min) 1 VDC Operate Time 0.5ms Release Time 0.1ms Features Sealed - Hermetically Mounting Type Through Hole Termination Style PC Pin	Category	Relays
Series 2200 Relay Type Reed Coil Type Non Latching Coil Current 8mA Coil Voltage 12VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 500mA Switching Voltage 200VAC, 200VDC - Max Turn On Voltage (Max) 9 VDC Turn Off Voltage (Min) 1 VDC Operate Time 0.5ms Release Time 0.1ms Features Sealed - Hermetically Mounting Type Through Hole Termination Style PC Pin		Signal Relays, Up to 2 Amps
Relay TypeReedCoil TypeNon LatchingCoil Current8mACoil Voltage12VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)500mASwitching Voltage200VAC, 200VDC - MaxTurn On Voltage (Max)9 VDCTurn Off Voltage (Min)1 VDCOperate Time0.5msRelease Time0.1msFeaturesSealed - HermeticallyMounting TypeThrough HoleTermination StylePC Pin	Package	-
Coil TypeNon LatchingCoil Current8mACoil Voltage12VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)500mASwitching Voltage200VAC, 200VDC - MaxTurn On Voltage (Max)9 VDCTurn Off Voltage (Min)1 VDCOperate Time0.5msRelease Time0.1msFeaturesSealed - HermeticallyMounting TypeThrough HoleTermination StylePC Pin	Series	2200
Coil Current Coil Voltage 12VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 500mA Switching Voltage 200VAC, 200VDC - Max Turn On Voltage (Max) 9 VDC Turn Off Voltage (Min) 1 VDC Operate Time 0.5ms Release Time 0.1ms Features Sealed - Hermetically Mounting Type Through Hole Termination Style PC Pin	Relay Type	Reed
Coil Voltage 12VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 500mA Switching Voltage 200VAC, 200VDC - Max Turn On Voltage (Max) 9 VDC Turn Off Voltage (Min) 1 VDC Operate Time 0.5ms Release Time 0.1ms Features Sealed - Hermetically Mounting Type Through Hole Termination Style PC Pin	Coil Type	Non Latching
Contact Form SPST-NO (1 Form A) Contact Rating (Current) 500mA Switching Voltage 200VAC, 200VDC - Max Turn On Voltage (Max) 9 VDC Turn Off Voltage (Min) 1 VDC Operate Time 0.5ms Release Time 0.1ms Features Sealed - Hermetically Mounting Type Through Hole Termination Style PC Pin	Coil Current	8mA
Contact Rating (Current) Switching Voltage 200VAC, 200VDC - Max Turn On Voltage (Max) 9 VDC Turn Off Voltage (Min) 1 VDC Operate Time 0.5ms Release Time 0.1ms Features Sealed - Hermetically Mounting Type Through Hole Termination Style 500mA 500	Coil Voltage	12VDC
Switching Voltage 200VAC, 200VDC - Max Turn On Voltage (Max) 9 VDC Turn Off Voltage (Min) 1 VDC Operate Time 0.5ms Release Time 0.1ms Features Sealed - Hermetically Mounting Type Through Hole Termination Style PC Pin	Contact Form	SPST-NO (1 Form A)
Turn On Voltage (Max) 7 Turn Off Voltage (Min) 9 VDC 1 VDC Operate Time 0.5ms Release Time 0.1ms Features Sealed - Hermetically Mounting Type Through Hole Termination Style PC Pin	Contact Rating (Current)	500mA
Turn Off Voltage (Min) Operate Time 0.5ms Release Time 0.1ms Features Sealed - Hermetically Mounting Type Through Hole Termination Style PC Pin	Switching Voltage	200VAC, 200VDC - Max
Operate Time0.5msRelease Time0.1msFeaturesSealed - HermeticallyMounting TypeThrough HoleTermination StylePC Pin	Turn On Voltage (Max)	9 VDC
Release Time 0.1ms Features Sealed - Hermetically Mounting Type Through Hole Termination Style PC Pin	Turn Off Voltage (Min)	1 VDC
Features Sealed - Hermetically Mounting Type Through Hole Termination Style PC Pin	Operate Time	0.5ms
Mounting Type Through Hole Termination Style PC Pin	Release Time	0.1ms
Termination Style PC Pin	Features	Sealed - Hermetically
	Mounting Type	Through Hole
Report errors?	Termination Style	PC Pin
		Report errors?

2204-12-311 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

2204-12-311 Payment Methods



















2204-12-311 Shipping Methods













If you have any question about 2204-12-311, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com