

2213393-2 Information

Heisener.com

Part Number 2213393-2

Manufacturer TE Connectivity AMP Connectors

Category Connectors, Interconnects

Solid State Lighting Connectors

Description PIN HOUSING, PANEL, 6P, B CODE

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









2213393-2 Specifications

Manufacturer Part Number 2213393-2 Manufacturer TE Connectivity AMP Connectors Category Connectors, Interconnects Solid State Lighting Connectors Package - Series Nector M Style Cable/Wire to Cable/Wire Connector Type Receptacle Housing for Pin Contact Number of Positions 6 Mounting Type Panel Mount Termination Crimp Pitch - Fastening Type - Features Keyed Housing Color Black Wire Gauge - Contact Material - Contact Finish - Housing Material Polybutylene Terephthalate (PBT), Glass Filled Operating Temperature -40°C ~ 85°C		
Category Connectors, Interconnects Solid State Lighting Connectors Package - Series Nector M Style Cable/Wire to Cable/Wire Connector Type Receptacle Housing for Pin Contact Number of Positions 6 Mounting Type Panel Mount Termination Crimp Pitch - Fastening Type - Features Keyed Housing Color Black Wire Gauge - Contact Material Contact Finish Housing Material Operating Temperature Connectors, Interconnects Solid State Lighting Connectors Number of Positions 6 Nector M 8 Receptacle Housing for Pin Contact 6 Cable/Wire Cable/Wire Cable/Wire Cable/Wire Solid State Lighting Connectors Nector M 8 Cable/Wire Cable Cable/Wire Cable	Manufacturer Part Number	2213393-2
Solid State Lighting Connectors Package - Series Nector M Style Cable/Wire to Cable/Wire Connector Type Receptacle Housing for Pin Contact Number of Positions 6 Mounting Type Panel Mount Termination Crimp Pitch - Fastening Type - Features Keyed Housing Color Black Wire Gauge Contact Material Contact Finish - Housing Material Operating Temperature Series Series Nector M School State Lighting Connectors Number of Positions 6 Nector M School Suble/Wire to Cable/Wire Cable/Wire Cable/Wire Cable/Wire Ontact Series Nector M School Suble/Wire Suble/Wire Cable/Wire Solid State Lighting Connectors Series Series Series Secontact Suble/Wire Suble/Wi	Manufacturer	TE Connectivity AMP Connectors
Package - Nector M Style Cable/Wire to Cable/Wire Connector Type Receptacle Housing for Pin Contact Number of Positions 6 Mounting Type Panel Mount Termination Crimp Pitch Fastening Type Features Keyed Housing Color Black Wire Gauge - Contact Material Contact Finish - L Housing Material Polybutylene Terephthalate (PBT), Glass Filled Operating Temperature - 40°C ~ 85°C	Category	Connectors, Interconnects
Series Nector M Style Cable/Wire to Cable/Wire Connector Type Receptacle Housing for Pin Contact Number of Positions 6 Mounting Type Panel Mount Termination Crimp Pitch - Fastening Type - Features Keyed Housing Color Black Wire Gauge - Contact Material - Contact Finish - Housing Material Polybutylene Terephthalate (PBT), Glass Filled Operating Temperature - Acousting Cable Cable Wire Cable Wire Cable C		Solid State Lighting Connectors
Style Cable/Wire to Cable/Wire Connector Type Receptacle Housing for Pin Contact Number of Positions 6 Mounting Type Panel Mount Termination Crimp Pitch - Fastening Type - Features Keyed Housing Color Black Wire Gauge - Contact Material - Contact Finish - Housing Material Polybutylene Terephthalate (PBT), Glass Filled Operating Temperature -40°C ~ 85°C	Package	-
Connector Type Receptacle Housing for Pin Contact Number of Positions 6 Mounting Type Panel Mount Termination Crimp Pitch - Fastening Type - Features Keyed Housing Color Black Wire Gauge - Contact Material - Contact Finish - Housing Material Polybutylene Terephthalate (PBT), Glass Filled Operating Temperature -40°C ~ 85°C	Series	Nector M
Number of Positions Mounting Type Panel Mount Termination Crimp Pitch - Fastening Type - Features Keyed Housing Color Black Wire Gauge Contact Material Contact Finish - Housing Material Operating Temperature 6 Panel Mount Crimp - Contact Mount - Contact Finish Polybutylene Terephthalate (PBT), Glass Filled -40°C ~ 85°C	Style	Cable/Wire to Cable/Wire
Mounting TypePanel MountTerminationCrimpPitch-Fastening Type-FeaturesKeyedHousing ColorBlackWire Gauge-Contact Material-Contact Finish-Housing MaterialPolybutylene Terephthalate (PBT), Glass FilledOperating Temperature-40°C ~ 85°C	Connector Type	Receptacle Housing for Pin Contact
Termination Crimp Pitch - Fastening Type - Features Keyed Housing Color Black Wire Gauge - Contact Material - Contact Finish - Housing Material Polybutylene Terephthalate (PBT), Glass Filled Operating Temperature - Crimp - Crimp - Reyed Feyed Feyed Foliack Foliack	Number of Positions	6
Pitch - Fastening Type - Features Keyed Housing Color Black Wire Gauge - Contact Material - Contact Finish - Housing Material Polybutylene Terephthalate (PBT), Glass Filled Operating Temperature -40°C ~ 85°C	Mounting Type	Panel Mount
Fastening Type - Keyed Housing Color Black Wire Gauge - Contact Material - Contact Finish - Housing Material Polybutylene Terephthalate (PBT), Glass Filled Operating Temperature - 40°C ~ 85°C	Termination	Crimp
Features Keyed Housing Color Black Wire Gauge - Contact Material - Contact Finish - Housing Material Polybutylene Terephthalate (PBT), Glass Filled Operating Temperature -40°C ~ 85°C	Pitch	-
Housing Color Black Wire Gauge Contact Material Contact Finish Housing Material Polybutylene Terephthalate (PBT), Glass Filled Operating Temperature Polybutylene Terephthalate (PBT), Glass Filled	Fastening Type	-
Wire Gauge Contact Material Contact Finish Housing Material Operating Temperature Polybutylene Terephthalate (PBT), Glass Filled -40°C ~ 85°C	Features	Keyed
Contact Material - Contact Finish - Housing Material Polybutylene Terephthalate (PBT), Glass Filled Operating Temperature -40°C ~ 85°C	Housing Color	Black
Contact Finish Housing Material Polybutylene Terephthalate (PBT), Glass Filled Operating Temperature -40°C ~ 85°C	Wire Gauge	-
Housing Material Polybutylene Terephthalate (PBT), Glass Filled Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$	Contact Material	-
Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$	Contact Finish	-
	Housing Material	Polybutylene Terephthalate (PBT), Glass Filled
Report errors?	Operating Temperature	-40°C ~ 85°C
		Report errors?

2213393-2 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

2213393-2 Payment Methods



















2213393-2 Shipping Methods













If you have any question about 2213393-2, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com