



2220J0160183KCR Information

Heisener.com

Ma: Cat

Part Number 2220J0160183KCR Manufacturer Knowles Syfer

Category Capacitors
Ceramic Capacitors

DescriptionCAP CER 2220**Package**2220 (5750 Metric)

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









2220J0160183KCR Specifications

Manufacturer Part Number 2220J0160183KCR Manufacturer Knowles Syfer Category Capacitors Package 2220 (5750 Metric) Series - Capacitance 0.018µF Tolerance ±10% Voltage - Rated 16V Temperature Coefficient C0G, NP0 (1B) Operating Temperature -55°C ~ 125°C Features Epoxy Mountable Ratings - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 2220 (5750 Metric) Size / Dimension 0.224" L x 0.197" W (5.70mm x 5.00mm) Height - Seated (Max) - Thickness (Max) 0.165" (4.20mm) Lead Spacing - Lead Style -		
Category Capacitors Package 2220 (5750 Metric) Series - Capacitance 0.018µF Tolerance ±10% Voltage - Rated 16V Temperature Coefficient C0G, NP0 (1B) Operating Temperature -55°C ~ 125°C Features Epoxy Mountable Ratings - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 2220 (5750 Metric) Size / Dimension 0.224" L x 0.197" W (5.70mm x 5.00mm) Height - Seated (Max) - Thickness (Max) 0.165" (4.20mm) Lead Spacing - Lead Style -	Manufacturer Part Number	2220J0160183KCR
Package 2220 (5750 Metric) Series - Capacitance 0.018μF Tolerance ±10% Voltage - Rated 16V Temperature Coefficient C0G, NP0 (1B) Operating Temperature -55°C ~ 125°C Features Epoxy Mountable Ratings - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 2220 (5750 Metric) Size / Dimension 0.224" L x 0.197" W (5.70mm x 5.00mm) Height - Seated (Max) - Thickness (Max) 0.165" (4.20mm) Lead Spacing - Lead Style -	Manufacturer	Knowles Syfer
Package 2220 (5750 Metric) Series - Capacitance 0.018µF Tolerance ±10% Voltage - Rated 16V Temperature Coefficient C0G, NP0 (1B) Operating Temperature -55°C ~ 125°C Features Epoxy Mountable Ratings - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 2220 (5750 Metric) Size / Dimension 0.224" L x 0.197" W (5.70mm x 5.00mm) Height - Seated (Max) - Thickness (Max) 0.165" (4.20mm) Lead Spacing - Lead Style -	Category	Capacitors
Series - Capacitance 0.018µF Tolerance ±10% Voltage - Rated 16V Temperature Coefficient COG, NP0 (1B) Operating Temperature -55°C ~ 125°C Features Epoxy Mountable Ratings - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 2220 (5750 Metric) Size / Dimension 0.224" L x 0.197" W (5.70mm x 5.00mm) Height - Seated (Max) - Thickness (Max) 0.165" (4.20mm) Lead Spacing - Lead Style -		Ceramic Capacitors
Capacitance 0.018μF Tolerance ±10% Voltage - Rated 16V Temperature Coefficient C0G, NP0 (1B) Operating Temperature -55°C ~ 125°C Features Epoxy Mountable Ratings - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 2220 (5750 Metric) Size / Dimension 0.224" L x 0.197" W (5.70mm x 5.00mm) Height - Seated (Max) - Thickness (Max) 0.165" (4.20mm) Lead Spacing - Lead Style -	Package	2220 (5750 Metric)
Tolerance ±10% Voltage - Rated 16V Temperature Coefficient C0G, NP0 (1B) Operating Temperature -55°C ~ 125°C Features Epoxy Mountable Ratings - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 2220 (5750 Metric) Size / Dimension 0.224" L x 0.197" W (5.70mm x 5.00mm) Height - Seated (Max) - Thickness (Max) 0.165" (4.20mm) Lead Spacing - Lead Style -	Series	-
Voltage - Rated16VTemperature CoefficientC0G, NP0 (1B)Operating Temperature-55°C ~ 125°CFeaturesEpoxy MountableRatings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case2220 (5750 Metric)Size / Dimension0.224" L x 0.197" W (5.70mm x 5.00mm)Height - Seated (Max)-Thickness (Max)0.165" (4.20mm)Lead Spacing-Lead Style-	Capacitance	0.018μF
Temperature Coefficient Operating Temperature -55°C ~ 125°C Features Epoxy Mountable Ratings - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 2220 (5750 Metric) Size / Dimension 0.224" L x 0.197" W (5.70mm x 5.00mm) Height - Seated (Max) Thickness (Max) 0.165" (4.20mm) Lead Spacing Lead Style -	Tolerance	±10%
Operating Temperature-55°C ~ 125°CFeaturesEpoxy MountableRatings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case2220 (5750 Metric)Size / Dimension0.224" L x 0.197" W (5.70mm x 5.00mm)Height - Seated (Max)-Thickness (Max)0.165" (4.20mm)Lead Spacing-Lead Style-	Voltage - Rated	16V
Features Epoxy Mountable Ratings - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 2220 (5750 Metric) Size / Dimension 0.224" L x 0.197" W (5.70mm x 5.00mm) Height - Seated (Max) - Thickness (Max) 0.165" (4.20mm) Lead Spacing - Lead Style -	Temperature Coefficient	C0G, NP0 (1B)
Ratings - General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 2220 (5750 Metric) Size / Dimension 0.224" L x 0.197" W (5.70mm x 5.00mm) Height - Seated (Max) - Thickness (Max) 0.165" (4.20mm) Lead Spacing - Lead Style	Operating Temperature	-55°C ~ 125°C
Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 2220 (5750 Metric) Size / Dimension 0.224" L x 0.197" W (5.70mm x 5.00mm) Height - Seated (Max) - Thickness (Max) 0.165" (4.20mm) Lead Spacing - Lead Style -	Features	Epoxy Mountable
Failure Rate Mounting Type Surface Mount, MLCC Package / Case 2220 (5750 Metric) Size / Dimension 0.224" L x 0.197" W (5.70mm x 5.00mm) Height - Seated (Max) - Thickness (Max) 0.165" (4.20mm) Lead Spacing - Lead Style -	Ratings	-
Mounting Type Surface Mount, MLCC Package / Case 2220 (5750 Metric) Size / Dimension 0.224" L x 0.197" W (5.70mm x 5.00mm) Height - Seated (Max) - Thickness (Max) 0.165" (4.20mm) Lead Spacing - Lead Style -	Applications	General Purpose
Package / Case 2220 (5750 Metric) Size / Dimension 0.224" L x 0.197" W (5.70mm x 5.00mm) Height - Seated (Max) - Thickness (Max) 0.165" (4.20mm) Lead Spacing - Lead Style -	Failure Rate	-
Size / Dimension 0.224" L x 0.197" W (5.70mm x 5.00mm) Height - Seated (Max) - Thickness (Max) 0.165" (4.20mm) Lead Spacing - Lead Style -	Mounting Type	Surface Mount, MLCC
Height - Seated (Max) Thickness (Max) Lead Spacing Lead Style - - - - - - - - - - - - -	Package / Case	2220 (5750 Metric)
Thickness (Max) 0.165" (4.20mm) Lead Spacing - Lead Style -	Size / Dimension	0.224" L x 0.197" W (5.70mm x 5.00mm)
Lead Spacing - Lead Style -	Height - Seated (Max)	-
Lead Style -	Thickness (Max)	0.165" (4.20mm)
·	Lead Spacing	-
Report errors?	Lead Style	-
		Report errors?

2220J0160183KCR Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

2220J0160183KCR Payment Methods

































If you have any question about 2220J0160183KCR, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com