



2220J0160185KDT Information

Heisener.com

Part Number 2220J0160185KDT

Manufacturer Knowles Syfer

Category Capacitors

Ceramic Capacitors

Description CAP CER 1.8UF 16V X7R 2220

Package 2220 (5750 Metric)

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









2220J0160185KDT Specifications

Manufacturer Part Number 2220J0160185KDT Manufacturer Knowles Syfer Category Capacitors Package 2220 (5750 Metric) Series - Capacitance 1.8µF Tolerance ±10% Voltage - Rated 16V Temperature Coefficient X7R (2R1) Operating Temperature -55°C ~ 125°C Features High Temperature Ratings - Applications High Reliability Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 2220 (5750 Metric) Size / Dimension 0.224" L x 0.197" W (5.70mm x 5.00mm) Height - Seated (Max) - Thickness (Max) 0.098" (2.50mm) Lead Spacing - Lead Style -		
Category Capacitors Package 2220 (5750 Metric) Series - Capacitance 1.8µF Tolerance ±10% Voltage - Rated 16V Temperature Coefficient X7R (2R1) Operating Temperature -55°C ~ 125°C Features High Temperature Ratings - Applications High Reliability Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 2220 (5750 Metric) Size / Dimension 0.224" L x 0.197" W (5.70mm x 5.00mm) Height - Seated (Max) - Thickness (Max) 0.098" (2.50mm) Lead Spacing - Lead Style -	Manufacturer Part Number	2220J0160185KDT
Package 2220 (5750 Metric) Series - Capacitance 1.8μF Tolerance ±10% Voltage - Rated 16V Temperature Coefficient X7R (2R1) Operating Temperature -55°C ~ 125°C Features High Temperature Ratings - Applications High Reliability Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 2220 (5750 Metric) Size / Dimension 0.224" L x 0.197" W (5.70mm x 5.00mm) Height - Seated (Max) - Thickness (Max) 0.098" (2.50mm) Lead Spacing - Lead Style -	Manufacturer	Knowles Syfer
Package 2220 (5750 Metric) Series - Capacitance 1.8µF Tolerance ±10% Voltage - Rated 16V Temperature Coefficient X7R (2R1) Operating Temperature -55°C ~ 125°C Features High Temperature Ratings - Applications High Reliability Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 2220 (5750 Metric) Size / Dimension 0.224" L x 0.197" W (5.70mm x 5.00mm) Height - Seated (Max) - Thickness (Max) 0.098" (2.50mm) Lead Spacing - Lead Style -	Category	Capacitors
Series - Capacitance 1.8μF Tolerance ±10% Voltage - Rated 16V Temperature Coefficient X7R (2R1) Operating Temperature -55°C ~ 125°C Features High Temperature Ratings - Applications High Reliability Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 2220 (5750 Metric) Size / Dimension 0.224" L x 0.197" W (5.70mm x 5.00mm) Height - Seated (Max) 0.098" (2.50mm) Lead Spacing - Lead Style -		Ceramic Capacitors
Capacitance 1.8µF Tolerance ±10% Voltage - Rated 16V Temperature Coefficient X7R (2R1) Operating Temperature -55°C ~ 125°C Features High Temperature Ratings - Applications High Reliability Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 2220 (5750 Metric) Size / Dimension 0.224" L x 0.197" W (5.70mm x 5.00mm) Height - Seated (Max) - Thickness (Max) 0.098" (2.50mm) Lead Spacing - Lead Style -	Package	2220 (5750 Metric)
Tolerance ±10% Voltage - Rated 16V Temperature Coefficient X7R (2R1) Operating Temperature -55°C ~ 125°C Features High Temperature Ratings - Applications High Reliability Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 2220 (5750 Metric) Size / Dimension 0.224" L x 0.197" W (5.70mm x 5.00mm) Height - Seated (Max) - Thickness (Max) 0.098" (2.50mm) Lead Spacing - Lead Style -	Series	-
Voltage - Rated16VTemperature CoefficientX7R (2R1)Operating Temperature-55°C ~ 125°CFeaturesHigh TemperatureRatings-ApplicationsHigh ReliabilityFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case2220 (5750 Metric)Size / Dimension0.224" L x 0.197" W (5.70mm x 5.00mm)Height - Seated (Max)-Thickness (Max)0.098" (2.50mm)Lead Spacing-Lead Style-	Capacitance	1.8μF
Temperature Coefficient ATR (2R1) Operating Temperature -55°C ~ 125°C Features High Temperature Ratings - Applications High Reliability Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 2220 (5750 Metric) Size / Dimension 0.224" L x 0.197" W (5.70mm x 5.00mm) Height - Seated (Max) Thickness (Max) 0.098" (2.50mm) Lead Spacing - Lead Style	Tolerance	±10%
Operating Temperature-55°C ~ 125°CFeaturesHigh TemperatureRatings-ApplicationsHigh ReliabilityFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case2220 (5750 Metric)Size / Dimension0.224" L x 0.197" W (5.70mm x 5.00mm)Height - Seated (Max)-Thickness (Max)0.098" (2.50mm)Lead Spacing-Lead Style-	Voltage - Rated	16V
Features High Temperature Ratings - Applications High Reliability Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 2220 (5750 Metric) Size / Dimension 0.224" L x 0.197" W (5.70mm x 5.00mm) Height - Seated (Max) - Thickness (Max) 0.098" (2.50mm) Lead Spacing - Lead Style -	Temperature Coefficient	X7R (2R1)
Ratings - High Reliability Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 2220 (5750 Metric) Size / Dimension 0.224" L x 0.197" W (5.70mm x 5.00mm) Height - Seated (Max) - Thickness (Max) 0.098" (2.50mm) Lead Spacing - Lead Style -	Operating Temperature	-55°C ~ 125°C
Applications High Reliability Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 2220 (5750 Metric) Size / Dimension 0.224" L x 0.197" W (5.70mm x 5.00mm) Height - Seated (Max) - Thickness (Max) 0.098" (2.50mm) Lead Spacing - Lead Style -	Features	High Temperature
Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 2220 (5750 Metric) Size / Dimension 0.224" L x 0.197" W (5.70mm x 5.00mm) Height - Seated (Max) - Thickness (Max) 0.098" (2.50mm) Lead Spacing - Lead Style -	Ratings	-
Mounting Type Surface Mount, MLCC Package / Case 2220 (5750 Metric) Size / Dimension 0.224" L x 0.197" W (5.70mm x 5.00mm) Height - Seated (Max) - Thickness (Max) 0.098" (2.50mm) Lead Spacing - Lead Style -	Applications	High Reliability
Package / Case 2220 (5750 Metric) Size / Dimension 0.224" L x 0.197" W (5.70mm x 5.00mm) Height - Seated (Max) - Thickness (Max) 0.098" (2.50mm) Lead Spacing - Lead Style -	Failure Rate	-
Size / Dimension 0.224" L x 0.197" W (5.70mm x 5.00mm) Height - Seated (Max) - Thickness (Max) 0.098" (2.50mm) Lead Spacing - Lead Style -	Mounting Type	Surface Mount, MLCC
Height - Seated (Max) Thickness (Max) Lead Spacing Lead Style - - - - - - - - - - - - -	Package / Case	2220 (5750 Metric)
Thickness (Max) 0.098" (2.50mm) Lead Spacing - Lead Style -	Size / Dimension	0.224" L x 0.197" W (5.70mm x 5.00mm)
Lead Spacing - Lead Style -	Height - Seated (Max)	-
Lead Style -	Thickness (Max)	0.098" (2.50mm)
	Lead Spacing	-
Report errors?	Lead Style	-
		Report errors?

2220J0160185KDT Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

2220J0160185KDT Payment Methods



















2220J0160185KDT Shipping Methods













If you have any question about 2220J0160185KDT, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com