

2220J0160223KFT

2220J0160223KFT Information

Heisener.com Octariarios carla tare	 2220J0160223KFT Knowles Syfer Capacitors Ceramic Capacitors CAP CER 0.022UF 16V C0G/NP0 2220 2220 (5750 Metric) For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



2220J0160223KFT Specifications

Manufacturer Part Number 2220/0160223KFT Manufacturer Knowles Syfer Category Capacitors Package 2220 (5750 Metric) Package 2220 (5750 Metric) Series - Capacitance 0.022µF Tolerance ±10% Voltage - Rated 16V Operating Temperature C0G, NP0 Operating Temperature -55°C ~ 125°C Pactage 14gh Reliability Features High Reliability Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 2200 (5750 Metric) Size / Dimension 0.224" L x 0.197" W (5.70mm x 5.00mm) Height - Seated (Max) - Thickness (Max) 0.098" (2.50mm) Lead Spacing -		
CategoryCapacitorsPackage2220 (5750 Metric)Series-Capacitance0.022µFTolerance±10%Voltage - Rated6VTomperature CoefficientCOG, NPOOperating Temperature-55°C ~ 125°CFeaturesHigh TemperatureRatings-ApplicationsHigh ReliabilityFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case220 (5750 Metric)Size / Dimension0.224" L x 0.197" W (5.70mm x 5.00mm)Height - Seated (Max)-Hickness (Max)0.098" (2.50mm)Lead Spacing-Lead Style-	Manufacturer Part Number	2220J0160223KFT
Ceranic CapacitorsPackage2220 (5750 Metric)Series-Capacitance0.022µFTolerance±10%Voltage - Rated16VTemperature CoefficientCOG, NP0Operating Temperature-55°C ~ 125°CFeaturesHigh TemperatureApplications-Applications-Mounting TypeSurface Mount, MLCCPackage / Case2200 (5750 Metric)Size / Dimension0.224" L x 0.197" W (5.70mm x 5.00mm)Hight-Seated (Max)-Thickness (Max)0.098" (2.50mm)Lead Style-Lead Style-	Manufacturer	Knowles Syfer
Package2220 (5750 Metric)Series-Capacitance0.022µFTolerance±10%Voltage - Rated16VComperature CoefficientCOG, NPOOperating Temperature-55°C ~ 125°CFeaturesHigh TemperatureApplications-ApplicationsSurface Mount, MLCCNounting Type0.224° L x 0.197° W (5.70mm x 5.00mm)Size / Dimension0.224° L x 0.197° W (5.70mm x 5.00mm)Height - Seated (Max)0.098° (2.50mm)Lead Spacing-Lead Style-Lead Style-Strice State-Strice Strice State- <td>Category</td> <td>Capacitors</td>	Category	Capacitors
Series-Capacitance0.022µFTolerance±10%Voltage - Rated16VTemperature CoefficientCOG, NP0Operating Temperature-55°C ~ 125°CFeaturesHigh TemperatureRatings-ApplicationsHigh ReliabilityFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case220 (5750 Metric)Size / Dimension0.224" L x 0.197" W (5.70mm x 5.00mm)Height - Seated (Max)-Thickness (Max)0.098" (2.50mm)Lead Spacing-Lead Style-Starley- <tr< td=""><td></td><td>Ceramic Capacitors</td></tr<>		Ceramic Capacitors
Capacitance0.022µFTolerance±10%Voltage - Rated16VTemperature CoefficientCOG, NPOOperating Temperature-55°C ~ 125°CFeaturesHigh TemperatureRatings-ApplicationsHigh ReliabilityFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case220 (5750 Metric)Size / Dimension0.224" L x 0.197" W (5.70mm x 5.00mm)Height - Seated (Max)-Thickness (Max)0.908" (2.50mm)Lead Spacing-Lead Style-Starten Starten Sta	Package	2220 (5750 Metric)
Tolerance±10%Voltage - Rated16VTemperature CoefficientC0G, NP0Operating Temperature-55°C ~ 125°CFeaturesHigh TemperatureRatings-ApplicationsHigh ReliabilityFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case220 (5750 Metric)Size / Dimension0.224" L x 0.197" W (5.70mm x 5.00mm)High reseated (Max)-Thickness (Max)0.098" (2.50mm)Lead Stufe-Lead Stufe-Stufe Stufe St	Series	-
Voltage - RatedI6VTemperature CoefficientCOG, NPOOperating Temperature-5°C ~ 125°CFeaturesHigh TemperatureRatings-ApplicationsHigh ReliabilityFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case2220 (5750 Metric)Size / Dimension-Height - Seated (Max)-Hickness (Max)0.098" (2.50mm)Lead Spacing-Lead Style-<	Capacitance	0.022µF
Temperature CoefficientC0G, NP0Operating Temperature-55°C ~ 125°CFeaturesHigh TemperatureRatings-ApplicationsHigh ReliabilityFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case2220 (5750 Metric)Size / Dimension0.224" L x 0.197" W (5.70mm x 5.00mm)High Testated (Max)-Thickness (Max)0.098" (2.50mm)Lead Spacing-Lead Spacing-Hat Style-State Style-State Style-State Style-State Style-State Style-State Style-State Style-State Style-Style <td>Tolerance</td> <td>$\pm 10\%$</td>	Tolerance	$\pm 10\%$
Operating Temperature-55°C ~ 125°CFeaturesHigh TemperatureRatings-ApplicationsHigh ReliabilityFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case2220 (5750 Metric)Size / Dimension0.224" L x 0.197" W (5.70mm x 5.00mm)Height - Seated (Max)-Thickness (Max)0.098" (2.50mm)Lead Spacing-Lead Style-	Voltage - Rated	16V
FeaturesHigh TemperatureFeaturesHigh TemperatureRatings-ApplicationsHigh ReliabilityFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case2220 (5750 Metric)Size / Dimension0.224" L x 0.197" W (5.70mm x 5.00mm)Height - Seated (Max)-Thickness (Max)0.098" (2.50mm)Lead Spacing-Lead Style-	Temperature Coefficient	C0G, NP0
Ratings-ApplicationsHigh ReliabilityFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case220 (5750 Metric)Size / Dimension0.224" L x 0.197" W (5.70mm x 5.00mm)Height - Seated (Max)-Thickness (Max)0.098" (2.50mm)Lead Spacing-Height - Seated (Max)-Height - Seated (Max)- </td <td>Operating Temperature</td> <td>-55°C ~ 125°C</td>	Operating Temperature	-55°C ~ 125°C
ApplicationsHigh ReliabilityFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case2220 (5750 Metric)Size / Dimension0.224" L x 0.197" W (5.70mm x 5.00mm)Height - Seated (Max)-Thickness (Max)0.098" (2.50mm)Lead Spacing-Lead Style-	Features	High Temperature
Failure Rate-Failure Rate-Mounting TypeSurface Mount, MLCCPackage / Case2220 (5750 Metric)Size / Dimension0.224" L x 0.197" W (5.70mm x 5.00mm)Height - Seated (Max)-Thickness (Max)0.098" (2.50mm)Lead Spacing-Lead Style-	Ratings	-
Mounting TypeSurface Mount, MLCCPackage / Case2220 (5750 Metric)Size / Dimension0.224" L x 0.197" W (5.70mm x 5.00mm)Height - Seated (Max)-Thickness (Max)0.098" (2.50mm)Lead Spacing-Lead Style-	Applications	High Reliability
Package / Case 2220 (5750 Metric) Size / Dimension 0.224" L x 0.197" W (5.70mm x 5.00mm) Height - Seated (Max) - Thickness (Max) 0.098" (2.50mm) Lead Spacing - Lead Style -	Failure Rate	-
Size / Dimension 0.224" L x 0.197" W (5.70mm x 5.00mm) Height - Seated (Max) - Thickness (Max) 0.098" (2.50mm) Lead Spacing - Lead Style -	Mounting Type	Surface Mount, MLCC
Height - Seated (Max)-Thickness (Max)0.098" (2.50mm)Lead Spacing-Lead Style-	Package / Case	2220 (5750 Metric)
Thickness (Max)0.098" (2.50mm)Lead Spacing-Lead Style-	Size / Dimension	0.224" L x 0.197" W (5.70mm x 5.00mm)
Lead Spacing-Lead Style-	Height - Seated (Max)	-
Lead Style -	Thickness (Max)	0.098" (2.50mm)
· ·	Lead Spacing	-
Report errors?	Lead Style	-
		Report errors?

2220J0160223KFT Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

2220J0160223KFT Payment Methods



If you have any question about 2220J0160223KFT, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com