

2220J0160470FCR

Request a Quote

2220J0160470FCR Information

		2220101 (0.1505)
Codar tencer, com	Part Number	2220J0160470FCR
	Manufacturer	Knowles Syfer
	Category	Capacitors
		Ceramic Capacitors
	Description	CAP CER 2220
	Package	2220 (5750 Metric)
		For the pricing/inventory/lead time, please contact
For Reference Only		us
		Website: https://www.heisener.com
		E-mail: salesdept@heisener.com



Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



2220J0160470FCR Specifications

Manufacturer Part Number 2220/0160470FCR Manufacturer Knowles Syfer Category Capacitors Package 2220 (5750 Metric) Package 2220 (5750 Metric) Series - Capacitance 47pF Tolerance ±1% Voltage - Rated COG NP0 (1B) Operating Temperature -55°C ~ 125°C Package Epoxy Mountable Ratings - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 2220 (5750 Metric) Size / Dimension 0.224" L x 0.197" W (5.70mm x 5.00mm) Height - Seated (Max) - Thickness (Max) 0.165" (4.20mm) Lead Spacing -		
CategoryCapacitorsPackage2220 (5750 Metric)Series-Capacitance47pFColerance±1%Voltage - Rated60VTomperature CoefficientCOG, NP0 (1B)Operating Temperature-55°C ~ 125°CFeaturesEpoxy MountableRatings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case220 (5750 Metric)Size / Dimension0.224" L x 0.197" W (5.70mm x 5.00mm)Height - Seated (Max)-Thickness (Max)0.165" (4.20mm)Lead Style-	Manufacturer Part Number	2220J0160470FCR
Iceranic CapacitorsPackage220 (750 Metric)Series-Capacitance47pFTolerance1%Voltage - Rated16VCorperature CoefficientCOG, NP0 (1B)Operating Temperature55°C ~ 125°CFeaturesEpoxy MountableApplications-ApplicationsSeries PurposeFailure Rate-Mounting TypeSufface Mount, MLCCPackage / Case220 (750 Metric)Size / Dimension0.624" L x 0.197" W (5.70mm x 5.00mm)Height - Seated (Max)-Hickness (Max)0.165" (4.20mm)Lead Spacing-Lead Style-Lead Style-	Manufacturer	Knowles Syfer
Package220 (5750 Metric)Series-Capacitance47pFTolerance±1%Voltage - Rated60Comperature CoefficientC0G, NP0 (1B)Operating Temperature-55°C ~ 125°CFeaturesEpoxy MountableRatings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeSufface Mount, MLCCPackage / Case0.224° L x 0.197° W (5.70mm x 5.00mm)Fichers (Max)0.165° (4.20mm)Height - Seated (Max)-Lead Spacing-Lead Style-Lead Style-	Category	Capacitors
Series-Capacitance47pFTolerance±1%Voltage Rated16VTemperature CoefficientCOG, NP0 (1B)Operating Temperature-55°C ~ 125°CFeaturesEpoxy MountableRatings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case220 (5750 Metric)Size / Dimension0.224" L x 0.197" W (5.70mm x 5.00mm)Height - Seated (Max)-Thickness (Max)0.165" (4.20mm)Lead Spacing-Lead Style-Starley- <t< td=""><td></td><td>Ceramic Capacitors</td></t<>		Ceramic Capacitors
Capacitance47pFTolerance±1%Voltage - Rated16VTemperature CoefficientCOG, NPO (1B)Operating Temperature-55°C ~ 125°CFeaturesEpoxy MountableRatings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeSurface Mount, MLCCSize / Dimension0.224" L x 0.197" W (5.70mm x 5.00mm)Height - Seated (Max)-Thickness (Max)0.165" (4.20mm)Lead Spacing-Lead Style-Starley Starley-Starley Starley-<	Package	2220 (5750 Metric)
Tolerance±1%Voltage - Rated16VTemperature CoefficientC0G, NP0 (1B)Operating Temperature-55°C ~ 125°CFeaturesEpoxy MountableRatings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case2220 (5750 Metric)Size / Dimension0.224" L x 0.197" W (5.70mm x 5.00mm)Height - Seated (Max)-Thickness (Max)0.165" (4.20mm)Lead Stule-Lead Stule-	Series	-
Voltage - RatedI6VTemperature CoefficientCOG, NPO (1B)Operating Temperature-5°C ~ 125°CFeaturesEpoxy MountableRatings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case2220 (5750 Metric)Size / Dimension-Height - Seated (Max)-Thickness (Max)0.165" (4.20mm) 5.00mm)Lead Spacing-Lead Style-State Style-State Style-State Style-State Style-State Style-State Style-State Style-State Style-State Style-<	Capacitance	47pF
Temperature CoefficientC0G, NP0 (1B)Operating Temperature-55°C ~ 125°CFeaturesEpoxy MountableRatings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case2220 (5750 Metric)Size / Dimension0.224" L x 0.197" W (5.70mm x 5.00mm)Height - Seated (Max)-Lead Spacing-Lead Spacing-Lead Style-State Style-<	Tolerance	±1%
Operating Temperature-55°C ~ 125°CFeaturesEpoxy MountableRatings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case2220 (5750 Metric)Size / Dimension0.224" L x 0.197" W (5.70mm x 5.00mm)Height - Seated (Max)-Thickness (Max)0.165" (4.20mm)Lead Spacing-Kead Style- </td <td>Voltage - Rated</td> <td>16V</td>	Voltage - Rated	16V
FeaturesEpoxy MountableFeaturesEpoxy MountableRatings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case2220 (5750 Metric)Size / Dimension0.224" L x 0.197" W (5.70mm x 5.00mm)Height - Seated (Max)-Thickness (Max)0.165" (4.20mm)Lead Spacing-Lead Style-	Temperature Coefficient	C0G, NP0 (1B)
Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case220 (5750 Metric)Size / Dimension0.224" L x 0.197" W (5.70mm x 5.00mm)Height - Seated (Max)-Thickness (Max)0.165" (4.20mm)Lead Spacing-Height - Seated (Max)-Height - Seated (Max)-Star (Max)<	Operating Temperature	-55°C ~ 125°C
ApplicationsGeneral PurposeFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case2220 (5750 Metric)Size / Dimension0.224" L x 0.197" W (5.70mm x 5.00mm)Height - Seated (Max)-Thickness (Max)0.165" (4.20mm)Lead Spacing-Lead Style-	Features	Epoxy Mountable
Failure Rate-Failure RateSurface Mount, MLCCMounting Type2220 (5750 Metric)Package / Case0.224" L x 0.197" W (5.70mm x 5.00mm)Size / Dimension0.224" L x 0.197" W (5.70mm x 5.00mm)Height - Seated (Max)-Thickness (Max)0.165" (4.20mm)Lead Spacing-Lead Style-	Ratings	-
Mounting TypeSurface Mount, MLCCPackage / Case2220 (5750 Metric)Size / Dimension0.224" L x 0.197" W (5.70mm x 5.00mm)Height - Seated (Max)-Thickness (Max)0.165" (4.20mm)Lead Spacing-Lead Style-	Applications	General Purpose
Package / Case 2220 (5750 Metric) Size / Dimension 0.224" L x 0.197" W (5.70mm x 5.00mm) Height - Seated (Max) - Thickness (Max) 0.165" (4.20mm) Lead Spacing - Lead Style -	Failure Rate	-
Size / Dimension 0.224" L x 0.197" W (5.70mm x 5.00mm) Height - Seated (Max) - Thickness (Max) 0.165" (4.20mm) Lead Spacing - Lead Style -	Mounting Type	Surface Mount, MLCC
Height - Seated (Max)-Thickness (Max)0.165" (4.20mm)Lead Spacing-Lead Style-	Package / Case	2220 (5750 Metric)
Thickness (Max)0.165" (4.20mm)Lead Spacing-Lead Style-	Size / Dimension	0.224" L x 0.197" W (5.70mm x 5.00mm)
Lead Spacing-Lead Style-	Height - Seated (Max)	-
Lead Style -	Thickness (Max)	0.165" (4.20mm)
· · · · · · · · · · · · · · · · · · ·	Lead Spacing	-
Report errors?	Lead Style	-
		Report errors?

2220J0160470FCR Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

2220J0160470FCR Payment Methods



If you have any question about 2220J0160470FCR, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com