



2220J0500561FCR Information

Heisener.com

For Reference Only

2220J0500561FCR Part Number Manufacturer Knowles Syfer Category

Capacitors

Ceramic Capacitors

Description CAP CER 2220 Package 2220 (5750 Metric)

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









2220J0500561FCR Specifications

Manufacturer Part Number 2220J0500561FCR Manufacturer Knowles Syfer Category Capacitors Package 2220 (5750 Metric) Series - Capacitance 560pF Tolerance ±1% Voltage - Rated 50V Temperature Coefficient C0G, NP0 (1B) Operating Temperature -55°C ~ 125°C Features Epoxy Mountable		
Category Capacitors Package 2220 (5750 Metric) Series - Capacitance 560pF Tolerance ±1% Voltage - Rated 50V Temperature Coefficient C0G, NP0 (1B) Operating Temperature -55°C ~ 125°C Features Epoxy Mountable	ıfacturer Part Number	2220J0500561FCR
Ceramic Capacitors Package 2220 (5750 Metric) Series - Capacitance 560pF Tolerance ±1% Voltage - Rated 50V Temperature Coefficient C0G, NP0 (1B) Operating Temperature -55°C ~ 125°C Features Epoxy Mountable	ıfacturer	Knowles Syfer
Package 2220 (5750 Metric) Series - Capacitance 560pF Tolerance ±1% Voltage - Rated 50V Temperature Coefficient C0G, NP0 (1B) Operating Temperature -55°C ~ 125°C Features Epoxy Mountable	gory	Capacitors
Series - Capacitance 560pF Tolerance ±1% Voltage - Rated 50V Temperature Coefficient C0G, NP0 (1B) Operating Temperature -55°C ~ 125°C Features Epoxy Mountable		Ceramic Capacitors
Capacitance $560 \mathrm{pF}$ Tolerance $\pm 1\%$ Voltage - Rated $50 \mathrm{V}$ Temperature Coefficient $C0G$, NP0 (1B)Operating Temperature $-55^{\circ}\mathrm{C} \sim 125^{\circ}\mathrm{C}$ FeaturesEpoxy Mountable	age	2220 (5750 Metric)
Tolerance $\pm 1\%$ Voltage - Rated $50V$ Temperature Coefficient $C0G$, NP0 (1B) Operating Temperature $-55^{\circ}C \sim 125^{\circ}C$ Features Epoxy Mountable	s	-
Voltage - Rated 50V Temperature Coefficient C0G, NP0 (1B) Operating Temperature -55°C ~ 125°C Features Epoxy Mountable	citance	560pF
Temperature Coefficient C0G, NP0 (1B) Operating Temperature -55°C ~ 125°C Epoxy Mountable	rance	$\pm 1\%$
Operating Temperature -55°C ~ 125°C Features Epoxy Mountable	ige - Rated	50V
Features Epoxy Mountable	perature Coefficient	C0G, NP0 (1B)
	ating Temperature	-55°C ~ 125°C
	ires	Epoxy Mountable
Ratings -	ıgs	-
Applications General Purpose	ications	General Purpose
Failure Rate -	re Rate	-
Mounting Type Surface Mount, MLCC	nting Type	Surface Mount, MLCC
Package / Case 2220 (5750 Metric)	age / Case	2220 (5750 Metric)
Size / Dimension 0.224" L x 0.197" W (5.70mm x 5.00mm)	/ Dimension	0.224" L x 0.197" W (5.70mm x 5.00mm)
Height - Seated (Max) -	nt - Seated (Max)	-
Thickness (Max) 0.165" (4.20mm)	kness (Max)	0.165" (4.20mm)
Lead Spacing -	Spacing	-
Lead Style -	Style	-
Report error		Report errors?

2220J0500561FCR Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

2220J0500561FCR Payment Methods



















2220J0500561FCR Shipping Methods













If you have any question about 2220J0500561FCR, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com