

2220J1000153GFT

2220J1000153GFT Information

Heisener.com	 2220J1000153GFT Knowles Syfer Capacitors Ceramic Capacitors CAP CER 0.015UF 100V C0G 2220 2220 (5750 Metric) For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



2220J1000153GFT Specifications

Ananfacturer Knowles Syfer Capacitors Capacitors Caranic Capacitors Ceranic Capacitors Package 2220 (5750 Metric) Series - Capacitance 0.015µF Colarance ±2% Voltage - Rated 100V Comperature Coefficient COG, NPO Operating Temperature 55°C ~ 125°C Vertures High Temperature Applications - Applications Series Applications Surface Mount, MLCC Applexed / Case 220 (5750 Metric) Cate / Dimension 520 (5750 Metric)		
Capacitors Ceramic Capacitors Package 2220 (5750 Metric) Package - Capacitance 0.015µF Polerance ±2% Yoltage - Rated 100V Premperature Coefficient COG, NPO Operating Temperature -55°C ~ 125°C Pactards High Temperature Values - Applications - Values High Reliability Values - Applications Surface Mount, MLCC Package / Case 220 (5750 Metric) Values / L x 0.197" W (5.70mm x 5.00mm) -	Manufacturer Part Number	2220J1000153GFT
Ceramic CapacitorsPackage2220 (5750 Metric)Beries-Capacitance0.015µFColerance±2%Voltage - Rated100VComperature CoefficientCOG, NPOOperating Temperature-55°C ~ 125°CVeaturesHigh TemperatureRatings-ApplicationsHigh ReliabilityValuer Rate-Automing TypeSurface Mount, MLCCPackage / Case2220 (5750 Metric)Bize / Dimension0.224" L x 0.197" W (5.70mm x 5.00mm)	Manufacturer	Knowles Syfer
Package2220 (5750 Metric)Beries-Capacitance0.015µFTolerance±2%Voltage - Rated100VCemperature CoefficientCOG, NPOOperating Temperature-55°C ~ 125°CBeatrags-ApplicationsHigh TemperatureApplicationsSurface Mount, MLCCPackage / Case2220 (5750 Metric)Bize / Dimension0.224" L x 0.197" W (5.70mm x 5.00mm)	Category	Capacitors
Action-Capacitance0.015μFColerance±2%Voltage - Rated100VComperature CoefficientCOG, NPOOperating Temperature-55°C ~ 125°CPeaturesHigh TemperatureRatings-ApplicationsHigh ReliabilityGalutre Rate-Aounting TypeSurface Mount, MLCCPackage / Case2220 (5750 Metric)Bize / Dimension0.224" L x 0.197" W (5.70mm x 5.00mm)		Ceramic Capacitors
Capacitance0.015μFColerance±2%Voltage - Rated100VComperature CoefficientCOG, NPOOperating Temperature-55°C ~ 125°CSeaturesHigh TemperatureRatings-ApplicationsHigh ReliabilitySalure Rate-Aounting TypeSurface Mount, MLCCPackage / Case2220 (5750 Metric)Size / Dimension0.224" L x 0.197" W (5.70mm x 5.00mm)	Package	2220 (5750 Metric)
Folerance±2%Yoltage - Rated100VCemperature CoefficientCOG, NP0Operating Temperature-55°C ~ 125°CVeaturesHigh TemperatureRatings-ApplicationsHigh ReliabilityGailure Rate-Aounting TypeSurface Mount, MLCCPackage / Case2220 (5750 Metric)Size / Dimension0.224" L x 0.197" W (5.70mm x 5.00mm)	Series	-
Yoltage - Rated100VYoltage - RatedC0G, NP0Operating Temperature-55°C ~ 125°CYeaturesHigh TemperatureRatings-ApplicationsHigh ReliabilityYalure Rate-Younting TypeSurface Mount, MLCCYeakage / Case2220 (5750 Metric)Size / Dimension0.224" L x 0.197" W (5.70mm x 5.00mm)	Capacitance	0.015µF
Comperature CoefficientCOG, NPOOperating Temperature-55°C ~ 125°CSeaturesHigh TemperatureRatings-ApplicationsHigh ReliabilityFailure Rate-Aounting TypeSurface Mount, MLCCPackage / Case2220 (5750 Metric)Size / Dimension0.224" L x 0.197" W (5.70mm x 5.00mm)	Tolerance	±2%
Deperating Temperature-55°C ~ 125°CGeaturesHigh TemperatureRatings-ApplicationsHigh ReliabilityGalure Rate-Aounting TypeSurface Mount, MLCCPackage / Case2220 (5750 Metric)Size / Dimension0.224" L x 0.197" W (5.70mm x 5.00mm)	Voltage - Rated	100V
FeaturesHigh TemperatureRatings-ApplicationsHigh ReliabilityFailure Rate-Aounting TypeSurface Mount, MLCCPackage / Case2220 (5750 Metric)Size / Dimension0.224" L x 0.197" W (5.70mm x 5.00mm)	Temperature Coefficient	COG, NP0
Ratings-ApplicationsHigh ReliabilityFailure Rate-Aounting TypeSurface Mount, MLCCPackage / Case2220 (5750 Metric)Size / Dimension0.224" L x 0.197" W (5.70mm x 5.00mm)	Operating Temperature	-55°C ~ 125°C
ApplicationsHigh ReliabilityFailure Rate-Aounting TypeSurface Mount, MLCCPackage / Case2220 (5750 Metric)Bize / Dimension0.224" L x 0.197" W (5.70mm x 5.00mm)	Features	High Temperature
Failure Rate-Aounting TypeSurface Mount, MLCCPackage / Case2220 (5750 Metric)Size / Dimension0.224" L x 0.197" W (5.70mm x 5.00mm)	Ratings	-
Aounting TypeSurface Mount, MLCCPackage / Case2220 (5750 Metric)Size / Dimension0.224" L x 0.197" W (5.70mm x 5.00mm)	Applications	High Reliability
Package / Case 2220 (5750 Metric) Size / Dimension 0.224" L x 0.197" W (5.70mm x 5.00mm)	Failure Rate	-
Dimension 0.224" L x 0.197" W (5.70mm x 5.00mm)	Mounting Type	Surface Mount, MLCC
	Package / Case	2220 (5750 Metric)
Height - Seated (Max) -	Size / Dimension	0.224" L x 0.197" W (5.70mm x 5.00mm)
	Height - Seated (Max)	-
Chickness (Max) 0.098" (2.50mm)	Thickness (Max)	0.098" (2.50mm)
Lead Spacing -	Lead Spacing	-
	Lead Style	-
Report errors?		Report errors?

2220J1000153GFT Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

2220J1000153GFT Payment Methods



If you have any question about 2220J1000153GFT, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com