



2220J1000471FCR Information

Heisener.com

Part Number 2220J1000471FCR
Manufacturer Knowles Syfer

Category Capacitors
Ceramic Capacitors

Description CAP CER 2220 **Package** 2220 (5750 Metric)

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
F-mail: salesdent@heisener.com

E-mail: salesdept@heisener.com

Request a Quote



Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









2220J1000471FCR Specifications

Manufacturer Knowles Syfer Category Capacitors Package 2220 (5750 Metric) Series - Capacitance 470pF Tolerance ±1% Voltage - Rated 100V Temperature Coefficient C0G, NP0 (1B) Operating Temperature -55°C ~ 125°C Features Epoxy Mountable Ratings -		
Category Capacitors Package 2220 (5750 Metric) Series - Capacitance 470pF Tolerance ±1% Voltage - Rated 100V Temperature Coefficient C0G, NP0 (1B) Operating Temperature -55°C ~ 125°C Features Epoxy Mountable Ratings -	Manufacturer Part Number	471FCR
Ceramic Capacitors Package 2220 (5750 Metric) Series - Capacitance 470pF Folerance ±1% Voltage - Rated 100V Temperature Coefficient C0G, NP0 (1B) Operating Temperature -55°C ~ 125°C Features Epoxy Mountable Ratings -	Manufacturer	yfer
Package 2220 (5750 Metric) Series - Capacitance 470pF Tolerance ±1% Voltage - Rated 100V Temperature Coefficient C0G, NP0 (1B) Operating Temperature -55°C ~ 125°C Features Epoxy Mountable Ratings -	Category	
Features Foreians		apacitors
Capacitance $470 \mathrm{pF}$ Folerance $\pm 1\%$ Voltage - Rated $100 \mathrm{V}$ Temperature Coefficient $C0G$, NP0 (1B)Operating Temperature $-55^{\circ}\mathrm{C} \sim 125^{\circ}\mathrm{C}$ FeaturesEpoxy MountableRatings-	Package) Metric)
Folerance $\pm 1\%$ Voltage - Rated $100V$ Temperature Coefficient $C0G$, NP0 (1B) Operating Temperature $-55^{\circ}C \sim 125^{\circ}C$ Features Epoxy Mountable Ratings -	Series	
Voltage - Rated 100V Temperature Coefficient COG, NP0 (1B) Operating Temperature -55°C ~ 125°C Features Epoxy Mountable Ratings -	Capacitance	
Temperature Coefficient COG, NP0 (1B) Operating Temperature -55°C ~ 125°C Features Epoxy Mountable Ratings -	Tolerance	
Operating Temperature -55°C ~ 125°C Features Epoxy Mountable Ratings -	Voltage - Rated	
Features Epoxy Mountable Ratings -	Temperature Coefficient	(1B)
Ratings -	Operating Temperature	25°C
-	Features	untable
Applications General Purpose	Ratings	
Tephronia Contrar in pose	Applications	ırpose
Failure Rate -	Failure Rate	
Mounting Type Surface Mount, MLCC	Mounting Type	ount, MLCC
Package / Case 2220 (5750 Metric)	Package / Case) Metric)
Size / Dimension 0.224" L x 0.197" W (5.70mm x 5.00mm)	Size / Dimension	0.197" W (5.70mm x 5.00mm)
Height - Seated (Max)	Height - Seated (Max)	
Thickness (Max) 0.165" (4.20mm)	Thickness (Max)	20mm)
Lead Spacing -	Lead Spacing	
Lead Style -	Lead Style	
Report error		Report errors?

2220J1000471FCR Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

2220J1000471FCR Payment Methods



















2220J1000471FCR Shipping Methods













If you have any question about 2220J1000471FCR, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com