



2220Y0100392FCT Information

Heisener.com

Part Number 2220Y0100392FCT Manufacturer Knowles Syfer

Category Capacitors

Ceramic Capacitors

Description CAP CER 2220


Package 2220 (5750 Metric)

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com





Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









2220Y0100392FCT Specifications

Manufacturer Part Number 2220Y0100392FCT Manufacturer Knowles Syfer Category Capacitors Package 2220 (5750 Metric) Series FlexiCap? Capacitance 3900pF Tolerance ±1% Voltage - Rated 10V Temperature Coefficient C0G, NP0 (1B) Operating Temperature -55°C ~ 125°C Features Soft Termination Ratings - Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 2220 (5750 Metric) Size / Dimension 0.224" L x 0.197" W (5.70mm x 5.00mm) Height - Seated (Max) - Thickness (Max) 0.165" (4.20mm) Lead Spacing - Lead Style -		
Category Capacitors Package 2220 (5750 Metric) Series FlexiCap? Capacitance 3900pF Tolerance ±1% Voltage - Rated 10V Temperature Coefficient C0G, NP0 (1B) Operating Temperature -55°C ~ 125°C Features Soft Termination Ratings - Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 2220 (5750 Metric) Size / Dimension 0.224" L x 0.197" W (5.70mm x 5.00mm) Height - Seated (Max) - Thickness (Max) 0.165" (4.20mm) Lead Spacing - Lead Style -	Manufacturer Part Number	2220Y0100392FCT
Package 2220 (5750 Metric) Series FlexiCap? Capacitance 3900pF Tolerance ±1% Voltage - Rated 10V Temperature Coefficient COG, NPO (1B) Operating Temperature -55°C ~ 125°C Features Soft Termination Ratings - Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 2220 (5750 Metric) Size / Dimension 0.224" L x 0.197" W (5.70mm x 5.00mm) Height - Seated (Max) - Thickness (Max) 0.165" (4.20mm) Lead Spacing - Lead Style -	Manufacturer	Knowles Syfer
Package 2220 (5750 Metric) Series FlexiCap? Capacitance 3900pF Tolerance ±1% Voltage - Rated 10V Temperature Coefficient C0G, NP0 (1B) Operating Temperature -55°C ~ 125°C Features Soft Termination Ratings - Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 2220 (5750 Metric) Size / Dimension 0.224" L x 0.197" W (5.70mm x 5.00mm) Height - Seated (Max) - Thickness (Max) 0.165" (4.20mm) Lead Spacing - Lead Style -	Category	Capacitors
Series FlexiCap? Capacitance 3900pF Tolerance ±1% Voltage - Rated 10V Temperature Coefficient C0G, NP0 (1B) Operating Temperature -55°C ~ 125°C Features Soft Termination Ratings - Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 2220 (5750 Metric) Size / Dimension 0.224" L x 0.197" W (5.70mm x 5.00mm) Height - Seated (Max) - Thickness (Max) 0.165" (4.20mm) Lead Spacing - Lead Style -		Ceramic Capacitors
Capacitance 3900pF Tolerance ±1% Voltage - Rated 10V Temperature Coefficient C0G, NP0 (1B) Operating Temperature -55°C ~ 125°C Features Soft Termination Ratings - Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 2220 (5750 Metric) Size / Dimension 0.224" L x 0.197" W (5.70mm x 5.00mm) Height - Seated (Max) - Thickness (Max) 0.165" (4.20mm) Lead Spacing - Lead Style -	Package	2220 (5750 Metric)
Tolerance ±1% Voltage - Rated 10V Temperature Coefficient COG, NPO (1B) Operating Temperature -55°C ~ 125°C Features Soft Termination Ratings - Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 2220 (5750 Metric) Size / Dimension 0.224" L x 0.197" W (5.70mm x 5.00mm) Height - Seated (Max) - Thickness (Max) 0.165" (4.20mm) Lead Spacing - Lead Style -	Series	FlexiCap?
Voltage - Rated10VTemperature CoefficientC0G, NP0 (1B)Operating Temperature-55°C ~ 125°CFeaturesSoft TerminationRatings-ApplicationsBoardflex SensitiveFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case2220 (5750 Metric)Size / Dimension0.224" L x 0.197" W (5.70mm x 5.00mm)Height - Seated (Max)-Thickness (Max)0.165" (4.20mm)Lead Spacing-Lead Style-	Capacitance	3900pF
Temperature Coefficient Operating Temperature -55°C ~ 125°C Features Soft Termination Ratings - Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 2220 (5750 Metric) Size / Dimension 0.224" L x 0.197" W (5.70mm x 5.00mm) Height - Seated (Max) Thickness (Max) 0.165" (4.20mm) Lead Spacing Lead Style -	Tolerance	±1%
Operating Temperature-55°C ~ 125°CFeaturesSoft TerminationRatings-ApplicationsBoardflex SensitiveFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case2220 (5750 Metric)Size / Dimension0.224" L x 0.197" W (5.70mm x 5.00mm)Height - Seated (Max)-Thickness (Max)0.165" (4.20mm)Lead Spacing-Lead Style-	Voltage - Rated	10V
Features Soft Termination Ratings Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 2220 (5750 Metric) Size / Dimension 0.224" L x 0.197" W (5.70mm x 5.00mm) Height - Seated (Max) - Thickness (Max) 0.165" (4.20mm) Lead Spacing - Lead Style -	Temperature Coefficient	C0G, NP0 (1B)
Ratings - Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 2220 (5750 Metric) Size / Dimension 0.224" L x 0.197" W (5.70mm x 5.00mm) Height - Seated (Max) - Thickness (Max) 0.165" (4.20mm) Lead Spacing - Lead Style	Operating Temperature	-55°C ~ 125°C
Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 2220 (5750 Metric) Size / Dimension 0.224" L x 0.197" W (5.70mm x 5.00mm) Height - Seated (Max) - Thickness (Max) 0.165" (4.20mm) Lead Spacing - Lead Style -	Features	Soft Termination
Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 2220 (5750 Metric) Size / Dimension 0.224" L x 0.197" W (5.70mm x 5.00mm) Height - Seated (Max) - Thickness (Max) 0.165" (4.20mm) Lead Spacing - Lead Style -	Ratings	-
Mounting Type Surface Mount, MLCC Package / Case 2220 (5750 Metric) Size / Dimension 0.224" L x 0.197" W (5.70mm x 5.00mm) Height - Seated (Max) - Thickness (Max) 0.165" (4.20mm) Lead Spacing - Lead Style -	Applications	Boardflex Sensitive
Package / Case 2220 (5750 Metric) Size / Dimension 0.224" L x 0.197" W (5.70mm x 5.00mm) Height - Seated (Max) - Thickness (Max) 0.165" (4.20mm) Lead Spacing - Lead Style -	Failure Rate	-
Size / Dimension 0.224" L x 0.197" W (5.70mm x 5.00mm) Height - Seated (Max) - Thickness (Max) 0.165" (4.20mm) Lead Spacing - Lead Style -	Mounting Type	Surface Mount, MLCC
Height - Seated (Max) Thickness (Max) Lead Spacing Lead Style - - - - - - - - - - - - -	Package / Case	2220 (5750 Metric)
Thickness (Max) 0.165" (4.20mm) Lead Spacing - Lead Style -	Size / Dimension	0.224" L x 0.197" W (5.70mm x 5.00mm)
Lead Spacing-Lead Style-	Height - Seated (Max)	-
Lead Style -	Thickness (Max)	0.165" (4.20mm)
	Lead Spacing	-
Report errors?	Lead Style	-
		Report errors?

2220Y0100392FCT Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

2220Y0100392FCT Payment Methods



















2220Y0100392FCT Shipping Methods













If you have any question about 2220Y0100392FCT, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com