



2220Y0160153KFT Information

Heisener.com

Part Number 2220Y0160153KFT Manufacturer Knowles Syfer

Category Capacitors
Ceramic Capacitors

Description CAP CER 0.015UF 16V C0G/NP0 2220

Package 2220 (5750 Metric)

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com

Request a Quote



Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









2220Y0160153KFT Specifications

Manufacturer Part Number 2220Y0160153KFT Manufacturer Knowles Syfer Category Capacitors Package 2220 (5750 Metric) Series FlexiCap? Capacitance 0.015µF Tolerance ±10% Voltage - Rated 16V Temperature Coefficient C0G, NPO Operating Temperature -55°C ~ 125°C Features Soft Termination, High Temperature Ratings - Applications High Reliability, Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 2220 (5750 Metric) Size / Dimension 0.224" L x 0.197" W (5.70mm x 5.00mm) Height - Seated (Max) - Thickness (Max) 0.098" (2.50mm)		
Category Capacitors Ceramic Capacitors Package 2220 (5750 Metric) Series FlexiCap? Capacitance 0.015µF Tolerance ±10% Voltage - Rated 16V Temperature Coefficient COG, NP0 Operating Temperature -55°C ~ 125°C Features Soft Termination, High Temperature Ratings - Applications High Reliability, Boardflex Sensitive Failure Rate Mounting Type Surface Mount, MLCC Package / Case 2220 (5750 Metric) Size / Dimension Height - Seated (Max) -	Manufacturer Part Number	2220Y0160153KFT
Package 2220 (5750 Metric) Series FlexiCap? Capacitance 0.015μF Tolerance ±10% Voltage - Rated 16V Temperature Coefficient C0G, NP0 Operating Temperature -55°C ~ 125°C Features Soft Termination, High Temperature Ratings - Applications High Reliability, Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 2220 (5750 Metric) Size / Dimension 0.224" L x 0.197" W (5.70mm x 5.00mm) Height - Seated (Max) -	Manufacturer	Knowles Syfer
Package2220 (5750 Metric)SeriesFlexiCap?Capacitance0.015μFTolerance±10%Voltage - Rated16VTemperature CoefficientC0G, NP0Operating Temperature-55°C ~ 125°CFeaturesSoft Termination, High TemperatureRatings-ApplicationsHigh Reliability, Boardflex SensitiveFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case2220 (5750 Metric)Size / Dimension0.224" L x 0.197" W (5.70mm x 5.00mm)Height - Seated (Max)-	Category	Capacitors
SeriesFlexiCap?Capacitance $0.015μF$ Tolerance $±10%$ Voltage - Rated $16V$ Temperature Coefficient $C0G$, NP0Operating Temperature $-55°C \sim 125°C$ FeaturesSoft Termination, High TemperatureRatings-ApplicationsHigh Reliability, Boardflex SensitiveFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case 2220 (5750 Metric)Size / Dimension $0.224"$ L x $0.197"$ W (5.70mm x 5.00mm)Height - Seated (Max)-		Ceramic Capacitors
Capacitance0.015μFTolerance±10%Voltage - Rated16VTemperature CoefficientCOG, NPOOperating Temperature-55°C ~ 125°CFeaturesSoft Termination, High TemperatureRatings-ApplicationsHigh Reliability, Boardflex SensitiveFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case2220 (5750 Metric)Size / Dimension0.224" L x 0.197" W (5.70mm x 5.00mm)Height - Seated (Max)-	Package	2220 (5750 Metric)
Tolerance ±10% Voltage - Rated 16V Temperature Coefficient C0G, NP0 Operating Temperature -55°C ~ 125°C Features Soft Termination, High Temperature Ratings - Applications High Reliability, Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 2220 (5750 Metric) Size / Dimension 0.224" L x 0.197" W (5.70mm x 5.00mm) Height - Seated (Max) -	Series	FlexiCap?
Voltage - Rated Temperature Coefficient COG, NP0 Operating Temperature -55°C ~ 125°C Features Soft Termination, High Temperature Ratings - Applications High Reliability, Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 2220 (5750 Metric) Size / Dimension Height - Seated (Max) -	Capacitance	0.015μF
Temperature Coefficient Operating Temperature -55°C ~ 125°C Features Soft Termination, High Temperature Ratings - Applications High Reliability, Boardflex Sensitive Failure Rate Mounting Type Surface Mount, MLCC Package / Case 2220 (5750 Metric) Size / Dimension Height - Seated (Max) - COG, NPO COG, NPO COG, NPO Soft Termination, High Temperature 1025°C Soft Termination, High Temperature 225°C Soft Termination, High Temperature 225°C Soft Termination, High Temperature 226°C Soft Termination, High Temperature 227°C Soft Termination, High Temperature 228°C Soft Temperature 228°C	Tolerance	$\pm 10\%$
Operating Temperature -55°C ~ 125°C Features Soft Termination, High Temperature Ratings - Applications High Reliability, Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 2220 (5750 Metric) Size / Dimension 0.224" L x 0.197" W (5.70mm x 5.00mm) Height - Seated (Max) -	Voltage - Rated	16V
Features Soft Termination, High Temperature Ratings - Applications High Reliability, Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 2220 (5750 Metric) Size / Dimension 0.224" L x 0.197" W (5.70mm x 5.00mm) Height - Seated (Max) -	Temperature Coefficient	COG, NPO
Ratings - Applications High Reliability, Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 2220 (5750 Metric) Size / Dimension 0.224" L x 0.197" W (5.70mm x 5.00mm) Height - Seated (Max) -	Operating Temperature	-55°C ~ 125°C
Applications High Reliability, Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 2220 (5750 Metric) Size / Dimension 0.224" L x 0.197" W (5.70mm x 5.00mm) Height - Seated (Max) -	Features	Soft Termination, High Temperature
Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 2220 (5750 Metric) Size / Dimension 0.224" L x 0.197" W (5.70mm x 5.00mm) Height - Seated (Max) -	Ratings	-
Mounting Type Surface Mount, MLCC Package / Case 2220 (5750 Metric) Size / Dimension 0.224" L x 0.197" W (5.70mm x 5.00mm) Height - Seated (Max) -	Applications	High Reliability, Boardflex Sensitive
Package / Case 2220 (5750 Metric) Size / Dimension 0.224" L x 0.197" W (5.70mm x 5.00mm) Height - Seated (Max) -	Failure Rate	-
Size / Dimension 0.224" L x 0.197" W (5.70mm x 5.00mm) Height - Seated (Max) -	Mounting Type	Surface Mount, MLCC
Height - Seated (Max)	Package / Case	2220 (5750 Metric)
-	Size / Dimension	0.224" L x 0.197" W (5.70mm x 5.00mm)
Thickness (Max) 0.098" (2.50mm)	Height - Seated (Max)	-
1111exties5 (11111)	Thickness (Max)	0.098" (2.50mm)
Lead Spacing -	Lead Spacing	-
Lead Style -	Lead Style	-
Report errors?		Report errors?

2220Y0160153KFT Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

2220Y0160153KFT Payment Methods



















2220Y0160153KFT Shipping Methods













If you have any question about 2220Y0160153KFT, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com