



2220Y0630683GFT Information

Heisener.com

For Reference Only

Manufact Category 2220Y0630683GFT

Manufacturer Knowles Syfer

Part Number

Capacitors
Ceramic Capacitors

Description CAP CER 0.068UF 63V C0G/NP0 2220

Package 2220 (5750 Metric)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









2220Y0630683GFT Specifications

Manufacturer Part Number 2220Y0630683GFT Manufacturer Knowles Syfer Category Capacitors Package 2220 (5750 Metric) Series FlexiCap? Capacitance 0.068µF Tolerance ±2% Voltage - Rated 63V Temperature Coefficient C0G, NPO Operating Temperature -55°C ~ 125°C Features Soft Termination, High Temperature Ratings - Applications High Reliability, Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 2220 (5750 Metric) Size / Dimension 0.224" L x 0.197" W (5.70mm x 5.00mm) Height - Seated (Max) - Thickness (Max) 0.098" (2.50mm) Lead Spacing - Lead Style -		
Category Capacitors Package 2220 (5750 Metric) Series FlexiCap? Capacitance 0.068µF Tolerance ±2% Voltage - Rated 63V Temperature Coefficient C0G, NPO Operating Temperature -55°C ~ 125°C Features Soft Termination, High Temperature Ratings - Applications High Reliability, Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 2220 (5750 Metric) Size / Dimension 0.224" L x 0.197" W (5.70mm x 5.00mm) Height - Seated (Max) - Thickness (Max) 0.098" (2.50mm) Lead Spacing - Lead Style -	Manufacturer Part Number	2220Y0630683GFT
Package 2220 (5750 Metric) Series FlexiCap? Capacitance 0.068μF Tolerance ±2% Voltage - Rated 63V Temperature Coefficient COG, NPO Operating Temperature -55°C ~ 125°C Features Soft Termination, High Temperature Ratings - Applications High Reliability, Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 2220 (5750 Metric) Size / Dimension 0.224" L x 0.197" W (5.70mm x 5.00mm) Height - Seated (Max) - Thickness (Max) 0.098" (2.50mm) Lead Spacing - Lead Style -	Manufacturer	Knowles Syfer
Package 2220 (5750 Metric) Series FlexiCap? Capacitance 0.068µF Tolerance ±2% Voltage - Rated 63V Temperature Coefficient C0G, NPO Operating Temperature -55°C ~ 125°C Features Soft Termination, High Temperature Ratings - Applications High Reliability, Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 2220 (5750 Metric) Size / Dimension 0.224" L x 0.197" W (5.70mm x 5.00mm) Height - Seated (Max) - Thickness (Max) 0.098" (2.50mm) Lead Spacing - Lead Style -	Category	Capacitors
Series FlexiCap? Capacitance 0.068µF Tolerance ±2% Voltage - Rated 63V Temperature Coefficient C0G, NP0 Operating Temperature -55°C ~ 125°C Features Soft Termination, High Temperature Ratings - Applications High Reliability, Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 2220 (5750 Metric) Size / Dimension 0.224" L x 0.197" W (5.70mm x 5.00mm) Height - Seated (Max) - Thickness (Max) 0.098" (2.50mm) Lead Spacing - Lead Style -		Ceramic Capacitors
Capacitance 0.068μF Tolerance ±2% Voltage - Rated 63V Temperature Coefficient C0G, NP0 Operating Temperature -55°C ~ 125°C Features Soft Termination, High Temperature Ratings - Applications High Reliability, Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 2220 (5750 Metric) Size / Dimension 0.224" L x 0.197" W (5.70mm x 5.00mm) Height - Seated (Max) - Thickness (Max) 0.098" (2.50mm) Lead Spacing - Lead Style -	Package	2220 (5750 Metric)
Tolerance ±2% Voltage - Rated 63V Temperature Coefficient C0G, NP0 Operating Temperature -55°C ~ 125°C Features Soft Termination, High Temperature Ratings - Applications High Reliability, Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 2220 (5750 Metric) Size / Dimension 0.224" L x 0.197" W (5.70mm x 5.00mm) Height - Seated (Max) - Thickness (Max) 0.098" (2.50mm) Lead Spacing - Lead Style -	Series	FlexiCap?
Voltage - Rated63 VTemperature CoefficientC0G, NP0Operating Temperature-55°C ~ 125°CFeaturesSoft Termination, High TemperatureRatings-ApplicationsHigh Reliability, Boardflex SensitiveFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case2220 (5750 Metric)Size / Dimension0.224" L x 0.197" W (5.70mm x 5.00mm)Height - Seated (Max)-Thickness (Max)0.098" (2.50mm)Lead Spacing-Lead Style-	Capacitance	0.068μF
Temperature CoefficientCOG, NPOOperating Temperature-55°C ~ 125°CFeaturesSoft Termination, High TemperatureRatings-ApplicationsHigh Reliability, Boardflex SensitiveFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case2220 (5750 Metric)Size / Dimension0.224" L x 0.197" W (5.70mm x 5.00mm)Height - Seated (Max)-Thickness (Max)0.098" (2.50mm)Lead Spacing-Lead Style-	Tolerance	±2%
Operating Temperature-55°C ~ 125°CFeaturesSoft Termination, High TemperatureRatings-ApplicationsHigh Reliability, Boardflex SensitiveFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case2220 (5750 Metric)Size / Dimension0.224" L x 0.197" W (5.70mm x 5.00mm)Height - Seated (Max)-Thickness (Max)0.098" (2.50mm)Lead Spacing-Lead Style-	Voltage - Rated	63V
Features Ratings - Applications High Reliability, Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 2220 (5750 Metric) Size / Dimension 0.224" L x 0.197" W (5.70mm x 5.00mm) Height - Seated (Max) - Thickness (Max) 0.098" (2.50mm) Lead Spacing - Lead Style -	Temperature Coefficient	C0G, NP0
Ratings - High Reliability, Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 2220 (5750 Metric) Size / Dimension 0.224" L x 0.197" W (5.70mm x 5.00mm) Height - Seated (Max) - Thickness (Max) 0.098" (2.50mm) Lead Spacing - Lead Style	Operating Temperature	-55°C ~ 125°C
Applications High Reliability, Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 2220 (5750 Metric) Size / Dimension 0.224" L x 0.197" W (5.70mm x 5.00mm) Height - Seated (Max) - Thickness (Max) 0.098" (2.50mm) Lead Spacing - Lead Style -	Features	Soft Termination, High Temperature
Failure Rate Mounting Type Surface Mount, MLCC Package / Case 2220 (5750 Metric) Size / Dimension 0.224" L x 0.197" W (5.70mm x 5.00mm) Height - Seated (Max) - Thickness (Max) 0.098" (2.50mm) Lead Spacing - Lead Style -	Ratings	-
Mounting Type Surface Mount, MLCC Package / Case 2220 (5750 Metric) Size / Dimension 0.224" L x 0.197" W (5.70mm x 5.00mm) Height - Seated (Max) - Thickness (Max) 0.098" (2.50mm) Lead Spacing - Lead Style -	Applications	High Reliability, Boardflex Sensitive
Package / Case 2220 (5750 Metric) Size / Dimension 0.224" L x 0.197" W (5.70mm x 5.00mm) Height - Seated (Max) - Thickness (Max) 0.098" (2.50mm) Lead Spacing - Lead Style -	Failure Rate	-
Size / Dimension 0.224" L x 0.197" W (5.70mm x 5.00mm) Height - Seated (Max) - Thickness (Max) 0.098" (2.50mm) Lead Spacing - Lead Style -	Mounting Type	Surface Mount, MLCC
Height - Seated (Max) Thickness (Max) Lead Spacing Lead Style - - - - - - - - - - - - -	Package / Case	2220 (5750 Metric)
Thickness (Max) 0.098" (2.50mm) Lead Spacing - Lead Style -	Size / Dimension	0.224" L x 0.197" W (5.70mm x 5.00mm)
Lead Spacing-Lead Style-	Height - Seated (Max)	-
Lead Style -	Thickness (Max)	0.098" (2.50mm)
	Lead Spacing	-
Report errors?	Lead Style	-
		Report errors?

2220Y0630683GFT Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

2220Y0630683GFT Payment Methods





















2220Y0630683GFT Shipping Methods













If you have any question about 2220Y0630683GFT, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com