



2220Y1000222FFR Information

Heisener.com

Part Number 2220Y1000222FFR
Manufacturer Knowles Syfer
Category Capacitors

Ceramic Capacitors

Description CAP CER 2200PF 100V C0G/NP0 2220

Package 2220 (5750 Metric)


For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com





Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









| Manufacturer Part Number 2220Y1000222FFR Manufacturer Knowles Syfer Category Capacitors Package 2220 (5750 Metric) Series FlexiCap? Capacitance 2200pF Tolerance ±1% Voltage - Rated 100V Temperature Coefficient COG, NPO Operating Temperature -55°C ~ 125°C Features Soft Termination, High Temperature Ratings - Applications High Reliability, Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 2220 (5750 Metric) Size / Dimension 0.224" L x 0.197" W (5.70mm x 5.00mm) | | |
|---|--------------------------|---------------------------------------|
| Category Capacitors Package 2220 (5750 Metric) Series FlexiCap? Capacitance 2200pF Tolerance ±1% Voltage - Rated 100V Temperature Coefficient C0G, NP0 Operating Temperature -55°C ~ 125°C Features Soft Termination, High Temperature Ratings - Applications High Reliability, Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 2220 (5750 Metric) | Manufacturer Part Number | 2220Y1000222FFR |
| Ceramic CapacitorsPackage2220 (5750 Metric)SeriesFlexiCap?Capacitance2200pFTolerance±1%Voltage - Rated100VTemperature CoefficientC0G, NP0Operating Temperature-55°C ~ 125°CFeaturesSoft Termination, High TemperatureRatings-ApplicationsHigh Reliability, Boardflex SensitiveFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case2220 (5750 Metric) | Manufacturer | Knowles Syfer |
| Package 2220 (5750 Metric) Series FlexiCap? Capacitance 2200pF Tolerance ±1% Voltage - Rated 100V Temperature Coefficient COG, NPO Operating Temperature -55°C ~ 125°C Features Soft Termination, High Temperature Ratings - Applications High Reliability, Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 2220 (5750 Metric) | Category | Capacitors |
| SeriesFlexiCap?Capacitance2200pFTolerance±1%Voltage - Rated100VTemperature CoefficientC0G, NP0Operating Temperature-55°C ~ 125°CFeaturesSoft Termination, High TemperatureRatings-ApplicationsHigh Reliability, Boardflex SensitiveFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case2220 (5750 Metric) | | Ceramic Capacitors |
| Capacitance 2200pF Tolerance ±1% Voltage - Rated 100V Temperature Coefficient C0G, NP0 Operating Temperature -55°C ~ 125°C Features Soft Termination, High Temperature Ratings - Applications High Reliability, Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 2220 (5750 Metric) | Package | 2220 (5750 Metric) |
| Tolerance ±1% Voltage - Rated 100V Temperature Coefficient C0G, NP0 Operating Temperature -55°C ~ 125°C Features Soft Termination, High Temperature Ratings - Applications High Reliability, Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 2220 (5750 Metric) | Series | FlexiCap? |
| Voltage - Rated 100V Temperature Coefficient C0G, NP0 Operating Temperature -55°C ~ 125°C Features Soft Termination, High Temperature Ratings - Applications High Reliability, Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 2220 (5750 Metric) | Capacitance | 2200pF |
| Temperature Coefficient COG, NPO Operating Temperature -55°C ~ 125°C Features Soft Termination, High Temperature Ratings - Applications High Reliability, Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 2220 (5750 Metric) | Tolerance | $\pm 1\%$ |
| Operating Temperature -55°C ~ 125°C Features Soft Termination, High Temperature Ratings - Applications High Reliability, Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 2220 (5750 Metric) | Voltage - Rated | 100V |
| Features Soft Termination, High Temperature Ratings - Applications High Reliability, Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 2220 (5750 Metric) | Temperature Coefficient | C0G, NP0 |
| Ratings - Applications High Reliability, Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 2220 (5750 Metric) | Operating Temperature | -55°C ~ 125°C |
| Applications High Reliability, Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 2220 (5750 Metric) | Features | Soft Termination, High Temperature |
| Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 2220 (5750 Metric) | Ratings | - |
| Mounting Type Surface Mount, MLCC Package / Case 2220 (5750 Metric) | Applications | High Reliability, Boardflex Sensitive |
| Package / Case 2220 (5750 Metric) | Failure Rate | - |
| | Mounting Type | Surface Mount, MLCC |
| Size / Dimension 0.224" L x 0.197" W (5.70mm x 5.00mm) | Package / Case | 2220 (5750 Metric) |
| | Size / Dimension | 0.224" L x 0.197" W (5.70mm x 5.00mm) |
| Height - Seated (Max) - | Height - Seated (Max) | - |
| Thickness (Max) 0.098" (2.50mm) | Thickness (Max) | 0.098" (2.50mm) |
| Lead Spacing - | Lead Spacing | - |
| Lead Style - | Lead Style | - |
| Report errors? | | Report errors? |

2220Y1000222FFR Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

2220Y1000222FFR Payment Methods



















2220Y1000222FFR Shipping Methods













If you have any question about 2220Y1000222FFR, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com