



### 2220Y1000274JDT Information

Heisener.com

Part Number2220Y1000274JDTManufacturerKnowles Syfer

Category Capacitors
Ceramic Capacitors

**Description** CAP CER 0.27UF 100V X7R 2220

**Package** 2220 (5750 Metric)

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
F-mail: salesdent@heisener.com

E-mail: salesdept@heisener.com



Request a Quote

### **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# 2220Y1000274JDT Specifications

Manufacturer Part Number2220Y1000274JDTManufacturerKnowles SyferCategoryCapacitorsPackageCeramic CapacitorsPackage2220 (5750 Metric)SeriesFlexiCap?Capacitance0.27μFTolerance±5%Voltage - Rated100VTemperature CoefficientX7R (2R1)Operating Temperature-55°C ~ 125°C	
Category  Capacitors  Ceramic Capacitors  Package  2220 (5750 Metric)  Series  FlexiCap?  Capacitance  0.27 $\mu$ F  Tolerance $\pm 5\%$ Voltage - Rated  100V  Temperature Coefficient  X7R (2R1)  Operating Temperature  -55°C ~ 125°C	
Ceramic CapacitorsPackage2220 (5750 Metric)SeriesFlexiCap?Capacitance $0.27μF$ Tolerance $±5%$ Voltage - Rated $100V$ Temperature Coefficient $X7R$ (2R1)Operating Temperature $-55°C \sim 125°C$	
Package $2220 (5750 \text{ Metric})$ SeriesFlexiCap?Capacitance $0.27\mu\text{F}$ Tolerance $\pm 5\%$ Voltage - Rated $100\text{V}$ Temperature CoefficientX7R (2R1)Operating Temperature $-55^{\circ}\text{C} \sim 125^{\circ}\text{C}$	
Series FlexiCap?  Capacitance $0.27\mu\text{F}$ Tolerance $\pm 5\%$ Voltage - Rated $100\text{V}$ Temperature Coefficient $X7R$ (2R1)  Operating Temperature $-55^{\circ}\text{C} \sim 125^{\circ}\text{C}$	
Capacitance $0.27\mu F$ Tolerance $\pm 5\%$ Voltage - Rated $100V$ Temperature Coefficient $X7R$ (2R1)  Operating Temperature $-55^{\circ}C \sim 125^{\circ}C$	
Tolerance $\pm 5\%$ Voltage - Rated $100V$ Temperature Coefficient $X7R$ (2R1)  Operating Temperature $-55^{\circ}C \sim 125^{\circ}C$	
Voltage - Rated $100V$ Temperature Coefficient $X7R$ (2R1)Operating Temperature $-55^{\circ}C \sim 125^{\circ}C$	
Temperature Coefficient $X7R (2R1)$ Operating Temperature $-55^{\circ}C \sim 125^{\circ}C$	
Operating Temperature $-55^{\circ}\text{C} \sim 125^{\circ}\text{C}$	
7 0 m 1 1 77 1 m	
Features Soft Termination, High Temperature	
Ratings -	
Applications High Reliability, Boardflex Sensitive	
Failure Rate -	
Mounting Type Surface Mount, MLCC	
Package / Case 2220 (5750 Metric)	
Size / Dimension 0.224" L x 0.197" W (5.70mm x 5.00mm)	
Height - Seated (Max)	
Thickness (Max) 0.098" (2.50mm)	
Lead Spacing -	
Lead Style -	
Report er	rors?

### 2220Y1000274JDT Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### 2220Y1000274JDT Payment Methods



















## 2220Y1000274JDT Shipping Methods













If you have any question about 2220Y1000274JDT, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com