



2220Y2000153JFT Information

Heisener.com

2220Y2000153JFT Part Number Manufacturer Knowles Syfer Category Capacitors

Ceramic Capacitors

Description CAP CER 0.015UF 200V C0G 2220

2220 (5750 Metric) **Package**

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









2220Y2000153JFT Specifications

Manufacturer Part Number2220Y2000153JFTManufacturerKnowles SyferCategoryCapacitorsPackage2220 (5750 Metric)SeriesFlexiCap?Capacitance0.015μFTolerance±5%Voltage - Rated200VTemperature CoefficientCOG, NP0Operating Temperature-55°C ~ 125°CFeaturesSoft Termination, High TemperatureRatings-ApplicationsHigh Reliability, Boardflex SensitiveFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case2220 (5750 Metric)
Category Capacitors Package 2220 (5750 Metric) Series FlexiCap? Capacitance 0.015μF Tolerance ±5% Voltage - Rated 200V Temperature Coefficient C0G, NPO Operating Temperature -55°C ~ 125°C Features Soft Termination, High Temperature Ratings - Applications High Reliability, Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC
Ceramic CapacitorsPackage2220 (5750 Metric)SeriesFlexiCap?Capacitance0.015μFTolerance±5%Voltage - Rated200VTemperature CoefficientC0G, NP0Operating Temperature-55°C ~ 125°CFeaturesSoft Termination, High TemperatureRatings-ApplicationsHigh Reliability, Boardflex SensitiveFailure Rate-Mounting TypeSurface Mount, MLCC
Package $2220 (5750 \text{Metric})$ SeriesFlexiCap?Capacitance $0.015 \mu \text{F}$ Tolerance $\pm 5\%$ Voltage - Rated 200V Temperature Coefficient $C0G, \text{NP0}$ Operating Temperature $-55^{\circ}\text{C} \sim 125^{\circ}\text{C}$ FeaturesSoft Termination, High TemperatureRatings-ApplicationsHigh Reliability, Boardflex SensitiveFailure Rate-Mounting TypeSurface Mount, MLCC
SeriesFlexiCap?Capacitance $0.015\mu F$ Tolerance $\pm 5\%$ Voltage - Rated $200V$ Temperature Coefficient $C0G, NPO$ Operating Temperature $-55^{\circ}C \sim 125^{\circ}C$ FeaturesSoft Termination, High TemperatureRatings-ApplicationsHigh Reliability, Boardflex SensitiveFailure Rate-Mounting TypeSurface Mount, MLCC
Capacitance 0.015µF Tolerance ±5% Voltage - Rated 200V Temperature Coefficient COG, NP0 Operating Temperature -55°C ~ 125°C Features Soft Termination, High Temperature Ratings - Applications High Reliability, Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC
Tolerance ±5% Voltage - Rated 200V Temperature Coefficient COG, NP0 Operating Temperature -55°C ~ 125°C Features Soft Termination, High Temperature Ratings - Applications High Reliability, Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC
Voltage - Rated200VTemperature CoefficientC0G, NP0Operating Temperature-55°C ~ 125°CFeaturesSoft Termination, High TemperatureRatings-ApplicationsHigh Reliability, Boardflex SensitiveFailure Rate-Mounting TypeSurface Mount, MLCC
Temperature Coefficient COG, NPO Operating Temperature -55°C ~ 125°C Features Soft Termination, High Temperature Ratings - Applications High Reliability, Boardflex Sensitive Failure Rate Mounting Type Surface Mount, MLCC
Operating Temperature -55°C ~ 125°C Soft Termination, High Temperature Ratings - Applications High Reliability, Boardflex Sensitive Failure Rate Mounting Type Surface Mount, MLCC
Features Soft Termination, High Temperature Ratings - Applications High Reliability, Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC
Ratings - Applications High Reliability, Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC
Applications High Reliability, Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC
Failure Rate - Mounting Type Surface Mount, MLCC
Mounting Type Surface Mount, MLCC
Pagkaga / Casa 2220 (5750 Matria)
rackage / Case 2220 (5/30 Metric)
Size / Dimension 0.224" L x 0.197" W (5.70mm x 5.00mm)
Height - Seated (Max)
Thickness (Max) 0.098" (2.50mm)
Lead Spacing -
Lead Style -
Report errors

2220Y2000153JFT Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

2220Y2000153JFT Payment Methods



















2220Y2000153JFT Shipping Methods













If you have any question about 2220Y2000153JFT, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com