



### 2220Y2000331KFT Information

Heisener.com

2220Y2000331KFT Part Number Manufacturer Knowles Syfer

Category Capacitors Ceramic Capacitors

**Description** CAP CER 330PF 200V C0G/NP0 2220

2220 (5750 Metric) **Package** 

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

### **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# 2220Y2000331KFT Specifications

Manufacturer Part Number2220Y2000331KFTManufacturerKnowles SyferCategoryCapacitorsPackage2220 (5750 Metric)SeriesFlexiCap?Capacitance330pFTolerance±10%Voltage - Rated200VTemperature CoefficientC0G, NP0Operating Temperature-55°C ~ 125°CFeaturesSoft Termination, High TemperatureRatings-ApplicationsHigh Reliability, Boardflex SensitiveFailure Rate-		
Category Capacitors  Package 2220 (5750 Metric) Series FlexiCap? Capacitance 330pF Tolerance ±10% Voltage - Rated 200V Temperature Coefficient Cog, NP0 Operating Temperature -55°C ~ 125°C Features Soft Termination, High Temperature Ratings - Applications High Reliability, Boardflex Sensitive Failure Rate -	Manufacturer Part Number	2220Y2000331KFT
PackageCeramic CapacitorsPackage2220 (5750 Metric)SeriesFlexiCap?Capacitance330pFTolerance±10%Voltage - Rated200VTemperature CoefficientC0G, NP0Operating Temperature-55°C ~ 125°CFeaturesSoft Termination, High TemperatureRatings-ApplicationsHigh Reliability, Boardflex SensitiveFailure Rate-	Manufacturer	Knowles Syfer
Package2220 (5750 Metric)SeriesFlexiCap?Capacitance330pFTolerance±10%Voltage - Rated200VTemperature CoefficientC0G, NP0Operating Temperature-55°C ~ 125°CFeaturesSoft Termination, High TemperatureRatings-ApplicationsHigh Reliability, Boardflex SensitiveFailure Rate-	Category	Capacitors
SeriesFlexiCap?Capacitance330pFTolerance±10%Voltage - Rated200VTemperature CoefficientC0G, NP0Operating Temperature-55°C ~ 125°CFeaturesSoft Termination, High TemperatureRatings-ApplicationsHigh Reliability, Boardflex SensitiveFailure Rate-		Ceramic Capacitors
Capacitance $330pF$ Tolerance $\pm 10\%$ Voltage - Rated $200V$ Temperature Coefficient $C0G, NP0$ Operating Temperature $-55^{\circ}C \sim 125^{\circ}C$ FeaturesSoft Termination, High TemperatureRatings-ApplicationsHigh Reliability, Boardflex SensitiveFailure Rate-	Package	2220 (5750 Metric)
Tolerance ±10%  Voltage - Rated 200V  Temperature Coefficient COG, NP0  Operating Temperature -55°C ~ 125°C  Features Soft Termination, High Temperature  Ratings -  Applications High Reliability, Boardflex Sensitive  Failure Rate -	Series	FlexiCap?
Voltage - Rated200VTemperature CoefficientC0G, NP0Operating Temperature-55°C ~ 125°CFeaturesSoft Termination, High TemperatureRatings-ApplicationsHigh Reliability, Boardflex SensitiveFailure Rate-	Capacitance	330pF
Temperature Coefficient  COG, NP0  Operating Temperature  -55°C ~ 125°C  Features  Soft Termination, High Temperature  Ratings  -  Applications  High Reliability, Boardflex Sensitive  Failure Rate  -	Tolerance	±10%
Operating Temperature -55°C ~ 125°C  Features Soft Termination, High Temperature  Ratings -  Applications High Reliability, Boardflex Sensitive  Failure Rate -	Voltage - Rated	200V
Features Soft Termination, High Temperature Ratings - Applications High Reliability, Boardflex Sensitive Failure Rate -	Temperature Coefficient	C0G, NP0
Ratings - Applications High Reliability, Boardflex Sensitive Failure Rate -	Operating Temperature	-55°C ~ 125°C
Applications High Reliability, Boardflex Sensitive Failure Rate -	Features	Soft Termination, High Temperature
Failure Rate -	Ratings	-
	Applications	High Reliability, Boardflex Sensitive
	Failure Rate	-
Mounting Type Surface Mount, MLCC	Mounting Type	Surface Mount, MLCC
Package / Case 2220 (5750 Metric)	Package / Case	2220 (5750 Metric)
Size / Dimension 0.224" L x 0.197" W (5.70mm x 5.00mm)	Size / Dimension	0.224" L x 0.197" W (5.70mm x 5.00mm)
Height - Seated (Max)	Height - Seated (Max)	-
Thickness (Max) 0.098" (2.50mm)	Thickness (Max)	0.098" (2.50mm)
Lead Spacing -	Lead Spacing	-
Lead Style -	Lead Style	-
Report errors?		Report errors?

#### 2220Y2000331KFT Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### 2220Y2000331KFT Payment Methods



















## 2220Y2000331KFT Shipping Methods













If you have any question about 2220Y2000331KFT, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com