



### 223MKP275KB Information



For Reference Only

Part Number 223MKP275KB
Manufacturer Illinois Capacitor
Category Capacitors
Film Capacitors

**Description** CAP FILM 0.022UF 10% 310VAC RAD

Package Radial

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# 223MKP275KB Specifications

Manufacturer Part Number         223MKP275KB           Manufacturer         Illinois Capacitor           Category         Capacitors           Package         Radial           Series         MKP           Capacitance         0.022μF           Tolerance         ±10%           Voltage Rating - AC         310V           Voltage Rating - DC         -           Dielectric Material         Polypropylene (PP), Metallized           ESR (Equivalent Series Resistance)         -           Operating Temperature         -40°C ~ 110°C           Mounting Type         Through Hole           Package / Case         Radial           Size / Dimension         0.709" L x 0.157" W (18.00mm x 4.00mm)           Height - Seated (Max)         0.366" (9.30mm)           Termination         PC Pins           Lead Spacing         0.591" (15.00mm)           Applications         EMI, RFI Suppression           Features         X2 Safety Rated	•	
Category         Capacitors           Film Capacitors           Package         Radial           Series         MKP           Capacitance         0.022µF           Tolerance         ±10%           Voltage Rating - AC         310V           Voltage Rating - DC         -           Dielectric Material         Polypropylene (PP), Metallized           ESR (Equivalent Series Resistance)         -           Operating Temperature         -40°C ~ 110°C           Mounting Type         Through Hole           Package / Case         Radial           Size / Dimension         0.709" L x 0.157" W (18.00mm x 4.00mm)           Height - Seated (Max)         0.366" (9.30mm)           Termination         PC Pins           Lead Spacing         0.591" (15.00mm)           Applications         EMI, RFI Suppression           Features         X2 Safety Rated	Manufacturer Part Number	223MKP275KB
Package         Radial           Series         MKP           Capacitance         0.022µF           Tolerance         ±10%           Voltage Rating - AC         310V           Voltage Rating - DC         -           Dielectric Material         Polypropylene (PP), Metallized           ESR (Equivalent Series Resistance)         -           Operating Temperature         -40°C ~ 110°C           Mounting Type         Through Hole           Package / Case         Radial           Size / Dimension         0.709" L x 0.157" W (18.00mm x 4.00mm)           Height - Seated (Max)         0.366" (9.30mm)           Termination         PC Pins           Lead Spacing         0.591" (15.00mm)           Applications         EMI, RFI Suppression           Features         X2 Safety Rated	Manufacturer	Illinois Capacitor
PackageRadialSeriesMKPCapacitance0.022μFTolerance±10%Voltage Rating - AC310VVoltage Rating - DC-Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-40°C ~ 110°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.709" L x 0.157" W (18.00mm x 4.00mm)Height - Seated (Max)0.366" (9.30mm)TerminationPC PinsLead Spacing0.591" (15.00mm)ApplicationsEMI, RFI SuppressionFeaturesX2 Safety Rated	Category	Capacitors
Series         MKP           Capacitance         0.022µF           Tolerance         ±10%           Voltage Rating - AC         310V           Voltage Rating - DC         -           Dielectric Material         Polypropylene (PP), Metallized           ESR (Equivalent Series Resistance)         -           Operating Temperature         -40°C ~ 110°C           Mounting Type         Through Hole           Package / Case         Radial           Size / Dimension         0.709" L x 0.157" W (18.00mm x 4.00mm)           Height - Seated (Max)         0.366" (9.30mm)           Termination         PC Pins           Lead Spacing         0.591" (15.00mm)           Applications         EMI, RFI Suppression           Features         X2 Safety Rated		Film Capacitors
Capacitance $0.022μF$ Tolerance $\pm 10\%$ Voltage Rating - AC $310V$ Voltage Rating - DC-Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature $-40^{\circ}$ C ~ $110^{\circ}$ CMounting TypeThrough HolePackage / CaseRadialSize / Dimension $0.709^{\circ}$ L x $0.157^{\circ}$ W $(18.00mm x 4.00mm)$ Height - Seated (Max) $0.366^{\circ}$ ( $9.30mm$ )TerminationPC PinsLead Spacing $0.591^{\circ}$ ( $15.00mm$ )ApplicationsEMI, RFI SuppressionFeaturesX2 Safety Rated	Package	Radial
Tolerance ±10%  Voltage Rating - AC 310V  Voltage Rating - DC -  Dielectric Material Polypropylene (PP), Metallized  ESR (Equivalent Series Resistance) -  Operating Temperature -40°C ~ 110°C  Mounting Type Through Hole  Package / Case Radial  Size / Dimension 0.709" L x 0.157" W (18.00mm x 4.00mm)  Height - Seated (Max) 0.366" (9.30mm)  Termination PC Pins  Lead Spacing 0.591" (15.00mm)  Applications EMI, RFI Suppression  Features X2 Safety Rated	Series	MKP
Voltage Rating - AC  Voltage Rating - DC  Dielectric Material  ESR (Equivalent Series Resistance)  Operating Temperature  -40°C ~ 110°C  Mounting Type  Through Hole  Package / Case  Radial  Size / Dimension  Height - Seated (Max)  Termination  Derating Temperature  Applications  EMI, RFI Suppression  Features  310V  310V  310V  310V  310V  400  -40°C ~ 110°C  Apolypropylene (PP), Metallized  -40°C ~ 110°C  40°C ~ 110°C	Capacitance	0.022μF
Voltage Rating - DC Dielectric Material Polypropylene (PP), Metallized  ESR (Equivalent Series Resistance) - Operating Temperature -40°C ~ 110°C Mounting Type Through Hole Package / Case Radial Size / Dimension 0.709" L x 0.157" W (18.00mm x 4.00mm) Height - Seated (Max) 0.366" (9.30mm)  Termination PC Pins Lead Spacing 0.591" (15.00mm)  Applications EMI, RFI Suppression Features X2 Safety Rated	Tolerance	±10%
Dielectric Material Polypropylene (PP), Metallized  ESR (Equivalent Series Resistance)  Operating Temperature  -40°C ~ 110°C  Mounting Type Through Hole  Package / Case Radial  Size / Dimension  0.709" L x 0.157" W (18.00mm x 4.00mm)  Height - Seated (Max)  0.366" (9.30mm)  Termination  PC Pins  Lead Spacing  0.591" (15.00mm)  Applications  EMI, RFI Suppression  Features  X2 Safety Rated	Voltage Rating - AC	310V
ESR (Equivalent Series Resistance)  Operating Temperature  -40°C ~ 110°C  Mounting Type  Through Hole  Package / Case  Radial  Size / Dimension  0.709" L x 0.157" W (18.00mm x 4.00mm)  Height - Seated (Max)  Termination  PC Pins  Lead Spacing  0.591" (15.00mm)  Applications  EMI, RFI Suppression  Features  X2 Safety Rated	Voltage Rating - DC	-
Operating Temperature  -40°C ~ 110°C  Mounting Type  Through Hole  Package / Case  Radial  Size / Dimension  0.709" L x 0.157" W (18.00mm x 4.00mm)  Height - Seated (Max)  0.366" (9.30mm)  Termination  PC Pins  Lead Spacing  0.591" (15.00mm)  Applications  EMI, RFI Suppression  Features  X2 Safety Rated	Dielectric Material	Polypropylene (PP), Metallized
Mounting Type Through Hole Package / Case Radial Size / Dimension 0.709" L x 0.157" W (18.00mm x 4.00mm) Height - Seated (Max) 0.366" (9.30mm) Termination PC Pins Lead Spacing 0.591" (15.00mm) Applications EMI, RFI Suppression Features X2 Safety Rated	ESR (Equivalent Series Resistance)	-
Package / CaseRadialSize / Dimension0.709" L x 0.157" W (18.00mm x 4.00mm)Height - Seated (Max)0.366" (9.30mm)TerminationPC PinsLead Spacing0.591" (15.00mm)ApplicationsEMI, RFI SuppressionFeaturesX2 Safety Rated	Operating Temperature	-40°C ~ 110°C
Size / Dimension0.709" L x 0.157" W (18.00mm x 4.00mm)Height - Seated (Max)0.366" (9.30mm)TerminationPC PinsLead Spacing0.591" (15.00mm)ApplicationsEMI, RFI SuppressionFeaturesX2 Safety Rated	Mounting Type	Through Hole
Height - Seated (Max)  Termination  PC Pins  Lead Spacing  0.591" (15.00mm)  Applications  EMI, RFI Suppression  Features  X2 Safety Rated	Package / Case	Radial
Termination PC Pins  Lead Spacing 0.591" (15.00mm)  Applications EMI, RFI Suppression  Features X2 Safety Rated	Size / Dimension	0.709" L x 0.157" W (18.00mm x 4.00mm)
Lead Spacing0.591" (15.00mm)ApplicationsEMI, RFI SuppressionFeaturesX2 Safety Rated	Height - Seated (Max)	0.366" (9.30mm)
Applications EMI, RFI Suppression Features X2 Safety Rated	Termination	PC Pins
Features X2 Safety Rated	Lead Spacing	0.591" (15.00mm)
·	Applications	EMI, RFI Suppression
Report errors?	Features	X2 Safety Rated
		Report errors?

#### 223MKP275KB Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## 223MKP275KB Payment Methods





















### 223MKP275KB Shipping Methods













If you have any question about 223MKP275KB, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com