

225P33492YD3

225P33492YD3 Information

	Heisener.com	 225P33492YD3 Cornell Dubilier Electronics (CDE) Capacitors Film Capacitors CAP FILM 0.33UF 10% 200VDC RAD Radial For the pricing/inventory/lead time, please contact	
	For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



225P33492YD3 Specifications

ManufacturerCornell Dubilier Electronics (CDE)CapacitorsFilm CapacitorsPackageRadialSeriesOrange Drop? 225PCapacitance0.33μFTolerance±10%Voltage Rating - AC-Voltage Rating - DC200VDielectric MaterialPolyesterSeries Resistance)-Operating Temperature-55°C ~ 85°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension1.250° L x 0.409° W (31.80mm x 10.40mm)Height - Seated (Max)0.709° (18.00mm)PerminationPC PinsLead Spacing0.720° (18.30mm)ApplicationsDC Link, DC FilteringFeatures-		
CategoryCapacitorsFilm CapacitorsPackageRadialSeriesOrange Drop? 225PCapacitance0.33µFTolerance±10%Voltage Rating - AC~Voltage Rating - DC200VDielectric MaterialPolyesterCoperating Temperature-55°C ~ 85°CMounting TypeRadialPackage / CaseRadialSize / Dimension1.250° L x 0.409° W (31.80mm x 10.40mm)Height - Seated (Max)Orong "(18.00mm)FerminationPC PinsLad Spacing0.720° (18.30mm)ApplicationsDC Link, DC FilteringFeatures-	Manufacturer Part Number	225P33492YD3
Filn CapacitorsPackageRadialSeriesOrange Drop? 225PCapacitance0.33μFTolerance±10%Voltage Rating - AC-Voltage Rating - DC200VDielectric MaterialPolyesterESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 85°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension1.250° L x 0.409° W (31.80mm x 10.40mm)FerminationPC PinsLead Spacing0.700° (18.30mm)ApplicationsDC Link, DC FilteringFeatures-	Manufacturer	Cornell Dubilier Electronics (CDE)
PackageRadialSeriesOrange Drop? 225PCapacitance0.33µFTolerance±10%Voltage Rating - AC-Voltage Rating - DC200VDielectric MaterialPolyesterESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 85°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension1.250" L x 0.409" W (31.80mm x 10.40mm)Height - Seated (Max)0.709" (18.00mm)CarefinationPC PinsLead Spacing0.720" (18.30mm)ApplicationsDC Link, DC FilteringFeatures-	Category	Capacitors
Series Orange Drop? 225P Capacitance 0.33µF Tolerance ±10% Voltage Rating - AC - Voltage Rating - DC 200V Dielectric Material Polyester ESR (Equivalent Series Resistance) - Operating Temperature -55°C ~ 85°C Mounting Type Through Hole Package / Case Radial Size / Dimension 1.250" L x 0.409" W (31.80mm x 10.40mm) Height - Seated (Max) 0.709" (18.00mm) Termination PC Pins Lead Spacing 0.720" (18.30mm) Applications JC Link, DC Filtering Features -		Film Capacitors
Capacitance0.33µFTolerance±10%Voltage Rating - AC-Voltage Rating - DC200VDielectric MaterialPolyesterESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 85°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension1.250" L x 0.409" W (31.80mm x 10.40mm)Height - Seated (Max)0.709" (18.00mm)TerminationPC PinsLead Spacing0.720" (18.30mm)Applications-Features-	Package	Radial
Tolerance±10%Voltage Rating - AC-Voltage Rating - DC200VDielectric MaterialPolyesterESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 85°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension1.250° L x 0.409° W (31.80mm x 10.40mm)Height - Seated (Max)0.709° (18.00mm)TerminationPC PinsLead Spacing0.720° (18.30mm)ApplicationsDC Link, DC FilteringFeatures-	Series	Orange Drop? 225P
Voltage Rating - AC-Voltage Rating - DC200VDielectric MaterialPolyesterESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 85°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension1.250" L x 0.409" W (31.80mm x 10.40mm)Height - Seated (Max)0.709" (18.00mm)TerminationPC PinsLead Spacing0.720" (18.30mm)ApplicationsDC Link, DC FilteringFeatures-	Capacitance	0.33µF
Voltage Rating - DC200VDielectric MaterialPolyesterESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 85°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension1.250" L x 0.409" W (31.80mm x 10.40mm)Height - Seated (Max)0.709" (18.00mm)TerminationPC PinsLead Spacing0.720" (18.30mm)ApplicationsDC Link, DC FilteringFeatures-	Tolerance	±10%
Dielectric MaterialPolyesterESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 85°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension1.250" L x 0.409" W (31.80mm x 10.40mm)Height - Seated (Max)0.709" (18.00mm)TerminationPC PinsLead Spacing0.720" (18.30mm)ApplicationsDC Link, DC FilteringFeatures-	Voltage Rating - AC	-
ESR (Equivalent Series Resistance) - Operating Temperature -55°C ~ 85°C Mounting Type Through Hole Package / Case Radial Size / Dimension 1.250" L x 0.409" W (31.80mm x 10.40mm) Height - Seated (Max) 0.709" (18.00mm) Termination PC Pins Lead Spacing 0.720" (18.30mm) Applications DC Link, DC Filtering Features -	Voltage Rating - DC	200V
Operating Temperature-55°C ~ 85°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension1.250" L x 0.409" W (31.80mm x 10.40mm)Height - Seated (Max)0.709" (18.00mm)TerminationPC PinsLead Spacing0.720" (18.30mm)ApplicationsDC Link, DC FilteringFeatures-	Dielectric Material	Polyester
Mounting TypeThrough HolePackage / CaseRadialPackage / Case1.250" L x 0.409" W (31.80mm x 10.40mm)Size / Dimension1.250" L x 0.409" W (31.80mm x 10.40mm)Height - Seated (Max)0.709" (18.00mm)TerminationPC PinsLead Spacing0.720" (18.30mm)ApplicationsDC Link, DC FilteringFeatures-	ESR (Equivalent Series Resistance)	-
Package / CaseRadialSize / Dimension1.250" L x 0.409" W (31.80mm x 10.40mm)Height - Seated (Max)0.709" (18.00mm)TerminationPC PinsLead Spacing0.720" (18.30mm)ApplicationsDC Link, DC FilteringFeatures-	Operating Temperature	-55°C ~ 85°C
Size / Dimension 1.250" L x 0.409" W (31.80mm x 10.40mm) Height - Seated (Max) 0.709" (18.00mm) Termination PC Pins Lead Spacing 0.720" (18.30mm) Applications DC Link, DC Filtering Features -	Mounting Type	Through Hole
Height - Seated (Max)0.709" (18.00mm)TerminationPC PinsLead Spacing0.720" (18.30mm)ApplicationsDC Link, DC FilteringFeatures-	Package / Case	Radial
TerminationPC PinsLead Spacing0.720" (18.30mm)ApplicationsDC Link, DC FilteringFeatures-	Size / Dimension	1.250" L x 0.409" W (31.80mm x 10.40mm)
Lead Spacing0.720" (18.30mm)ApplicationsDC Link, DC FilteringFeatures-	Height - Seated (Max)	0.709" (18.00mm)
ApplicationsDC Link, DC FilteringFeatures-	Termination	PC Pins
Features -	Lead Spacing	0.720" (18.30mm)
	Applications	DC Link, DC Filtering
Report errors?	Features	-
		Report errors?

225P33492YD3 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE GUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

225P33492YD3 Payment Methods



If you have any question about 225P33492YD3, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com